

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



standard

## **10RC250F 12-10 Female Disconnect** *Abb Installation Products, Inc*

Insulated Female Disconnect, Length 1.03 Inches, Width .29 s, Maximum Insulation .250, Tab Size .250X.032, Wire #12-#10 Awg, Color Yellow, Copper, Tin Plated 0 (lbs/each) Terminals & Connectors  Vertex of the Common Street Str
s, Maximum Insulation .250, Tab Size .250X.032, Wire #12-#10 Awg, Color Yellow, Copper, Tin Plated (Ibs/each) Terminals & Connectors  ORC-250F INS VIN FEM-250 DISC Insulated Female Disconnect, Length 1.03 Inches, Width .29 (Insulation .250, Tab Size .250x.032, Wire Range) 10 AWG, Color Yellow, Copper, Tin Plated
Terminals & Connectors  verted  ORC-250F INS VIN FEM-250 DISC  Insulated Female Disconnect, Length 1.03 Inches, Width .29  s, Maximum Insulation .250, Tab Size .250x.032, Wire Range 10 AWG, Color Yellow, Copper, Tin Plated
v ated ORC-250F INS VIN FEM-250 DISC Insulated Female Disconnect, Length 1.03 Inches, Width .29 s, Maximum Insulation .250, Tab Size .250x.032, Wire Range 10 AWG, Color Yellow, Copper, Tin Plated
orc-250F INS VIN FEM-250 DISC Insulated Female Disconnect, Length 1.03 Inches, Width .29 s, Maximum Insulation .250, Tab Size .250x.032, Wire Range 10 AWG, Color Yellow, Copper, Tin Plated
orc-250F INS VIN FEM-250 DISC Insulated Female Disconnect, Length 1.03 Inches, Width .29 s, Maximum Insulation .250, Tab Size .250x.032, Wire Range 10 AWG, Color Yellow, Copper, Tin Plated
orc-250F INS VIN FEM-250 DISC Insulated Female Disconnect, Length 1.03 Inches, Width .29 s, Maximum Insulation .250, Tab Size .250x.032, Wire Rango 10 AWG, Color Yellow, Copper, Tin Plated
orc-250F INS VIN FEM-250 DISC Insulated Female Disconnect, Length 1.03 Inches, Width .29 s, Maximum Insulation .250, Tab Size .250x.032, Wire Rango 10 AWG, Color Yellow, Copper, Tin Plated
ated ORC-250F INS VIN FEM-250 DISC Insulated Female Disconnect, Length 1.03 Inches, Width .29 s, Maximum Insulation .250, Tab Size .250x.032, Wire Range 10 AWG, Color Yellow, Copper, Tin Plated
ORC-250F INS VIN FEM-250 DISC Insulated Female Disconnect, Length 1.03 Inches, Width .29 s, Maximum Insulation .250, Tab Size .250x.032, Wire Range 10 AWG, Color Yellow, Copper, Tin Plated
Insulated Female Disconnect, Length 1.03 Inches, Width .29 s, Maximum Insulation .250, Tab Size .250x.032, Wire Range 10 AWG, Color Yellow, Copper, Tin Plated
Insulated Female Disconnect, Length 1.03 Inches, Width .29 s, Maximum Insulation .250, Tab Size .250x.032, Wire Range 10 AWG, Color Yellow, Copper, Tin Plated
s, Maximum Insulation .250, Tab Size .250x.032, Wire Range 10 AWG, Color Yellow, Copper, Tin Plated
• •
n Fem-250 Disc 12-10 Len 1.03
e construction of the female disconnect offers long-term idability. Brazed seam serrated barrel provides maximum e strength
on
210800523
250F
0800523
INALS
nsulated Female Disconnect
1

UL E66716 / UL E66716