

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941

We Deliver...Lower Cost, Quality Products, & Personal Service

Fax: 936-560-4685



1418N4SSM10 N4X Wallmount Encl W/Panel - 36 X 30 X 10 - 304 SS Hammond MFG.

Catalog Number	1418N4SSM10
Manufacturer	Hammond MFG.
Description	N4X Wallmount Encl W/Panel - 36 X 30 X 10 - 304 SS
Weight per unit	125.0 (lbs/each)
Product Category	

Features

Material Stainless Steel

Material, Color, and Finish

Color Unpainted

Dimensions and Weight

36 in x 30 in x 10 in Size

Descriptions

Description	N4X WALLMOUNT ENCL W/PANEL - 36 X 30 X 10 - 304 SS
extra long description	HMND 1418N4SSM10 NEMA 4X SS ENCL 36
Long Description	N4X Wallmount Encl w/panel - 36 x 30 x 10 - 304 SS
Product Type	·
Special Features	Formed 14 gauge 304 or 316 stainless steel. Smooth,
•	

continuously welded seams without knockouts, cutouts or holes. Door stiffeners are provided in the larger enclosures for extra rigidity. Welded brackets provide for enclosure mounting. Formed lip on door and enclosure excludes flowing liquids and contaminants. Stainless steel continuous hinge on door may be removed by pulling the stainless steel hinge pin. Door is secured with easily operated stainless steel clamps. Provision for

Manufacturer Information

Brand	Hammond MFG.
GTIN	00623980386201
Manufacturers Part Number	1418N4SSM10
UPC	623980386201

padlocking. Seaml

Taxonomies, Classifications, and Categories

Category Description	STEEL JUNCTION BOXES
Туре	Type 4X Stainless Steel Wallmount Enclosure

Availability

Status Inactive



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging Carton	1
Weight Per each	125
Uses, Certifications, and Standards	
Application	Designed for use as instrument enclosures, electric, hydraulic or pneumatic control housings, electrical junction boxes or terminal wiring enclosures. Provides protection where equipment may be hosed down or otherwise be very wet, or in specific applications where corrosion is a serious problem
Mounting	WALL
nema rating	13;3R;4X
standard	CSA, UL, CE