Series 5
Die Cast Aluminum Conduit Outlet Bodies, Covers & Gaskets

Series 5 die cast copper-free aluminum conduit bodies, covers and gaskets are available for use with rigid or EMT conduit (with set screw). Conduit bodies are available in trade sizes ½" to 4", in the most popular conduit body shapes (C, LB, LL, LR, T) and ½" to 2" in TB and X shapes. The Series 5 family is available as components or pre-packaged in various configurations as a SnapPack™ assembly. In addition, Series 5 is completely interchangeable with other manufacturers.



Applications:

- Act as pull outlets for conductors being installed
- Provide openings for making splices and taps in conductors
- Act as mounting outlets for lighting fixtures and wiring devices
- Connect conduit sections
- Provide taps for branch conduit runs
- Make 90° bends in conduit runs
- Provide for access to conductors for maintenance and future system changes

Features:

- Die cast copper-free aluminum construction is lightweight and corrosion-resistant for long, reliable service
- Epoxy powder coat finish provides additional corrosion resistance and an aesthetically-pleasing appearance
- Conduit bodies are supplied with threaded hubs for use with rigid/IMC conduit or as a combination body
- Combination bodies are supplied with tri-head set screws (slotted, Phillips, Robertson) for use with EMT or rigid/IMC conduit on trade sizes ½" to 2"
- Domed aluminum cover provides additional cubic capacity
- Perforated center gasket that can be easily removed, if desired
- SnapPack™ available in choice of three configurations to match customer preferences

Certifications and Compliances:

- UL Listed
- cUL Listed
- UL File No. E-15022
- Suitable for wet locations (½" to 2" rigid bodies)
- Suitable for NEMA 4 (½" to 1" rigid bodies with integral gasket cover)

Standard Materials and Finishes:

- Bodies – copper-free aluminum with epoxy powder paint
- Covers – aluminum with stainless steel screws, natural
- Gaskets – neoprene, natural

Integral gasket covers. The sheet aluminum covers feature a raised dome with stainless steel screws supplied with nylon washers and a gasket for simplifying installation—reducing inventory and labor costs. These innovative covers are UL and cUL Listed and are NEMA 4 rated ½" to 1" trade sizes with rigid bodies.



SnapPack™. Designed for ordering and receiving convenience, the SnapPack combines a body, gasket and sheet aluminum cover in a single assembly.

1 Rigid body with traditional cover and gasket (e.g. LB15 CGN)




2 Combination body with traditional cover and gasket (e.g. LB15 MTC)



3 **NEMA 4** rigid body with integral gasketed cover (e.g. X15 ICG)



Series 5
Die Cast Aluminum Conduit Outlet Bodies, Covers & Gaskets



TYPE LB

Size	Outlet Body: Cat. # Rigid/IMC	Outlet Body: Cat. # Combo EMT, Rigid/IMC	SnapPack: Cat. # Rigid/IMC Body, Traditional Cover & Gasket	SnapPack: Cat. # Combo EMT, Body, Traditional Cover & Gasket	SnapPack: Cat. # NEMA 4 Rigid/IMC Body, Integral Cover & Gasket	Internal Vol. in Cu. In.	Unit Qty.	Wt. Lbs. Per 100*	Max. No. of Conductors
½"	**LB15**	**LB15 MT**	**LB15 CGN**	**LB15 MTC**	**LB15 ICG (4.5 Cu. In.)**	4.35	10	26	-
¾"	**LB25**	**LB25 MT**	**LB25 CGN**	**LB25 MTC**	**LB25 ICG (7.5 Cu. In.)**	7.30	10	48	#6 AWG
1"	**LB35**	**LB35 MT**	**LB35 CGN**	**LB35 MTC**	**LB35 ICG (10.8 Cu. In.)**	12.20	5	64	3 #4 AWG
1¼"	**LB45**	**LB45 MT**	**LB45 CGN**	**LB45 MTC**	-	32.30	2	140	3 #2 AWG
1½"	**LB55**	**LB55 MT**	**LB55 CGN**	**LB55 MTC**	-	33.80	2	160	3 #1/0 AWG
2"	**LB65**	**LB65 MT**	**LB65 CGN**	**LB65 MTC**	-	71.20	1	260	3 #3/0 AWG
2½"	**LB75**	**LB75 MT†**	**LB75 CGN**	**LB75 MTC**	-	71.20	1	500	3 #300MCM
3"	**LB85**	**LB85 MT†**	**LB85 CGN**	**LB85 MTC**	-	183.50	1	600	3 #300MCM
3½"	**LB95**	**LB95 MT†**	**LB95 CGN**	**LB95 MTC**	-	304.90	1	900	3 #400MCM
4"	**LB105**	**LB105 MT†**	**LB105 CGN**	**LB105 MTC**	-	308.00	1	1000	3 #400MCM

*Weight lbs. per 100 is listed for outlet body only.
†Combo EMT, rigid/IMC fittings greater than 2" trade size are SET SCREW ONLY (not combination threaded and set screw).



TYPE LR

Size	Outlet Body: Cat. # Rigid/IMC	Outlet Body: Cat. # Combo EMT, Rigid/IMC	SnapPack: Cat. # Rigid/IMC Body, Traditional Cover & Gasket	SnapPack: Cat. # Combo EMT, Body, Traditional Cover & Gasket	SnapPack: Cat. # NEMA 4 Rigid/IMC Body, Integral Cover & Gasket	Internal Vol. in Cu. In.	Unit Qty.	Wt. Lbs. Per 100*	Max. No. of Conductors
½"	**LR15**	**LR15 MT**	**LR15 CGN**	**LR15 MTC**	**LR15 ICG (4.5 Cu. In.)**	4.35	10	26	-
¾"	**LR25**	**LR25 MT**	**LR25 CGN**	**LR25 MTC**	**LR25 ICG (7.5 Cu. In.)**	7.30	10	48	#6 AWG
1"	**LR35**	**LR35 MT**	**LR35 CGN**	**LR35 MTC**	**LR35 ICG (10.8 Cu. In.)**	12.20	5	64	3 #4 AWG
1¼"	**LR45**	**LR45 MT**	**LR45 CGN**	**LR45 MTC**	-	35.80	2	140	3 #2 AWG
1½"	**LR55**	**LR55 MT**	**LR55 CGN**	**LR55 MTC**	-	35.80	2	160	3 #1/0 AWG
2"	**LR65**	**LR65 MT**	**LR65 CGN**	**LR65 MTC**	-	69.70	1	260	3 #3/0 AWG
2½"	**LR75**	-	**LR75 CGN**	-	-	69.70	1	500	3 #300MCM
3"	**LR85**	-	**LR85 CGN**	-	-	186.00	1	600	3 #350MCM
3½"	**LR95**	-	**LR95 CGN**	-	-	306.00	1	900	3 #350MCM
4"	**LR105**	-	**LR105 CGN**	-	-	308.00	1	1000	3 #350MCM

*Weight lbs. per 100 is listed for outlet body only.

 Copyright© 2015 Commercial Products Catalog

Series 5
Die Cast Aluminum Conduit Outlet Bodies, Covers & Gaskets



TYPE LL

	Outlet Body		SnapPack						
Size	Cat. # Rigid/IMC	Cat. # Combo EMT, Rigid/IMC	Cat. # Rigid/IMC Body, Traditional Cover & Gasket	Cat. # Combo EMT, Body, Traditional Cover & Gasket	Cat. # NEMA 4 Rigid/IMC Body, Integral Cover & Gasket	Internal Vol. in Cu. In.	Unit Qty.	Wt. Lbs. Per 100*	Max. No. of Conductors
½"	**LL15**	**LL15 MT**	**LL15 CGN**	**LL15 MTC**	**LL15 ICG (4.5 Cu. In.)**	4.35	10	30	-
¾"	**LL25**	**LL25 MT**	**LL25 CGN**	**LL25 MTC**	**LL25 ICG (7.5 Cu. In.)**	7.30	10	48	#6 AWG
1"	**LL35**	**LL35 MT**	**LL35 CGN**	**LL35 MTC**	**LL35 ICG (10.8 Cu. In.)**	12.20	5	64	3 #4 AWG
1¼"	**LL45**	**LL45 MT**	**LL45 CGN**	**LL45 MTC**	**-**	35.80	2	140	3 #2 AWG
1½"	**LL55**	**LL55 MT**	**LL55 CGN**	**LL55 MTC**	**-**	35.80	2	160	3 #1/0 AWG
2"	**LL65**	**LL65 MT**	**LL65 CGN**	**LL65 MTC**	**-**	69.70	1	270	3 #3/0 AWG
2½"	**LL75**	**-**	**LL75 CGN**	**-**	**-**	69.70	1	500	3 #300MCM
3"	**LL85**	**-**	**LL85 CGN**	**-**	**-**	186.00	1	600	3 #350MCM
3½"	**LL95**	**-**	**LL95 CGN**	**-**	**-**	306.00	1	900	3 #350MCM
4"	**LL105**	**-**	**LL105 CGN**	**-**	**-**	308.00	1	1000	3 #350MCM

*Weight lbs. per 100 is listed for outlet body only.




TYPE C

	Outlet Body		SnapPack						
Size	Cat. # Rigid/IMC	Cat. # Combo EMT, Rigid/IMC	Cat. # Rigid/IMC Body, Traditional Cover & Gasket	Cat. # Combo EMT, Body, Traditional Cover & Gasket	Cat. # NEMA 4 Rigid/IMC Body, Integral Cover & Gasket	Internal Vol. in Cu. In.	Unit Qty.	Wt. Lbs. Per 100*	Max. No. of Conductors
½"	**C15**	**C15 MT**	**C15 CGN**	**C15 MTC**	**C15 ICG (4.5 Cu. In.)**	4.35	10	27	-
¾"	**C25**	**C25 MT**	**C25 CGN**	**C25 MTC**	**C25 ICG (7.5 Cu. In.)**	7.30	10	40	#6 AWG
1"	**C35**	**C35 MT**	**C35 CGN**	**C35 MTC**	**C35 ICG (10.8 Cu. In.)**	12.20	5	64	3 #4 AWG
1¼"	**C45**	**C45 MT**	**C45 CGN**	**C45 MTC**	**-**	32.30	2	165	3 #2 AWG
1½"	**C55**	**C55 MT**	**C55 CGN**	**C55 MTC**	**-**	33.80	2	150	3 #1/0 AWG
2"	**C65**	**C65 MT**	**C65 CGN**	**C65 MTC**	**-**	69.50	1	270	3 #2/0 AWG
2½"	**C75**	**-**	**C75 CGN**	**-**	**-**	69.50	1	500	3 #250MCM
3"	**C85**	**-**	**C85 CGN**	**-**	**-**	188.00	1	600	3 #250MCM
3½"	**C95**	**-**	**C95 CGN**	**-**	**-**	307.00	1	900	3 #300MCM
4"	**C105**	**-**	**C105 CGN**	**-**	**-**	309.00	1	1000	3 #300MCM

*Weight lbs. per 100 is listed for outlet body only.

 Copyright© 2015 Commercial Products Catalog


Series 5
Die Cast Aluminum Conduit Outlet Bodies, Covers & Gaskets



TYPE T

Size	Outlet Body: Cat. # Rigid/IMC	Outlet Body: Cat. # Combo EMT, Rigid/IMC	SnapPack: Cat. # Rigid/IMC Body, Traditional Cover & Gasket	SnapPack: Cat. # Combo EMT, Body, Traditional Cover & Gasket	SnapPack: Cat. # NEMA 4 Rigid/IMC Body, Integral Cover & Gasket	Internal Vol. in Cu. In.	Unit Qty.	Wt. Lbs. Per 100*	Max. No. of Conductors
1/2"	**T15**	**T15 MT**	**T15 CGN**	**T15 MTC**	**T15 ICG (4.5 Cu. In.)**	4.35	10	27	-
3/4"	**T25**	**T25 MT**	**T25 CGN**	**T25 MTC**	**T25 ICG (7.5 Cu. In.)**	7.30	10	40	#6 AWG
1"	**T35**	**T35 MT**	**T35 CGN**	**T35 MTC**	**T35 ICG (10.8 Cu. In.)**	12.20	5	64	3 #4 AWG
1 1/4"	**T45**	**T45 MT**	**T45 CGN**	**T45 MTC**	-	33.10	2	165	3 #2 AWG
1 1/2"	**T55**	**T55 MT**	**T55 CGN**	**T55 MTC**	-	33.10	2	150	3 #2 AWG
2"	**T65**	**T65 MT**	**T65 CGN**	**T65 MTC**	-	67.00	1	270	3 #1 AWG
2 1/2"	**T75**	-	**T75 CGN**	-	-	67.00	1	500	3 #3/0 AWG
3"	**T85**	-	**T85 CGN**	-	-	175.00	1	600	3 #3/0 AWG
3 1/2"	**T95**	-	**T95 CGN**	-	-	298.00	1	900	3 #4/0 AWG
4"	**T105**	-	**T105 CGN**	-	-	300.00	1	1000	3 #4/0 AWG

*Weight lbs. per 100 is listed for outlet body only.



TYPE TB

Size	Outlet Body: Cat. # Rigid/IMC	Outlet Body: Cat. # Combo EMT, Rigid/IMC	SnapPack: Cat. # Rigid/IMC Body, Traditional Cover & Gasket	SnapPack: Cat. # Combo EMT, Body, Traditional Cover & Gasket	SnapPack: Cat. # NEMA 4 Rigid/IMC Body, Integral Cover & Gasket	Internal Vol. in Cu. In.	Unit Qty.	Wt. Lbs. Per 100*	Max. No. of Conductors
1/2"	**TB15**	-	-	-	**TB15 ICG (4.5 Cu. In.)**	4.50	10	29	-
3/4"	**TB25**	-	-	-	**TB25 ICG (7.5 Cu. In.)**	7.50	10	42	3 #6 AWG
1"	**TB35**	-	-	-	**TB35 ICG (10.8 Cu. In.)**	10.80	5	58	3 #4 AWG
1 1/4"	**TB45**	-	-	-	-	32.30	2	110	3 #2 AWG
1 1/2"	**TB55**	-	-	-	-	34.20	2	109	3 #2 AWG
2"	**TB65**	-	-	-	-	71.40	1	192	3 #2/0 AWG

*Weight lbs. per 100 is listed for outlet body only.



TYPE X

Size	Outlet Body: Cat. # Rigid/IMC	Outlet Body: Cat. # Combo EMT, Rigid/IMC	SnapPack: Cat. # Rigid/IMC Body, Traditional Cover & Gasket	SnapPack: Cat. # Combo EMT, Body, Traditional Cover & Gasket	SnapPack: Cat. # NEMA 4 Rigid/IMC Body, Integral Cover & Gasket	Internal Vol. in Cu. In.	Unit Qty.	Wt. Lbs. Per 100*	Max. No. of Conductors
1/2"	**X15**	-	-	-	**X15 ICG (4.5 Cu. In.)**	4.50	10	31	-
3/4"	**X25**	-	-	-	**X25 ICG (7.5 Cu. In.)**	7.50	10	47	3 #6 AWG
1"	**X35**	-	-	-	**X35 ICG (10.8 Cu. In.)**	10.80	5	62	3 #4 AWG
1 1/4"	**X45**	-	-	-	-	32.30	2	118	3 #2 AWG
1 1/2"	**X55**	-	-	-	-	34.20	2	118	3 #2 AWG
2"	**X65**	-	-	-	-	71.40	1	213	3 #2/0 AWG

*Weight lbs. per 100 is listed for outlet body only.

 Copyright© 2015 Commercial Products Catalog

Series 5
Die Cast Aluminum Conduit Outlet Bodies, Covers & Gaskets

INTEGRAL GASKET COVERS

Aluminum Cover with Neoprene Integral Gasket



Size	Cat. #	Unit Qty.	Wt. Lbs. Per 100
½"	**150G**	50	6
¾"	**250G**	50	7
1"	**350G**	50	8
1¼" - 1½"	**450G**	50	17
2"	**650G**	25	26
2½" - 3"	**850G**	10	80
3½" - 4"	**950G**	10	145

½" - 3" are NEMA 4 rated.

ALUMINUM COVERS

Aluminum




Size	Cat. #	Unit Qty.	Wt. Lbs. Per 100
½"	**150**	50	5
¾"	**250**	50	6
1"	**350**	50	7
1¼" - 1½"	**450**	50	15
2"	**650**	25	24
2½" - 3"	**850D**	10	78
3½" - 4"	**950D**	10	140

GASKETS

Neoprene




Size	Cat. #	Unit Qty.	Wt. Lbs. Per 100
½"	**GASK015N**	50	2
¾"	**GASK025N**	50	2
1"	**GASK035N**	50	3
1¼" - 1½"	**GASK045N**	50	6
2"	**GASK065N**	25	10
2½" - 3"	**GASK085N**	10	20
3½" - 4"	**GASK095N**	10	30



Type LB Dimensions (in Inches) – Threaded & Set Screw:


Size	A	B	C	D	E	F
½"	1.31	3.87	0.50	2.11	4.24	1.07
¾"	1.53	4.67	0.75	2.38	4.97	1.28
1"	1.74	5.37	1.00	2.74	5.79	1.56
1¼"	2.49	7.23	1.25	3.50	7.79	1.99
1½"	2.49	7.23	1.50	3.65	7.81	2.27
2"	3.10	9.46	2.00	4.24	10.20	2.91
2½"	4.44	12.22	2.50	5.75	13.14	3.43
3"	4.44	12.22	3.00	6.41	13.14	4.13
3½"	5.42	14.83	3.50	7.11	15.46	4.65
4"	5.42	14.83	4.00	7.20	15.46	5.16



Type LR Dimensions (in Inches) – Threaded & Set Screw:


Size	A	B	C	D	E	F
½"	1.31	3.87	0.50	2.06	4.40	1.40
¾"	1.53	4.67	0.75	2.28	5.07	1.64
1"	1.74	5.37	1.00	2.51	5.94	1.90
1¼"	2.49	7.23	1.25	3.50	7.87	2.85
1½"	2.49	7.23	1.50	3.50	7.87	2.85
2"	3.10	9.46	2.00	3.83	9.88	3.41
2½"	4.50	12.22	2.50	6.00	13.14	4.00
3"	4.65	12.22	3.00	6.10	13.00	4.70
3½"	5.42	14.83	3.50	6.40	15.45	5.43
4"	5.42	14.83	4.00	6.40	15.45	5.43

Series 5
Die Cast Aluminum Conduit Outlet Bodies, Covers & Gaskets




Type LL Dimensions (in Inches) – Threaded & Set Screw:

Size	A	B	C	D	E	F
½″	1.31	3.87	0.50	2.06	4.40	1.40
¾″	1.53	4.67	0.75	2.28	5.07	1.64
1″	1.74	5.37	1.00	2.68	5.94	1.90
1¼″	2.49	7.23	1.25	3.50	7.87	2.85
1½″	2.49	7.23	1.50	3.50	7.87	2.85
2″	3.10	9.46	2.00	3.83	10.20	3.41
2½″	4.50	12.22	2.50	6.00	13.14	4.00
3″	4.65	12.22	3.00	6.10	13.00	4.70
3½″	5.42	14.83	3.50	6.05	15.35	5.43
4″	5.42	14.83	4.00	6.05	15.35	5.43




Type C Dimensions (in Inches) – Threaded & Set Screw:

Size	A	B	C	D	E	F
½″	1.31	3.87	0.50	1.40	4.82	1.07
¾″	1.53	4.67	0.75	1.64	5.50	1.35
1″	1.74	5.37	1.00	1.90	6.44	1.67
1¼″	2.49	7.23	1.25	2.73	8.45	2.27
1½″	2.49	7.23	1.50	2.73	8.45	2.27
2″	3.10	9.46	2.00	3.41	10.71	2.91
2½″	4.50	12.22	2.50	4.30	14.00	3.50
3″	4.65	12.22	3.00	4.66	13.80	4.13
3½″	5.42	14.83	3.50	5.36	16.10	5.30
4″	5.42	14.83	4.00	5.36	16.10	5.30




Type T Dimensions (in Inches) – Threaded & Set Screw:

Size	A	B	C	D	E	F
½″	1.31	3.87	0.50	1.40	4.82	1.07
¾″	1.53	4.67	0.75	1.64	5.40	1.35
1″	1.74	5.37	1.00	1.90	6.33	1.15
1¼″	2.49	7.23	1.25	2.73	8.45	2.27
1½″	2.49	7.23	1.50	2.73	8.45	2.27
2″	3.10	9.46	2.00	3.41	10.71	2.91
2½″	4.50	12.22	2.50	4.00	14.00	3.50
3″	4.65	12.22	3.00	4.66	13.80	4.13
3½″	5.42	14.83	3.50	5.40	16.00	5.30
4″	5.42	14.83	4.00	5.40	16.00	5.30



Type TB Dimensions (in Inches) – Threaded & Set Screw:

Size	A	B	C	D	E	F
½″	1.31	3.92	0.50	2.10	4.72	1.07
¾″	1.53	4.64	0.75	2.40	5.51	1.28
1″	1.74	5.38	1.00	2.77	6.47	1.56
1¼″	2.49	7.24	1.25	3.53	8.25	1.99
1½″	2.49	7.24	1.50	3.53	8.25	2.27
2″	3.10	9.50	2.00	4.50	10.50	2.91



Type X Dimensions (in Inches) – Threaded & Set Screw:

Size	A	B	C	D	E	F
½″	1.31	3.92	0.50	1.37	4.72	1.07
¾″	1.53	4.64	0.75	1.63	5.51	1.28
1″	1.74	5.38	1.00	1.88	6.47	1.56
1¼″	2.49	7.24	1.25	2.51	8.25	1.99
1½″	2.49	7.24	1.50	2.50	8.25	2.27
2″	3.10	9.50	2.00	3.40	10.50	2.91

 Copyright© 2015 Commercial Products Catalog

Series 5
Die Cast Aluminum Conduit Outlet Bodies, Covers & Gaskets

Series 5 die cast copper-free aluminum conduit bodies, covers and gaskets are available for use with rigid or EMT conduit (with set screw). Conduit bodies are available in trade sizes ½" to 4", in the most popular conduit body shapes (C, LB, LL, LR, T) and ½" to 2" in TB and X shapes. The Series 5 family is available as components or pre-packaged in various configurations as a SnapPack™ assembly. In addition, Series 5 is completely interchangeable with other manufacturers.



Applications:

- Act as pull outlets for conductors being installed
- Provide openings for making splices and taps in conductors
- Act as mounting outlets for lighting fixtures and wiring devices
- Connect conduit sections
- Provide taps for branch conduit runs
- Make 90° bends in conduit runs
- Provide for access to conductors for maintenance and future system changes

Features:

- Die cast copper-free aluminum construction is lightweight and corrosion-resistant for long, reliable service
- Epoxy powder coat finish provides additional corrosion resistance and an aesthetically-pleasing appearance
- Conduit bodies are supplied with threaded hubs for use with rigid/IMC conduit or as a combination body
- Combination bodies are supplied with tri-head set screws (slotted, Phillips, Robertson) for use with EMT or rigid/IMC conduit on trade sizes ½" to 2"
- Domed aluminum cover provides additional cubic capacity
- Perforated center gasket that can be easily removed, if desired
- SnapPack™ available in choice of three configurations to match customer preferences

Certifications and Compliances:

- UL Listed
- cUL Listed
- UL File No. E-15022
- Suitable for wet locations (½" to 2" rigid bodies)
- Suitable for NEMA 4 (½" to 1" rigid bodies with integral gasket cover)

Standard Materials and Finishes:

- Bodies – copper-free aluminum with epoxy powder paint
- Covers – aluminum with stainless steel screws, natural
- Gaskets – neoprene, natural

Integral gasket covers. The sheet aluminum covers feature a raised dome with stainless steel screws supplied with nylon washers and a gasket for simplifying installation—reducing inventory and labor costs. These innovative covers are UL and cUL Listed and are NEMA 4 rated ½" to 1" trade sizes with rigid bodies.



SnapPack™. Designed for ordering and receiving convenience, the SnapPack combines a body, gasket and sheet aluminum cover in a single assembly.

1 Rigid body with traditional cover and gasket (e.g. LB15 CGN)




2 Combination body with traditional cover and gasket (e.g. LB15 MTC)



3 **NEMA 4** rigid body with integral gasketed cover (e.g. X15 ICG)



Series 5
Die Cast Aluminum Conduit Outlet Bodies, Covers & Gaskets



TYPE LB

Size	Outlet Body: Cat. # Rigid/IMC	Outlet Body: Cat. # Combo EMT, Rigid/IMC	SnapPack: Cat. # Rigid/IMC Body, Traditional Cover & Gasket	SnapPack: Cat. # Combo EMT, Body, Traditional Cover & Gasket	SnapPack: Cat. # NEMA 4 Rigid/IMC Body, Integral Cover & Gasket	Internal Vol. in Cu. In.	Unit Qty.	Wt. Lbs. Per 100*	Max. No. of Conductors
½"	**LB15**	**LB15 MT**	**LB15 CGN**	**LB15 MTC**	**LB15 ICG (4.5 Cu. In.)**	4.35	10	26	-
¾"	**LB25**	**LB25 MT**	**LB25 CGN**	**LB25 MTC**	**LB25 ICG (7.5 Cu. In.)**	7.30	10	48	#6 AWG
1"	**LB35**	**LB35 MT**	**LB35 CGN**	**LB35 MTC**	**LB35 ICG (10.8 Cu. In.)**	12.20	5	64	3 #4 AWG
1¼"	**LB45**	**LB45 MT**	**LB45 CGN**	**LB45 MTC**	-	32.30	2	140	3 #2 AWG
1½"	**LB55**	**LB55 MT**	**LB55 CGN**	**LB55 MTC**	-	33.80	2	160	3 #1/0 AWG
2"	**LB65**	**LB65 MT**	**LB65 CGN**	**LB65 MTC**	-	71.20	1	260	3 #3/0 AWG
2½"	**LB75**	**LB75 MT†**	**LB75 CGN**	**LB75 MTC**	-	71.20	1	500	3 #300MCM
3"	**LB85**	**LB85 MT†**	**LB85 CGN**	**LB85 MTC**	-	183.50	1	600	3 #300MCM
3½"	**LB95**	**LB95 MT†**	**LB95 CGN**	**LB95 MTC**	-	304.90	1	900	3 #400MCM
4"	**LB105**	**LB105 MT†**	**LB105 CGN**	**LB105 MTC**	-	308.00	1	1000	3 #400MCM

*Weight lbs. per 100 is listed for outlet body only.
†Combo EMT, rigid/IMC fittings greater than 2" trade size are SET SCREW ONLY (not combination threaded and set screw).



TYPE LR

Size	Outlet Body: Cat. # Rigid/IMC	Outlet Body: Cat. # Combo EMT, Rigid/IMC	SnapPack: Cat. # Rigid/IMC Body, Traditional Cover & Gasket	SnapPack: Cat. # Combo EMT, Body, Traditional Cover & Gasket	SnapPack: Cat. # NEMA 4 Rigid/IMC Body, Integral Cover & Gasket	Internal Vol. in Cu. In.	Unit Qty.	Wt. Lbs. Per 100*	Max. No. of Conductors
½"	**LR15**	**LR15 MT**	**LR15 CGN**	**LR15 MTC**	**LR15 ICG (4.5 Cu. In.)**	4.35	10	26	-
¾"	**LR25**	**LR25 MT**	**LR25 CGN**	**LR25 MTC**	**LR25 ICG (7.5 Cu. In.)**	7.30	10	48	#6 AWG
1"	**LR35**	**LR35 MT**	**LR35 CGN**	**LR35 MTC**	**LR35 ICG (10.8 Cu. In.)**	12.20	5	64	3 #4 AWG
1¼"	**LR45**	**LR45 MT**	**LR45 CGN**	**LR45 MTC**	-	35.80	2	140	3 #2 AWG
1½"	**LR55**	**LR55 MT**	**LR55 CGN**	**LR55 MTC**	-	35.80	2	160	3 #1/0 AWG
2"	**LR65**	**LR65 MT**	**LR65 CGN**	**LR65 MTC**	-	69.70	1	260	3 #3/0 AWG
2½"	**LR75**	-	**LR75 CGN**	-	-	69.70	1	500	3 #300MCM
3"	**LR85**	-	**LR85 CGN**	-	-	186.00	1	600	3 #350MCM
3½"	**LR95**	-	**LR95 CGN**	-	-	306.00	1	900	3 #350MCM
4"	**LR105**	-	**LR105 CGN**	-	-	308.00	1	1000	3 #350MCM

*Weight lbs. per 100 is listed for outlet body only.

 Copyright© 2015 Commercial Products Catalog

Series 5
Die Cast Aluminum Conduit Outlet Bodies, Covers & Gaskets



TYPE LL

	Outlet Body		SnapPack						
Size	Cat. # Rigid/IMC	Cat. # Combo EMT, Rigid/IMC	Cat. # Rigid/IMC Body, Traditional Cover & Gasket	Cat. # Combo EMT, Body, Traditional Cover & Gasket	Cat. # NEMA 4 Rigid/IMC Body, Integral Cover & Gasket	Internal Vol. in Cu. In.	Unit Qty.	Wt. Lbs. Per 100*	Max. No. of Conductors
½"	**LL15**	**LL15 MT**	**LL15 CGN**	**LL15 MTC**	**LL15 ICG (4.5 Cu. In.)**	4.35	10	30	-
¾"	**LL25**	**LL25 MT**	**LL25 CGN**	**LL25 MTC**	**LL25 ICG (7.5 Cu. In.)**	7.30	10	48	#6 AWG
1"	**LL35**	**LL35 MT**	**LL35 CGN**	**LL35 MTC**	**LL35 ICG (10.8 Cu. In.)**	12.20	5	64	3 #4 AWG
1¼"	**LL45**	**LL45 MT**	**LL45 CGN**	**LL45 MTC**	**-**	35.80	2	140	3 #2 AWG
1½"	**LL55**	**LL55 MT**	**LL55 CGN**	**LL55 MTC**	**-**	35.80	2	160	3 #1/0 AWG
2"	**LL65**	**LL65 MT**	**LL65 CGN**	**LL65 MTC**	**-**	69.70	1	270	3 #3/0 AWG
2½"	**LL75**	**-**	**LL75 CGN**	**-**	**-**	69.70	1	500	3 #300MCM
3"	**LL85**	**-**	**LL85 CGN**	**-**	**-**	186.00	1	600	3 #350MCM
3½"	**LL95**	**-**	**LL95 CGN**	**-**	**-**	306.00	1	900	3 #350MCM
4"	**LL105**	**-**	**LL105 CGN**	**-**	**-**	308.00	1	1000	3 #350MCM

*Weight lbs. per 100 is listed for outlet body only.




TYPE C

	Outlet Body		SnapPack						
Size	Cat. # Rigid/IMC	Cat. # Combo EMT, Rigid/IMC	Cat. # Rigid/IMC Body, Traditional Cover & Gasket	Cat. # Combo EMT, Body, Traditional Cover & Gasket	Cat. # NEMA 4 Rigid/IMC Body, Integral Cover & Gasket	Internal Vol. in Cu. In.	Unit Qty.	Wt. Lbs. Per 100*	Max. No. of Conductors
½"	**C15**	**C15 MT**	**C15 CGN**	**C15 MTC**	**C15 ICG (4.5 Cu. In.)**	4.35	10	27	-
¾"	**C25**	**C25 MT**	**C25 CGN**	**C25 MTC**	**C25 ICG (7.5 Cu. In.)**	7.30	10	40	#6 AWG
1"	**C35**	**C35 MT**	**C35 CGN**	**C35 MTC**	**C35 ICG (10.8 Cu. In.)**	12.20	5	64	3 #4 AWG
1¼"	**C45**	**C45 MT**	**C45 CGN**	**C45 MTC**	**-**	32.30	2	165	3 #2 AWG
1½"	**C55**	**C55 MT**	**C55 CGN**	**C55 MTC**	**-**	33.80	2	150	3 #1/0 AWG
2"	**C65**	**C65 MT**	**C65 CGN**	**C65 MTC**	**-**	69.50	1	270	3 #2/0 AWG
2½"	**C75**	**-**	**C75 CGN**	**-**	**-**	69.50	1	500	3 #250MCM
3"	**C85**	**-**	**C85 CGN**	**-**	**-**	188.00	1	600	3 #250MCM
3½"	**C95**	**-**	**C95 CGN**	**-**	**-**	307.00	1	900	3 #300MCM
4"	**C105**	**-**	**C105 CGN**	**-**	**-**	309.00	1	1000	3 #300MCM

*Weight lbs. per 100 is listed for outlet body only.

 Copyright© 2015 Commercial Products Catalog


Series 5
Die Cast Aluminum Conduit Outlet Bodies, Covers & Gaskets



TYPE T

Size	Outlet Body: Cat. # Rigid/IMC	Outlet Body: Cat. # Combo EMT, Rigid/IMC	SnapPack: Cat. # Rigid/IMC Body, Traditional Cover & Gasket	SnapPack: Cat. # Combo EMT, Body, Traditional Cover & Gasket	SnapPack: Cat. # NEMA 4 Rigid/IMC Body, Integral Cover & Gasket	Internal Vol. in Cu. In.	Unit Qty.	Wt. Lbs. Per 100*	Max. No. of Conductors
1/2"	**T15**	**T15 MT**	**T15 CGN**	**T15 MTC**	**T15 ICG (4.5 Cu. In.)**	4.35	10	27	-
3/4"	**T25**	**T25 MT**	**T25 CGN**	**T25 MTC**	**T25 ICG (7.5 Cu. In.)**	7.30	10	40	#6 AWG
1"	**T35**	**T35 MT**	**T35 CGN**	**T35 MTC**	**T35 ICG (10.8 Cu. In.)**	12.20	5	64	3 #4 AWG
1 1/4"	**T45**	**T45 MT**	**T45 CGN**	**T45 MTC**	-	33.10	2	165	3 #2 AWG
1 1/2"	**T55**	**T55 MT**	**T55 CGN**	**T55 MTC**	-	33.10	2	150	3 #2 AWG
2"	**T65**	**T65 MT**	**T65 CGN**	**T65 MTC**	-	67.00	1	270	3 #1 AWG
2 1/2"	**T75**	-	**T75 CGN**	-	-	67.00	1	500	3 #3/0 AWG
3"	**T85**	-	**T85 CGN**	-	-	175.00	1	600	3 #3/0 AWG
3 1/2"	**T95**	-	**T95 CGN**	-	-	298.00	1	900	3 #4/0 AWG
4"	**T105**	-	**T105 CGN**	-	-	300.00	1	1000	3 #4/0 AWG

*Weight lbs. per 100 is listed for outlet body only.



TYPE TB

Size	Outlet Body: Cat. # Rigid/IMC	Outlet Body: Cat. # Combo EMT, Rigid/IMC	SnapPack: Cat. # Rigid/IMC Body, Traditional Cover & Gasket	SnapPack: Cat. # Combo EMT, Body, Traditional Cover & Gasket	SnapPack: Cat. # NEMA 4 Rigid/IMC Body, Integral Cover & Gasket	Internal Vol. in Cu. In.	Unit Qty.	Wt. Lbs. Per 100*	Max. No. of Conductors
1/2"	**TB15**	-	-	-	**TB15 ICG (4.5 Cu. In.)**	4.50	10	29	-
3/4"	**TB25**	-	-	-	**TB25 ICG (7.5 Cu. In.)**	7.50	10	42	3 #6 AWG
1"	**TB35**	-	-	-	**TB35 ICG (10.8 Cu. In.)**	10.80	5	58	3 #4 AWG
1 1/4"	**TB45**	-	-	-	-	32.30	2	110	3 #2 AWG
1 1/2"	**TB55**	-	-	-	-	34.20	2	109	3 #2 AWG
2"	**TB65**	-	-	-	-	71.40	1	192	3 #2/0 AWG

*Weight lbs. per 100 is listed for outlet body only.



TYPE X

Size	Outlet Body: Cat. # Rigid/IMC	Outlet Body: Cat. # Combo EMT, Rigid/IMC	SnapPack: Cat. # Rigid/IMC Body, Traditional Cover & Gasket	SnapPack: Cat. # Combo EMT, Body, Traditional Cover & Gasket	SnapPack: Cat. # NEMA 4 Rigid/IMC Body, Integral Cover & Gasket	Internal Vol. in Cu. In.	Unit Qty.	Wt. Lbs. Per 100*	Max. No. of Conductors
1/2"	**X15**	-	-	-	**X15 ICG (4.5 Cu. In.)**	4.50	10	31	-
3/4"	**X25**	-	-	-	**X25 ICG (7.5 Cu. In.)**	7.50	10	47	3 #6 AWG
1"	**X35**	-	-	-	**X35 ICG (10.8 Cu. In.)**	10.80	5	62	3 #4 AWG
1 1/4"	**X45**	-	-	-	-	32.30	2	118	3 #2 AWG
1 1/2"	**X55**	-	-	-	-	34.20	2	118	3 #2 AWG
2"	**X65**	-	-	-	-	71.40	1	213	3 #2/0 AWG

*Weight lbs. per 100 is listed for outlet body only.

 Copyright© 2015 Commercial Products Catalog

Series 5
Die Cast Aluminum Conduit Outlet Bodies, Covers & Gaskets

INTEGRAL GASKET COVERS

Aluminum Cover with Neoprene Integral Gasket



Size	Cat. #	Unit Qty.	Wt. Lbs. Per 100
½"	**150G**	50	6
¾"	**250G**	50	7
1"	**350G**	50	8
1¼" - 1½"	**450G**	50	17
2"	**650G**	25	26
2½" - 3"	**850G**	10	80
3½" - 4"	**950G**	10	145

½" - 3" are NEMA 4 rated.

ALUMINUM COVERS

Aluminum




Size	Cat. #	Unit Qty.	Wt. Lbs. Per 100
½"	**150**	50	5
¾"	**250**	50	6
1"	**350**	50	7
1¼" - 1½"	**450**	50	15
2"	**650**	25	24
2½" - 3"	**850D**	10	78
3½" - 4"	**950D**	10	140

GASKETS

Neoprene




Size	Cat. #	Unit Qty.	Wt. Lbs. Per 100
½"	**GASK015N**	50	2
¾"	**GASK025N**	50	2
1"	**GASK035N**	50	3
1¼" - 1½"	**GASK045N**	50	6
2"	**GASK065N**	25	10
2½" - 3"	**GASK085N**	10	20
3½" - 4"	**GASK095N**	10	30



Type LB Dimensions (in Inches) – Threaded & Set Screw:


Size	A	B	C	D	E	F
½"	1.31	3.87	0.50	2.11	4.24	1.07
¾"	1.53	4.67	0.75	2.38	4.97	1.28
1"	1.74	5.37	1.00	2.74	5.79	1.56
1¼"	2.49	7.23	1.25	3.50	7.79	1.99
1½"	2.49	7.23	1.50	3.65	7.81	2.27
2"	3.10	9.46	2.00	4.24	10.20	2.91
2½"	4.44	12.22	2.50	5.75	13.14	3.43
3"	4.44	12.22	3.00	6.41	13.14	4.13
3½"	5.42	14.83	3.50	7.11	15.46	4.65
4"	5.42	14.83	4.00	7.20	15.46	5.16



Type LR Dimensions (in Inches) – Threaded & Set Screw:


Size	A	B	C	D	E	F
½"	1.31	3.87	0.50	2.06	4.40	1.40
¾"	1.53	4.67	0.75	2.28	5.07	1.64
1"	1.74	5.37	1.00	2.51	5.94	1.90
1¼"	2.49	7.23	1.25	3.50	7.87	2.85
1½"	2.49	7.23	1.50	3.50	7.87	2.85
2"	3.10	9.46	2.00	3.83	9.88	3.41
2½"	4.50	12.22	2.50	6.00	13.14	4.00
3"	4.65	12.22	3.00	6.10	13.00	4.70
3½"	5.42	14.83	3.50	6.40	15.45	5.43
4"	5.42	14.83	4.00	6.40	15.45	5.43

Series 5
Die Cast Aluminum Conduit Outlet Bodies, Covers & Gaskets




Type LL Dimensions (in Inches) – Threaded & Set Screw:

Size	A	B	C	D	E	F
½″	1.31	3.87	0.50	2.06	4.40	1.40
¾″	1.53	4.67	0.75	2.28	5.07	1.64
1″	1.74	5.37	1.00	2.68	5.94	1.90
1¼″	2.49	7.23	1.25	3.50	7.87	2.85
1½″	2.49	7.23	1.50	3.50	7.87	2.85
2″	3.10	9.46	2.00	3.83	10.20	3.41
2½″	4.50	12.22	2.50	6.00	13.14	4.00
3″	4.65	12.22	3.00	6.10	13.00	4.70
3½″	5.42	14.83	3.50	6.05	15.35	5.43
4″	5.42	14.83	4.00	6.05	15.35	5.43




Type C Dimensions (in Inches) – Threaded & Set Screw:

Size	A	B	C	D	E	F
½″	1.31	3.87	0.50	1.40	4.82	1.07
¾″	1.53	4.67	0.75	1.64	5.50	1.35
1″	1.74	5.37	1.00	1.90	6.44	1.67
1¼″	2.49	7.23	1.25	2.73	8.45	2.27
1½″	2.49	7.23	1.50	2.73	8.45	2.27
2″	3.10	9.46	2.00	3.41	10.71	2.91
2½″	4.50	12.22	2.50	4.30	14.00	3.50
3″	4.65	12.22	3.00	4.66	13.80	4.13
3½″	5.42	14.83	3.50	5.36	16.10	5.30
4″	5.42	14.83	4.00	5.36	16.10	5.30




Type T Dimensions (in Inches) – Threaded & Set Screw:

Size	A	B	C	D	E	F
½″	1.31	3.87	0.50	1.40	4.82	1.07
¾″	1.53	4.67	0.75	1.64	5.40	1.35
1″	1.74	5.37	1.00	1.90	6.33	1.15
1¼″	2.49	7.23	1.25	2.73	8.45	2.27
1½″	2.49	7.23	1.50	2.73	8.45	2.27
2″	3.10	9.46	2.00	3.41	10.71	2.91
2½″	4.50	12.22	2.50	4.00	14.00	3.50
3″	4.65	12.22	3.00	4.66	13.80	4.13
3½″	5.42	14.83	3.50	5.40	16.00	5.30
4″	5.42	14.83	4.00	5.40	16.00	5.30



Type TB Dimensions (in Inches) – Threaded & Set Screw:

Size	A	B	C	D	E	F
½″	1.31	3.92	0.50	2.10	4.72	1.07
¾″	1.53	4.64	0.75	2.40	5.51	1.28
1″	1.74	5.38	1.00	2.77	6.47	1.56
1¼″	2.49	7.24	1.25	3.53	8.25	1.99
1½″	2.49	7.24	1.50	3.53	8.25	2.27
2″	3.10	9.50	2.00	4.50	10.50	2.91



Type X Dimensions (in Inches) – Threaded & Set Screw:

Size	A	B	C	D	E	F
½″	1.31	3.92	0.50	1.37	4.72	1.07
¾″	1.53	4.64	0.75	1.63	5.51	1.28
1″	1.74	5.38	1.00	1.88	6.47	1.56
1¼″	2.49	7.24	1.25	2.51	8.25	1.99
1½″	2.49	7.24	1.50	2.50	8.25	2.27
2″	3.10	9.50	2.00	3.40	10.50	2.91

 Copyright© 2015 Commercial Products Catalog