

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



154DC 1-1/4" Watertight Hub *Bridgeport Fittings*

Catalog Number	154DC
Manufacturer	Bridgeport Fittings
Description	Threaded Hub, Zinc Die Cast, Size 1 1/4 Inch
Weight per unit	0.5200 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel

Features

Cable Entry	Through Rigid conduit into throat of fitting
Material	Zinc Die Cast
modia	Voc

Material, Color, and Finish

Finish	Ball burnish

Dimensions and Weight

Size 1-	-1/4
---------	------

Descriptions

Description	1-1/4" WATERTIGHT HUB
extra long description	BPT 154-DC 1 1/4" THREADED HUB
Long Description	Threaded Hub, Zinc Die Cast, Size 1 1/4 Inch
Product Type	1 1/4" Threaded Hub
Special Features	UL Type 4 Water Tight

Manufacturer Information

Brand	Bridgeport
GTIN	00781747091543
Manufacturers Part Number	154-DC
UPC	781747091543

Taxonomies, Classifications, and Categories

Category Description	Watertight Hub, 3-PIECE COUPLINGS, THREADLESS COUPLINGS	
	AND THREADLESS CONNECTOR	
Туре	Threaded Hubs	
Trade Size		
Trade Size	1 25	

Trade Size

.1.1.5	JUC JIZC	1 · Z J	
Packag	aina		
	yy		

Carton	5	
Package	25	
Weight Per each	0.52	



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	To secure threaded rigid service entrance conduit to box or
	enclosure. Insulated throat rated 105 degree c. UL listed Type 4 -
	Watertight. Suitable for Aluminum and Steel Rigid Conduit
standard	UL, CSA
Temperature Rating	105 C