

Market focused portfolio with products designed for broad applications

Value - competitive prices with industry-leading DLC listings

Performance - market leading performance with connected sensors options delivering value beyond lumens per watt






Whether lighting schools, offices, or hospitals on a budget, Metalux's commercial recessed products offer a complete family of innovative, affordable, and energy saving LED solutions for your next project.

Click on products to learn more

Good

Better

Best

| | |  |  |  |  |  |  | |
|----------------------------|----------------------------------|---|--|---|---|---|---|----------------------|
| | | GR8 Fluorescent | FP LED | AP GR | GR LED | RTC LED | FR LED Standard | FR LED High Perf. |
| APPLICABILITY ¹ | Education | ★ | ★★★ | ★★★ | ★★★ | ★★★ | ★★ | ★★ |
| | Office | ★ | ★★ | ★★ | ★★ | ★★★ | ★★★ | ★★★ |
| | Healthcare | ★ | ★ | ★★ | ★★ | ★★ | ★★ | ★★ |
| | Retail | ★ | ★★★ | ★★ | ★★ | ★★ | ★★ | ★★ |
| FEATURES / PERFORMANCE | Sizes | 1x4, 2x2, 2x4 | 1x4, 2x2, 2x4 | 2x2, 2x4 | 1x4, 2x2, 2x4 | 1x4, 2x2, 2x4 | 2x2, 2x4 | |
| | lm/W (Max) | < 90 (depends on lamp and ballast) | 124 | 140 | 140 | 126 | 130 | 150 |
| | Lum (Max) | 9000 | 7000 | 6400 | 18000 | 7000 | 3200 | 8000 |
| | Life (@60K) | L10 | L73 | L90 | L89 | L75 | L88 | |
| | Lens | Clear, Prismatic | Frost, Smooth | Clear, Prismatic | Frost, Prismatic | Frost, Ribbed | Frost, Smooth | |
| | Emergency | Integrated | Integrated | No | Integrated | Integrated | Integrated | |
| | CRI | 70 or 80 (depending on lamp selected) | 80 / 90 | 80+ | 80+ | 80+ | 80+ | |
| | Sensor Location | None | Tile Mount | Tile Mount | Integrated | Integrated | Integrated | |
| | DLC | None | Standard | Premium | Premium | Premium | Premium | |
| | Door | Yes | No | Yes | Yes | No | Yes | |
| INTERGRATED CONTROLS | Basic Occupancy | | | | ✓ | ✓ | ✓ | ✓ |
| | Stand Alone Daylight / Occupancy | | | | ✓ | ✓ | ✓ | ✓ |
| | WaveLinx | | | | ✓ | ✓ | ✓ | ✓ |
| | LumaWatt Pro | | | | ✓ | ✓ | ✓ | ✓ |
| | DLVP | | | | ✓ | | ✓ | ✓ |

Notes: 1. ★★ = high applicability, ★ = medium applicability, ★ = low applicability, blank = non-applicable

Market focused portfolio with products designed for broad applications

Value - competitive prices with industry-leading DLC listings

Performance - market leading performance with connected sensors options delivering value beyond lumens per watt





Whether lighting schools, offices, or hospitals on a budget, Metalux's commercial recessed products offer a complete family of innovative, affordable, and energy saving LED solutions for your next project.

Click on products to learn more

Good

Better

Best

| | |  |  |  |  |  |  | |
|----------------------------|----------------------------------|---|--|---|---|---|---|----------------------|
| | | GR8 Fluorescent | FP LED | AP GR | GR LED | RTC LED | FR LED Standard | FR LED High Perf. |
| APPLICABILITY ¹ | Education | ★ | ★★★ | ★★★ | ★★★ | ★★★ | ★★ | ★★ |
| | Office | ★ | ★★ | ★★ | ★★ | ★★★ | ★★★ | ★★★ |
| | Healthcare | ★ | ★ | ★★ | ★★ | ★★ | ★★ | ★★ |
| | Retail | ★ | ★★★ | ★★ | ★★ | ★★ | ★★ | ★★ |
| FEATURES / PERFORMANCE | Sizes | 1x4, 2x2, 2x4 | 1x4, 2x2, 2x4 | 2x2, 2x4 | 1x4, 2x2, 2x4 | 1x4, 2x2, 2x4 | 2x2, 2x4 | |
| | lm/W (Max) | < 90 <small>(depends on lamp and ballast)</small> | 124 | 140 | 140 | 126 | 130 | 150 |
| | Lum (Max) | 9000 | 7000 | 6400 | 18000 | 7000 | 3200 | 8000 |
| | Life (@60K) | L10 | L73 | L90 | L89 | L75 | L88 | |
| | Lens | Clear, Prismatic | Frost, Smooth | Clear, Prismatic | Frost, Prismatic | Frost, Ribbed | Frost, Smooth | |
| | Emergency | Integrated | Integrated | No | Integrated | Integrated | Integrated | |
| | CRI | 70 or 80 <small>(depending on lamp selected)</small> | 80 / 90 | 80+ | 80+ | 80+ | 80+ | |
| | Sensor Location | None | Tile Mount | Tile Mount | Integrated | Integrated | Integrated | |
| | DLC | None | Standard | Premium | Premium | Premium | Premium | |
| | Door | Yes | No | Yes | Yes | No | Yes | |
| INTERGRATED CONTROLS | Basic Occupancy | | | | ✓ | ✓ | ✓ | ✓ |
| | Stand Alone Daylight / Occupancy | | | | ✓ | ✓ | ✓ | ✓ |
| | WaveLinx | | | | ✓ | ✓ | ✓ | ✓ |
| | LumaWatt Pro | | | | ✓ | ✓ | ✓ | ✓ |
| | DLVP | | | | ✓ | ✓ | ✓ | ✓ |

Notes: 1. ★★ = high applicability, ★ = medium applicability, ★ = low applicability, blank = non-applicable