

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Carton

Weight Per each

257RTI2 3" Raintight Diecast Compression Connector *Nsi Industries*

Catalog Number	257RTI2
Manufacturer	Noi Industrias
Description	3" Raintight Insulated Connector, NPT Thread
Weight per unit	1.7 (lbs/each)
Product Category	Liquid Tight Fittings
- eatures	
Connector Type	Compression
insulation	Insulated Throat
media	Yes
Dimensions and Weight	
Size	3
Descriptions	
Description	3" RAINTIGHT DIECAST COMPRESSION CONNECTOR
extra long description	BPT 257-RTI2 3" RAINTIGHT INS CONNE
Features	Think Orange: Quality In, Water Out. Listed for Damp or Wet
	Locations.
Long Description	3" Raintight Insulated Connector, NPT THREAD
Product Type	G
Special Features	The Dual Internal sealing rings create a raintight seal.
Manufacturer Information	
Brand	Bridgeport
GTIN	00781747192578
Manufacturers Part Number	257-RTI2
UPC	781747192578
Taxonomies, Classifications, and (Categories
Category Description	METALLIC FITTINGS
Туре	Raintight Compression
Trade Size	
Trade Size	3
Packaging	
JJ	

12

1.725

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-56-7941

Fax: 936-560-4685

Uses, Certifications, and Standards

Application

Compression style connector with internal sealing ring and knockout gasket to create a raintight seal when connecting EMT to box or enclosure. With Bridgeport's newly redesigned Raintight Compression Connectors, 256-RTI2 thru 259-RTI2, contractors can install just one wet location fitting for either

thread less Rigid / IMC or EMT. These 3" dual Listed Zinc Alloy fittings come standard with a 105° C temperature rated insulated throat and the words "Rigid / EMT and RAINTIGHT" clearly cast

into the body. Thi

standard cULus