
# Commercial grade AC toggle combination switches

## Product description

Single-pole, 3-way
15A, 120/277V/AC; 15A, 120V/AC
20A, 120V/AC




271

### Toggle combination switches, back & side wire

| Rating A | Rating V/AC | Description | Color suffix | Catalog no. | |
|---|---|---|---|---|---|
| 15 | 120/277 | (2) Single-pole, switches | A, B, LA, V, W | ☐271__ | • |
| | | (1) Single-pole, switch with (1) 3-Way switch | B, LA, V, W | ☐275__ | • |
| | | (2) 3-Way, switches | LA, V, W | ☐276__ | • |
| 15 | 120 | (1) Single-pole, switch 1/25w (1) 125V pilot light | B, LA, V, W | ☐277__* | • |
| | | (1) 3-Way, switch w/pilot light 1/25w (1) 125V pilot light | B, V | ☐294__* | • |

* Not NOM cert




277

### Toggle switch with receptacle, back & side wire

| Rating A | Rating V/AC | Description | Color suffix | Catalog no. | |
|---|---|---|---|---|---|
| 15<br>15 | 120<br>125 | (1) Single-pole, switch with nema 5-15<br>(1) 2-Pole, 3-wire tamper resistant receptacle | A, B, BK, LA, V, W | ☐TR274___ | • |
| 15<br>15 | 120<br>125 | (1) 3-Way switch with nema 5-15<br>(1) 2-Pole, 3-wire tamper resistant receptacle | A, B, BK, LA, V, W | ☐TR293___ | • |
| 15<br>20 | 120<br>125 | (1) Single-pole, switch with nema 5-20<br>(1) 2-Pole, 3-wire tamper resistant receptacle | A, B, BK, LA, V, W | ☐TR291___* | • |

* Not NOM cert



TR274

### Accessories for commercial specification grade toggle combination switches

| Description | Catalog no. | | |
|---|---|---|---|
| 1-Gang, standard size duplex, 302/304 stainless steel receptacle wallplate | ☐93101 | • | • |
| 1-Gang, standard size duplex, unbreakable nylon receptacle wallplate, almond | ☐5132A | • | • |


93101


5132A

### Color ordering information:

For ordering devices, include Catalog no. Followed by the Color suffix: A (Almond), B (Brown), BK (Black), LA (Light Almond), V (Ivory), W (White)

| A | B | BK | LA | V | W |
|---|---|---|---|---|---|
| (Almond) | (Brown) | (Black) | (Lt. Almond) | (Ivory) | (White) |


**Specification information:** 120/277 V/AC commercial toggle combination: E-40
**Compliances, specifications and availability are subject to change without notice.**

Indicates NAFTA compliant - Page Q-30
RoHS compliant – Page Q-30

# Commercial grade AC toggle combination switches

## Product description

Single-pole, 3-way
15A, 120/277V/AC; 15A, 120V/AC
20A, 120V/AC




271

### Toggle combination switches, back & side wire

| Rating A | Rating V/AC | Description | Color suffix | Catalog no. | |
|---|---|---|---|---|---|
| 15 | 120/277 | (2) Single-pole, switches | A, B, LA, V, W | ☐271__ | • |
| | | (1) Single-pole, switch with (1) 3-Way switch | B, LA, V, W | ☐275__ | • |
| | | (2) 3-Way, switches | LA, V, W | ☐276__ | • |
| 15 | 120 | (1) Single-pole, switch 1/25w (1) 125V pilot light | B, LA, V, W | ☐277__* | • |
| | | (1) 3-Way, switch w/pilot light 1/25w (1) 125V pilot light | B, V | ☐294__* | • |

* Not NOM cert




277

### Toggle switch with receptacle, back & side wire

| Rating A | Rating V/AC | Description | Color suffix | Catalog no. | |
|---|---|---|---|---|---|
| 15<br>15 | 120<br>125 | (1) Single-pole, switch with nema 5-15<br>(1) 2-Pole, 3-wire tamper resistant receptacle | A, B, BK, LA, V, W | ☐TR274___ | • |
| 15<br>15 | 120<br>125 | (1) 3-Way switch with nema 5-15<br>(1) 2-Pole, 3-wire tamper resistant receptacle | A, B, BK, LA, V, W | ☐TR293___ | • |
| 15<br>20 | 120<br>125 | (1) Single-pole, switch with nema 5-20<br>(1) 2-Pole, 3-wire tamper resistant receptacle | A, B, BK, LA, V, W | ☐TR291___* | • |

* Not NOM cert



TR274

### Accessories for commercial specification grade toggle combination switches

| Description | Catalog no. | | |
|---|---|---|---|
| 1-Gang, standard size duplex, 302/304 stainless steel receptacle wallplate | ☐93101 | • | • |
| 1-Gang, standard size duplex, unbreakable nylon receptacle wallplate, almond | ☐5132A | • | • |


93101


5132A

### Color ordering information:

For ordering devices, include Catalog no. Followed by the Color suffix: A (Almond), B (Brown), BK (Black), LA (Light Almond), V (Ivory), W (White)

| A | B | BK | LA | V | W |
|---|---|---|---|---|---|
| (Almond) | (Brown) | (Black) | (Lt. Almond) | (Ivory) | (White) |

**Specification information:** 120/277 V/AC commercial toggle combination: E-40
**Compliances, specifications and availability are subject to change without notice.**

Indicates NAFTA compliant - Page Q-30
RoHS compliant – Page Q-30