

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

280DCX 3/8 MC FMC to 1/2" Emt *Nsi Industries*

Catalog Number	280DCX
Manufacturer	Nsi Industries
Description	Emt to Ac/MC/FMC/NM Transition Fitting
Weight per unit	0.0700 (lbs/each)
Product Category	Die Cast Set Screw Emt to Flex
Features	
Inside Diameter	0.615
outside diameter	0.093
Dimensions and Weight	
Length	1.51
Descriptions	
Description	3/8 MC FMC TO 1/2" EMT
extra long description	BPT 280-DCX 3/8 MC FMC to 1/2" EMT
Long Description	
Product Type	2/0 M/0 FM/0 to 1/0 Front
Special Features	For dry locations only. Max wire fill is 60% or 0.137 sq. inches.
Manufacturer Information	
Brand	Nsi Industries
Manufacturers Part Number	280-DCX
Taxonomies, Classifications, and (Categories
Type	COURLING
Trade Size	
Trade Size	0.5
	X!Y
Packaging Carton	1
Cai (OH	I

0.07

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941

Fax: 936-560-4685

Uses, Certifications, and Standards

Application

Transition fitting for use between 1/2" EMT to 3/8" Steel and Aluminum FMC, metal clad and armored cable assemblies with O.D. of .43-.61 (14/2 to 10/3 within the specified ranges), as well as 14/2 to 10/3 NM Cables, (2) 14/2 or (2) 12/2 NM Cables stacked, or the following combinations: 14/2 & 12/2, 14/2 & 12/3, 14/3 & 12/2. AC/MC should be prepared to the desired length and fed through the fitting. AC/MC/MCIA and FMC should be inserted until the armor engages with the endstop at the center of the fitting.

standard

UL