











Incandescent Lamps

Shape	Base	Order Watts Code	Description	Volts	Case Qty.	Filament Design	MOL	LCL	Rated Life Hours	Lumens Initial	Color Temp. K	CBCP	Beam Spread	Footnotes	Additional Information
INCANDESCENT LAMPS (CONTINUED)															
200 WATTS (CONTINUED)															
	PS30	Med	200 14636 200PS30/CVG	120	60	C-9	8.06	6	1000	3480				2A, 9L, 9M	Inside Frost-covRguard®, BB, Teflon® Coated
			14637 200PS30/RS/CVG	120	60	C-9	8.06	6	1000	3330				2A, 9L, 9M	Inside Frost-covRguard® Rough Service, BB, Teflon® Coated
			20316 200/SBIF	120	60	C-9	8.06	6	1000	3320					I.F.-Silvered Bowl
	200 20172	200		130	60	C-9	8.06	6	750	3540					Clear
	177			120					1950	2725					(Ratings @ 120 volts.)
	200 20252	200/IF		130	60	C-9	8.06	6	750	3540					Inside Frost
	177			120					1950	2725					(Ratings @ 120 volts.)
	200 20354	200/99IF		130	60	C-9	8.06	6	2500	3000					I.F.-Extended Service, BB
	177			120					6800	2310					(Ratings @ 120 volts.)
	200 20403	200PS30/24		130	60	C-9	8.06	6	1000	3240				2A, 5E	Clear-Rough Service
	177			120					2600	2495				2A, 5E	(Ratings @ 120 volts.)
	200 33468	200PS30/23 24PK		130	24	C-9	8.06	6	1000	3240				2A, 5E	I.F.-Rough Service
	177			120					2600	2495					(Ratings @ 120 volts.)
	200 20192	200		250	60	C-9	8.06	6	1000	2980					Clear
240 WATTS															
	A21	Med	240 15843 240A/RL/SW 6PK	120	30	CC-8	5.75	4.31	750	4300					Soft White-Reader Light™
	PAR56	Scr w Term	240 20575 240PAR56/VNSP	12	12	C-6	4.5		2000		2800	140000		1A, 2A, 5B, 5C, 9N	Very Narrow Reflector
			20576 240PAR56/MFL	12	12	C-6	4.5		2000		2800	46000		1A, 2A, 5B, 5C, 9N	Medium Flood
			20577 240PAR56/WFL	12	12	C-6	4.5		2000		2800	13000		1A, 2A, 5B, 5C, 9N	Wide Flood
250 WATTS															
	R40	Med	250 37770 250R40/1 6PK	120	30	C-9	6.56		5000	2200				2A, 2B, 3B, 5E, 6A	Reflector-Warm Up Infrared Heat Lamp - Clear Face
			37771 250R40/10 6PK	120	30	C-9	6.56		5000					2A, 2B, 3B, 5E, 6A	Reflector-Chill Chaser Infrared Heat Lamp. Red, HRG
			46881 250R40/1/CVG	120	30	C-9	6.56		5000	2150					Clear-covRguard® Teflon® Coated. Food Warming, Reflector-Infrared
	Med Skirt	250 20724	250R40/4	120	24	C-9	7.43		5000					2A, 2B, 3B, 5E, 6A	Reflector Infrared Industrial-Light I.F., BB
300 WATTS															
	PAR56	Scr w Term	300 23427 300PAR56/WFL	12	12	C-6	4.5		1000	6000				2B, 9F, 9N	PAR-Wide Flood. Swimming
	PAR56	Mog End Pr300	20803 300PAR56/NSP	120	12	CC-13	5		2000	3840	2750	68000		1A, 2A, 5B, 5C, 9N	Narrow Reflector
			20836 300PAR56/MFL	120	12	CC-13	5		2000	3840	2750	24000		1A, 2A, 5B, 5C, 9N	Medium Flood
			20849 300PAR56/WFL	120	12	CC-13	5		2000	3840	2750	11000		1A, 2A, 5B, 5C, 9N	Wide Flood
			20838 300PAR56/MFL	130	12	CC-13	5		2000	3840	2750	24000		1A, 2A, 5B, 5C, 9N	Medium Flood
			20851 300PAR56/WFL	130	12	CC-13	5		2000	3840	2750	11000		1A, 2A, 5B, 5C, 9N	Wide Flood
	PS25	Med	300 20861 300M	120	60	CC-8	6.93	5.18	750	6200					Clear
			25919 300M/IF 6PK	120	30	CC-8	6.93	5.18	750	6200					Inside Frost
	300 20863	300M		130	60	CC-8	6.93	5.18	750	6120					Clear
	266			120					1950	4170					(Ratings @ 120 volts.)
	300 20917	300M/IF		130	60	CC-8	6.93	5.18	750	6120					Inside Frost
	266			120					1950	4170					(Ratings @ 120 volts.)



Incandescent Lamps

Shape	Base	Order Watts Code	Description	Volts	Case Qty.	Filament Design	MOL	LCL	Rated Life Hours	Lumens Initial	Color Temp. K	CBCP	Beam Spread	Footnotes	Additional Information
INCANDESCENT LAMPS (CONTINUED)															
200 WATTS (CONTINUED)															
	PS30	Med	200 14636 200PS30/CVG	120	60	C-9	8.06	6	1000	3480				2A, 9L, 9M	Inside Frost-covRguard®, BB, Teflon® Coated
			14637 200PS30/RS/CVG	120	60	C-9	8.06	6	1000	3330				2A, 9L, 9M	Inside Frost-covRguard® Rough Service, BB, Teflon® Coated
			20316 200/SBIF	120	60	C-9	8.06	6	1000	3320					I.F.-Silvered Bowl
	200 20172	200		130	60	C-9	8.06	6	750	3540					Clear
	177			120					1950	2725					(Ratings @ 120 volts.)
	200 20252	200/IF		130	60	C-9	8.06	6	750	3540					Inside Frost
	177			120					1950	2725					(Ratings @ 120 volts.)
	200 20354	200/99IF		130	60	C-9	8.06	6	2500	3000					I.F.-Extended Service, BB
	177			120					6800	2310					(Ratings @ 120 volts.)
	200 20403	200PS30/24		130	60	C-9	8.06	6	1000	3240				2A, 5E	Clear-Rough Service
	177			120					2600	2495				2A, 5E	(Ratings @ 120 volts.)
	200 33468	200PS30/23 24PK		130	24	C-9	8.06	6	1000	3240				2A, 5E	I.F.-Rough Service
	177			120					2600	2495					(Ratings @ 120 volts.)
	200 20192	200		250	60	C-9	8.06	6	1000	2980					Clear
240 WATTS															
	A21	Med	240 15843 240A/RL/SW 6PK	120	30	CC-8	5.75	4.31	750	4300					Soft White-Reader Light™
	PAR56	Scrw Term	240 20575 240PAR56/VNSP	12	12	C-6	4.5		2000		2800	140000		1A, 2A, 5B, 5C, 9N	Very Narrow Reflector
			20576 240PAR56/MFL	12	12	C-6	4.5		2000		2800	46000		1A, 2A, 5B, 5C, 9N	Medium Flood
			20577 240PAR56/WFL	12	12	C-6	4.5		2000		2800	13000		1A, 2A, 5B, 5C, 9N	Wide Flood
250 WATTS															
	R40	Med	250 37770 250R40/1 6PK	120	30	C-9	6.56		5000	2200				2A, 2B, 3B, 5E, 6A	Reflector-Warm Up Infrared Heat Lamp - Clear Face
			37771 250R40/10 6PK	120	30	C-9	6.56		5000					2A, 2B, 3B, 5E, 6A	Reflector-Chill Chaser Infrared Heat Lamp. Red, HRG
			46881 250R40/1/CVG	120	30	C-9	6.56		5000	2150					Clear-covRguard® Teflon® Coated. Food Warming, Reflector-Infrared
	Med Skirt	250 20724	250R40/4	120	24	C-9	7.43		5000					2A, 2B, 3B, 5E, 6A	Reflector Infrared Industrial-Light I.F., BB
300 WATTS															
	PAR56	Scrw Term	300 23427 300PAR56/WFL	12	12	C-6	4.5		1000	6000				2B, 9F, 9N	PAR-Wide Flood. Swimming
	PAR56	Mog End Pr300	20803 300PAR56/NSP	120	12	CC-13	5		2000	3840	2750	68000		1A, 2A, 5B, 5C, 9N	Narrow Reflector
			20836 300PAR56/MFL	120	12	CC-13	5		2000	3840	2750	24000		1A, 2A, 5B, 5C, 9N	Medium Flood
			20849 300PAR56/WFL	120	12	CC-13	5		2000	3840	2750	11000		1A, 2A, 5B, 5C, 9N	Wide Flood
			20838 300PAR56/MFL	130	12	CC-13	5		2000	3840	2750	24000		1A, 2A, 5B, 5C, 9N	Medium Flood
			20851 300PAR56/WFL	130	12	CC-13	5		2000	3840	2750	11000		1A, 2A, 5B, 5C, 9N	Wide Flood
	PS25	Med	300 20861 300M	120	60	CC-8	6.93	5.18	750	6200					Clear
			25919 300M/IF 6PK	120	30	CC-8	6.93	5.18	750	6200					Inside Frost
	300 20863	300M		130	60	CC-8	6.93	5.18	750	6120					Clear
	266			120					1950	4170					(Ratings @ 120 volts.)
	300 20917	300M/IF		130	60	CC-8	6.93	5.18	750	6120					Inside Frost
	266			120					1950	4170					(Ratings @ 120 volts.)