


Type EFL

Aluminum Core Light Weight
Liquid-Tight Flexible Metal Conduit (LFMC)



Construction

- Constructed of continuously interlocked aluminum core for exceptional crush and corrosion resistance.
- Durable, sunlight resistant thermoplastic PVC jacket that resists heat, oil and chemical breakdown.



Square-Locked Design with cord packing 3/8" through 1-1/4"

Installation

- Conduit used with standard liquid-tight fitting for easy installation. IP 66/67 Rated when installed with approved fittings.
- Delivers superior wiring protection where agency approvals are not required.
- Manufactured in a full range of trade sizes from 3/8" through 4".
- Smooth appearing jacket for exposed applications.
- Rated for temperature range of -4°F to +176°F (-20°C to +80°C).
- Provides liquid-tight raceway for electrical conductors.



Interlocked Design 1-1/2" through 4"

See pages 23-28 for fittings



• RoHS WEEE COMPLIANT

Type EFL

Gray thermoplastic PVC jacket
no bonding wire



Product Specifications

Ordering Information

| Electrical Trade Size | | Inside Diameter | | Outside Diameter | | Approx Inside Bend Radius | Approx Weight lbs. | Standard Carton | |
|-----------------------|-----|-----------------|-------|------------------|-------|---------------------------|--------------------|-----------------|-------------|
| Inches | mm | Inches | | Inches | | | | Inches | PER 100 FT. |
| | | MIN. | MAX. | MIN. | MAX. | | | | |
| 3/8 | 12 | .485 | .505 | .690 | .710 | 2.0 | 14 | 100 | 38002 |
| 1/2 | 16 | .620 | .640 | .820 | .840 | 2.5 | 16 | 100 | 38012 |
| 3/4 | 21 | .815 | .835 | 1.030 | 1.050 | 3.0 | 19 | 100 | 38022 |
| 1 | 27 | 1.030 | 1.055 | 1.290 | 1.315 | 4.0 | 32 | 100 | 38031 |
| 1-1/4 | 35 | 1.370 | 1.395 | 1.635 | 1.660 | 4.5 | 42 | 50 | 38041 |
| 1-1/2 | 41 | 1.575 | 1.600 | 1.865 | 1.900 | 5.5 | 58 | 50 | 38051 |
| 2 | 53 | 2.020 | 2.045 | 2.340 | 2.375 | 7.0 | 78 | 50 | 38061 |
| 2-1/2 | 63 | 2.480 | 2.505 | 2.840 | 2.875 | 9.5 | 103 | 50 | 38071 |
| 3 | 78 | 3.070 | 3.100 | 3.460 | 3.500 | 15 | 123 | 25 | 38081 |
| 4 | 103 | 4.000 | 4.040 | 4.460 | 4.500 | 17 | 196 | 25 | 38091 |

NOTE: 1. Other colors available upon request.

TYPICAL SPECIFICATION:

Conduit shall be Anaconda SEALTITE® Type EFL. Conduit shall provide a flexible liquid-tight raceway for wiring and shall be constructed of continuously interlocked aluminum core with sunlight resistant PVC outer jacket. Type EFL conduit shall be used for applications where agency approvals are not required. Conduit IP 66/67 rated when installed with approved end fittings.

Type EFL

Aluminum Core Light Weight
Liquid-Tight Flexible Metal Conduit (LFMC)



Construction

- Constructed of continuously interlocked aluminum core for exceptional crush and corrosion resistance.
- Durable, sunlight resistant thermoplastic PVC jacket that resists heat, oil and chemical breakdown.



Square-Locked Design with cord packing 3/8" through 1-1/4"

Installation

- Conduit used with standard liquid-tight fitting for easy installation. IP 66/67 Rated when installed with approved fittings.
- Delivers superior wiring protection where agency approvals are not required.
- Manufactured in a full range of trade sizes from 3/8" through 4".
- Smooth appearing jacket for exposed applications.
- Rated for temperature range of -4°F to +176°F (-20°C to +80°C).
- Provides liquid-tight raceway for electrical conductors.



Interlocked Design 1-1/2" through 4"

See pages 23-28 for fittings



• RoHS WEEE COMPLIANT

Type EFL

Gray thermoplastic PVC jacket
no bonding wire



Product Specifications

Ordering Information

| Electrical Trade Size | | Inside Diameter | | Outside Diameter | | Approx Inside Bend Radius | Approx Weight lbs. | Standard Carton | |
|-----------------------|-----|-----------------|-------|------------------|-------|---------------------------|--------------------|-----------------|-------------|
| Inches | mm | Inches | | Inches | | | | Inches | PER 100 FT. |
| | | MIN. | MAX. | MIN. | MAX. | | | | |
| 3/8 | 12 | .485 | .505 | .690 | .710 | 2.0 | 14 | 100 | 38002 |
| 1/2 | 16 | .620 | .640 | .820 | .840 | 2.5 | 16 | 100 | 38012 |
| 3/4 | 21 | .815 | .835 | 1.030 | 1.050 | 3.0 | 19 | 100 | 38022 |
| 1 | 27 | 1.030 | 1.055 | 1.290 | 1.315 | 4.0 | 32 | 100 | 38031 |
| 1-1/4 | 35 | 1.370 | 1.395 | 1.635 | 1.660 | 4.5 | 42 | 50 | 38041 |
| 1-1/2 | 41 | 1.575 | 1.600 | 1.865 | 1.900 | 5.5 | 58 | 50 | 38051 |
| 2 | 53 | 2.020 | 2.045 | 2.340 | 2.375 | 7.0 | 78 | 50 | 38061 |
| 2-1/2 | 63 | 2.480 | 2.505 | 2.840 | 2.875 | 9.5 | 103 | 50 | 38071 |
| 3 | 78 | 3.070 | 3.100 | 3.460 | 3.500 | 15 | 123 | 25 | 38081 |
| 4 | 103 | 4.000 | 4.040 | 4.460 | 4.500 | 17 | 196 | 25 | 38091 |

NOTE: 1. Other colors available upon request.

TYPICAL SPECIFICATION:

Conduit shall be Anaconda SEALTITE® Type EFL. Conduit shall provide a flexible liquid-tight raceway for wiring and shall be constructed of continuously interlocked aluminum core with sunlight resistant PVC outer jacket. Type EFL conduit shall be used for applications where agency approvals are not required. Conduit IP 66/67 rated when installed with approved end fittings.