

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



# **385 1-1/2" Malleable Insulated Grounding Bushing** *Nsi Industries*

| Catalog Number   | 385  |
|------------------|--|
| Manufacturer     | Nsi Industries   |
| Description      | Bushing, Insulated, Grounding, Malleable Iron, Size 1 1/2 Inch, 14-1/0 Lug |
| Weight per unit  | 0.2240 (lbs/each)  |
| Product Category | Rigid Conduit Fittings - Steel   |

#### **Features**

Material Malleable Iron media Yes

#### Material, Color, and Finish

Grey with Black Insulator Color Zinc Electroplated Finish

# **Dimensions and Weight**

Size 1-1/2

### **Descriptions**

| Description            | 1-1/2" MALLEABLE INSULATED GROUNDING BUSHING                                  |
|------------------------|---|
| extra long description | BPT 385 1-1/2 GRD.BUSH.INS.14-1/0 M   |
| Long Description       | Bushing, Insulated, Grounding, Malleable Iron, Size 1 1/2 Inch,<br>14-1/0 Lug |
| Product Type           | 1.1/2 CDD Dush Inc.14.1/0 Moll  |
| Special Features       | Grounding Lug Wire Capacity #14 - #1/0  |

#### **Manufacturer Information**

| Brand | Bridgeport     |
|-------|----------------|
| GTIN  | 00781747003850 |
| UPC   | 781747003850   |

# **Taxonomies, Classifications, and Categories**

| Category Description | SERVICE ENTRANCE FITTINGS: Weatherheads & Grounding |  |
|----------------------|---|--|
|                      | Fittings & Ground Rods                              |  |
| Туре                 | BUSHING   |  |
| ada Cina             |   |  |

#### Trade Size

Trade Size 1.5

# **Packaging**

| Carton          | 20    |  |
|-----------------|-------|--|
| Package         | 200   |  |
| Weight Per each | 0.224 |  |

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

# **Uses, Certifications, and Standards**

| Application        | Used with locknut to terminate service conduit to cabinet. Lug |
|--------------------|--|
|                    | provided for bonding jumper to neutral busbar.                 |
| standard           | cULus  |
| Temperature Rating | 150?°C   |