

**Commercial  
Specification Grade  
AC Specialty Switches**

1A, 125V/AC; 1A, 250V/AC  
3A, 125V/AC; 3A, 250V/AC  
6A, 125V/AC  
Single-Pole, Two-Circuit




449NP



458BD



442



460



452

**Canopy Switches**

**FEATURES**

- Wide variety of sizes for use in fixtures, appliances, doorways and equipment.
- Shank is threaded 15/32"-32 x 15/32" (11.8mm) long.
- Hex nut and finishing nut furnished.
- 6" (152.4mm) wire lead terminals, #18 105°C stripped 0.75" (19.1mm).

**Push Button**



Rating A V/AC	Circuit	Description	Sequence	Finish	Catalog No.
1A 125V "T" 1A 250V 3A 250V	Single-Pole	Metal Push Button	On-Off	Nickel	☐ 449NP

**Pull Chain**



Rating A V/AC	Circuit	Description	Sequence	Finish	Catalog No.
1A 125V "T" 1A 250V 3A 125V	Single-Pole	Pull Chain with End Bell	On-Off	Nickel	☐ 458NP
1A 125V "T" 1A 250V 3A 125V	Single-Pole	Pull Chain with End Bell	On-Off	Brass	☐ 458BD
3A 125V "T" 3A 250V 6A 125V	Single-Pole	Pull Chain with End Bell	On-Off	Nickel	☐ 442

**Pull Chain**



Rating A V/AC	Circuit	Description	Sequence	Finish	Catalog No.
3A 250V 6A 125V	Two-Circuit	Pull Chain with End Bell	Lo-Med-Hi-Off	Brass	☐ 460

**Circuit Control Toggle Switch**

**FEATURES**

- Shank is threaded 15/32"-32 x 9/32" (7.1mm) long.
- Keyed shank, indicator plate and finishing nut furnished.
- 6" (152.4mm) wire leads, #18 105°C stripped 0.75" (19.1mm).

**Bat Handle**



Rating A V/AC	Circuit	Description	Sequence	Catalog No.
3A 250V 6A 125V	SPST	Metal Bat Handle	On-Off	☐ 452

**Icon Key**

NAFTA Compliant - see page O-30

## Canopy Switches

Single-Pole, Two-Circuit  
 1A, 125V/AC; 1A, 250V/AC  
 3A, 125V/AC; 3A, 250V/AC; 6A, 125V/AC; 6A, 250V/AC

### FEATURES

- Wide variety of sizes for use in fixtures, appliances, doorways and with equipment.
- Shank is threaded 15/32"-32 x 15/32" (11.8mm) long.
- Hex nut and finishing nut furnished.
- 6" (152.4mm) wire lead terminals, #18 105°C stripped 0.75" (19.1mm).

### Pull Chain Canopy Switches

1A 125V/AC "T", 3A 250V/AC, 6A 125V/AC

Description	Color	Catalog No.
Pull Chain with End Bell, Single-Pole, On-Off Sequence	Nickel	<input type="checkbox"/> 458NP
Pull Chain with End Bell, Single-Pole, On-Off Sequence	Brass	<input type="checkbox"/> 458BD



458BD

 UL Recognized component for US & Canada, file no. E89885

### Pull Chain Canopy Switches

3A 125V/AC "T", 3A 250V/AC, 6A 250V/AC

Description	Color	Catalog No.
Pull Chain with End Bell, Single-Pole, On-Off Sequence	Nickel	<input type="checkbox"/> 442



442

 UL Recognized component for US & Canada, file no. E89885

### Pull Chain Canopy Switches

3A 250V/AC, 6A 125V/AC

Description	Color	Catalog No.	
Pull Chain with End Bell, Two-Circuit Lo-Med-Hi-Off Sequence	Brass	<input type="checkbox"/> 460	•



460

 UL Recognized component for US & Canada, file no. E89885