
MATERIAL SAFETY DATA SHEET

Industrial Polyester Fiber and Resin

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME GHT(General High Tenacity) ; SHT(Super High Tenacity); FHT(High Tenacity for Seat Belt);SLS(Super Low Shrinkage) ; TLS(High Tenacity Low Shrinkage); TMS(High Tenacity Medium shrinkage); HMLS(High Modulus Low Shrinkage); Color Yarn; Low Wick Yarn; AA yarn(Adhesion Activated); Bright Polyester Chip;Semi-Dull Polyester Chip;

OTHER/GENERIC NAMES: Industrial Polyester Fiber and Resin

PRODUCT USE: Industrial fiber or resin. If the fiber is to be used for special applications, e.g., in the Food handling industry, or in the medical or surgical sector, please contact Zhejiang Guxiandao Industrial fibre Co.,Ltd. to determine the suitability of the intended use.

MANUFACTURER: Zhejiang Guxiandao Industrial fibre Co.,Ltd.
Yue Dong Road, Pao Jiang Industrial District,
Shaoxing City, Zhejiang Province, China.

FOR MORE INFORMATION CALL:

(Monday-Friday, 8:00am-5:00pm)
Product Stewardship
00-86-575-88138005

IN CASE OF EMERGENCY CALL:

(24 Hours/Day, 7 Days/Week)
00-86-575-88138013

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT NAME</u>	<u>CAS NUMBER</u>	<u>WEIGHT %</u>
Polyethylene Terephthalate	25038-59-9	> 98

Trace impurities and additional material names not listed above may also appear in Section 15 toward the end of the MSDS. These materials may be listed for local "Right-To-Know" compliance and for other reasons.

3. HAZARDS IDENTIFICATION

There are no hazards associated with the product for which first aid is required.

POTENTIAL HEALTH HAZARDS

SKIN: May cause mechanical irritation.

EYES: May cause mechanical irritation.

INHALATION: Not respirable in this form. Thermal processing of fiber may generate fumes and vapors which may cause irritation to the nose and throat. Dust should be considered as a nuisance dust (see Section 8).

INGESTION: Not a probable route of exposure.

DELAYED EFFECTS: None known

MATERIAL SAFETY DATA SHEET

Industrial Polyester Fiber and Resin

Ingredients found on one of the OSHA designated carcinogen lists are listed below.

<u>INGREDIENT NAME</u>	<u>NTP STATUS</u>	<u>IARC STATUS</u>	<u>OSHA LIST</u>
-------------------------------	--------------------------	---------------------------	-------------------------

No ingredients listed in this section.

4. FIRST AID MEASURES

- SKIN:** If irritation develops, wash affected area with soap and water. If discomfort continues, obtain medical attention.
- EYES:** If irritation develops, flush eyes with running water. If discomfort continues, obtain medical attention.
- INHALATION:** If processing vapor occurs and irritation develops, remove person to fresh air. If discomfort persists, seek medical attention.
- INGESTION:** Not a probable route of exposure.
- ADVICE TO PHYSICIAN:** No specific advice. Treat symptomatically.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

- | | |
|---------------------------------------------|-------------------------------------------------|
| FLASH POINT: | Not applicable |
| FLASH POINT METHOD: | Not applicable |
| AUTOIGNITION TEMPERATURE: UPPER | 500 ⁰ C (Layer Ignition Temperature) |
| FLAME LIMIT (volume % in air): LOWER | Not applicable |
| FLAME LIMIT (volume % in air): FLAME | Not applicable |
| PROPAGATION RATE (solids): | Not determined |
| OSHA FLAMMABILITY CLASS: | Not applicable |

EXTINGUISHING MEDIA:

All standard agents may be used.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

None.

SPECIAL FIRE FIGHTING PRECAUTIONS/INSTRUCTIONS:

Wear self-contained breathing apparatus meeting NIOSH standards. Avoid excessive inhalation of smoke or potential thermal decomposition products.

6. ACCIDENTAL RELEASE MEASURES

IN CASES OF SPILL OR OTHER RELEASE: (Always wear recommended personal protective equipment.)
Sweep or vacuum and place in containers for disposal to an approved landfill or reuse.

MATERIAL SAFETY DATA SHEET

Industrial Polyester Fiber and Resin

7. HANDLING AND STORAGE

NORMAL HANDLING: (Always wear recommended personal protective equipment.)
No special handling requirements.

STORAGE RECOMMENDATIONS:
No special storage requirements.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:
Mechanical ventilation should be used during processing to remove any dusts, mists, or vapors, which may be generated.

PERSONAL PROTECTIVE EQUIPMENT

SKIN PROTECTION:
Protect against potential physical hazards such as contact with yarn moving at high speed, etc.

EYE PROTECTION:
Safety glasses are recommended during processing.

RESPIRATORY PROTECTION:
None normally required.

ADDITIONAL RECOMMENDATIONS:
None required.

EXPOSURE GUIDELINES (Guidelines exist for the following ingredients)

<u>INGREDIENT NAME</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER LIMIT</u>
-------------------------------	-------------------------	------------------------	---------------------------

* No ingredients listed in this section *

OTHER EXPOSURE LIMITS FOR POTENTIAL DECOMPOSITION PRODUCTS:

Dust should be considered a nuisance dust:
ACGIH TLV: 10 mg/m³ total dust
OSHA PEL: 15-mg/m³ total dust; 5-mg/m³ respirable dust

See Section 16 regarding finish mists.

MATERIAL SAFETY DATA SHEET

Industrial Polyester Fiber and Resin

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	off white solid or delustered fiber or colored fiber or clear to super bright resin
PHYSICAL STATE:	Solid
MOLECULAR WEIGHT:	>30,000
CHEMICAL FORMULA:	(C ₁₀ H ₈ O ₄) _x
ODOR:	No specific odor.
SPECIFIC GRAVITY (water = 1.0):	1.3 - 1.4 g/cm ³
SOLUBILITY IN WATER (weight %):	Insoluble
pH:	Not applicable
BOILING POINT:	Not determined
MELTING POINT:	260 °C
VAPOR PRESSURE:	Not applicable
VAPOR DENSITY (air = 1.0):	Not applicable
EVAPORATION RATE:	Not applicable
% VOLATILES:	Not applicable
FLASH POINT:	Not determined

COMPARED TO: Not applicable

(Flash point method and additional flammability data are found in Section 5.)

10. STABILITY AND REACTIVITY

NORMALLY STABLE? (CONDITIONS TO AVOID):

Normally stable

INCOMPATIBILITIES:

Tends to dissolve in caustic materials.

HAZARDOUS DECOMPOSITION PRODUCTS:

Thermal decomposition products may include CO, ethylene glycol, aldehydes and other C, H, and O compounds varying in chemical structure and molecular weights.

HAZARDOUS POLYMERIZATION:

Will not occur.

11. TOXICOLOGICAL INFORMATION

IMMEDIATE (ACUTE) EFFECTS:

Not considered to cause irritant or allergic contact dermatitis based on testing results for skin irritation (rabbits), skin sensitization (guinea pig), and clinic evaluation using repeated insult patch test.

DELAYED (SUBCHRONIC AND CHRONIC) EFFECTS:

Not Available

OTHER DATA:

MATERIAL SAFETY DATA SHEET

Industrial Polyester Fiber and Resin

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

RCRA

Is the unused product a RCRA hazardous waste if discarded? No
If yes, the RCRA ID number is: Not

OTHER DISPOSAL CONSIDERATIONS: Dispose of as nonhazardous waste in accordance with local, state and federal regulations

The information offered here is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

14. TRANSPORT INFORMATION

US DOT PROPER SHIPPING NAME:

US DOT HAZARD CLASS: Not regulated
US DOT ID NUMBER: Not applicable

Store in dry area. Keep away from heat sources

15. REGULATORY INFORMATION

TOXIC SUBSTANCES CONTROL ACT (TSCA)

TSCA INVENTORY STATUS: Polymer is listed on the TSCA Inventory.
OTHER TSCA ISSUES: None

SARA TITLE III / CERCLA

"Reportable Quantities" (RQs) and/or "Threshold Planning Quantities" (TPQs) exist for the following ingredients.

<u>INGREDIENT NAME</u>	<u>SARA/CERCLA RQ (lb.)</u>	<u>SARA EHS TPQ (lb.)</u>
No ingredients listed in this section.		

SECTION 311 HAZARD CLASS: No ingredients listed in this section

SARA 313 TOXIC CHEMICALS: No ingredients listed in this section

MATERIAL SAFETY DATA SHEET
Industrial Polyester Fiber and Resin

ADDITIONAL REGULATORY INFORMATION:

None.

WHMIS CLASSIFICATION (CANADA):

Not a controlled product.

FOREIGN INVENTORY STATUS:

Not determined.

16. OTHER INFORMATION

Polyester Fibers are coated with minor quantities of finish oils. Textile processes may volatilize portions of these finishes and produce visible misting in the workplace. Ventilation is recommended to minimize exposure to such finish mists which should not exceed a concentration of 5 mg/m³ (ACGIH TLV for mineral oil)