

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



5021M 105-130V 1200W, Mov, Delayed Response, Turnlock *Nsi Industries*

Soon	
Catalog Number	5021M
Manufacturer	Nsi Industries
Description	Delayed Response Utility, 105 to 130 V Ac, 1200 W, 3.187 In Width, 2.187 In Height, Lexan Housing Material, Gray, Cadmium Coated CDS Photocell Sensor, -40 °F Operating Temperature, +140 °F Operating Temperature, Twist Lock Mount, 0.2 LB/Ea
Weight per unit	0.2000 (lbs/each)
Product Category	Lighting Photocells
Features	
supply voltage	105-130 VAC
Timing Range	2 Minutes
Dimensions and Weight	
Size	H=2.187 - W=3.187
Descriptions	
Description	105-130V 1200W, MOV, DELAYED RESPONSE, TURNLOCK
Manufacturer Information	
GTIN	00786261610157
UPC	786261610157
Taxonomies, Classifications, and	
Category Description	
Type	•
,	Doiay ou nosponso o time, or ado
Availability Manufacturer Status	Inactive
	mactive
Packaging	1
Carton Weight Per each	0.2
· ·	
Uses, Certifications, and Standar	
Application	Street-Highway Lighting
Enclosure	Lexan Housing
environmental conditions	-40 to + 140 F 50-60 Hz
Frequency Rating Mounting	TWIST LOCK
Operating Temperature	-40 to + 140 F
standard	-40 to + 140 F cULus
stanuaru	COLUS