

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Width

62A8004AD 2LT F48HO Rig-Pro *Crouse-Hinds*

Catalog Number	62A8004AD
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Pauluhn Rigpro Linear Fluorescent Light Fixture, 1/2" Entry, 50/60 HZ, 4 FT Lamp, Fluorescent, Clear Polycarbonate Lens, T12HO RDC, Aluminum, Through Feed, 120-277 Vac, 48W
Weight per unit	19.0 (lbs/each)
Product Category	Fluorescent Hazardous Location
Features	
Ballast Type	F48T12HO
dimensions	48.5000 IN X 7.2500 IN X 8.0000 IN
Lamp Type	F48 T12HO RDC
Material	Housing: Aluminum Type 5052H32; Lens: Clear polycarbonate
Reflector Type	Aluminum Type 5052H32, Electrostatically Applied White Polyester Powder Coat
Socket Type	Double spring loaded
Voltage Rating	120 to 277 v
Wattage	60W
Material, Color, and Finish	
Color	Natural
Finish	Electrostatically applied polyester powder coat
Dimensions and Weight	
Height	8 in
Length	48.5 inches

7.25 in



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

_	•	. •	
Desc	rin'	tian	•
			•
レしろし	ıw	uvii	

Description	2LT F48HO RIG-PRO
extra long description	CRS-H 62A8004AD LINFLUOR AL-2X60W 1
Features	The Pauluhn RigPro is a linear fluorescent fixture for Class I, Division 2, Class I, Zone 2 and Class II, Division 2 locations. Constructed of extruded aluminum with T5HO or T12HO lamps, the RigPro is available in two and four foot length fixtures. An optional emergency battery back-up is also available.
Long Description	Eaton Crouse-Hinds series Pauluhn RigPro linear fluorescent light fixture,1/2" entry ,50/60 Hz,4 ft lamp,Fluorescent,Clear polycarbonate lens,T12HO RDC,Aluminum,Through feed,120-277 Vac,48W
Product Type	Linfluor AI-2X60W 120-277V 1/2NPT X 2
Special Features	Class I Division 2

Manufacturer Information

Brand	EATON CROUSE-HINDS SERIES
GTIN	00662276384293
Manufacturers Part Number	62A8004AD
UPC	662276384293

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Туре	Light fixture

Availability

Status	Inactive

Packaging

······································		
Carton	1	
Weight Per each	19	

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Lighting and Lighting Controls
Frequency Rating	50/60 Hz
Mounting	SURFACE
standard	UL 844, UL 1598, UL 924, CSA