

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





65023000 1/2" LFNC Orange Sealtight *Southwire Company*

| Catalog Number | 65023000 | | | |
|-------------------------------|--|--|--|--|
| Manufacturer | Southwire Company | | | |
| Description | UI Liquidtight Flexible Nonmetallic Conduit, Type LFNC-A, 6500 Series, Liquidtight Flexible Nonmetallic Conduit. Flame Retardant Three Part PVC Construction. Color: Orange, 1/2 Inch Diameter, 100 Foot Carton | | | |
| Weight per unit | | | | |
| Product Category | 20120105134924 | | | |
| Features | | | | |
| Inside Diameter | 0.610/0.650 | | | |
| Material | PVC | | | |
| outside diameter | 0.900/0.940 | | | |
| Material, Color, and Finish | Orongo | | | |
| Color Finish | 3 | | | |
| Jacket Material | PVC PVC | | | |
| | FVC | | | |
| Dimensions and Weight Length | 100 | | | |
| Descriptions | | | | |
| Description | 1/2" LFNC ORANGE SEALTIGHT | | | |
| extra long description | AFC 6502-30-00 1/2 UL ORANGE LFNC-A | | | |
| Features | LIQUID-TUFF™ Type LFNC-A is a layered Liquidtight Flexible Nonmetallic Conduit, designed for use in wet, dry or oily locations as a flame resistant, Nonmetallic raceway for power, control and communications cables where repetitive motion and constant flexing is required. It is intended for applications where abrasion and physical abuse may occur. LIQUID-TUFF™ Type LFNC-A carries the UL Listing Marks for US and Canada | | | |
| Long Description | UL Liquidtight Flexible Nonmetallic Conduit, Type LFNC-A, 6500 Series, Liquidtight Flexible Nonmetallic Conduit. Flame Retardant Three Part PVC Construction. Color: Orange, 1/2 inch Diameter, 100 Foot Carton | | | |
| Product Type | 1/2 UI Orange LFNC-A 100 CTN | | | |
| Short Description | 1/2 UL ORANGE LFNC-A 100 CTN | | | |
| Special Features | Nylon reinforced braid between two layers of PVC for strength and flexibility. Sunlight resistant, oil resistant, mild acid | | | |

resistance, non-conductive raceway.



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| и | | _ | | 1 | | _ 1 | | | | . | | | | | _ |
|---|------------|----|---|---|---|-----|----|-----------|-----|----------|------|----|----|---|----------|
| ľ | ۱ <i>۱</i> | 12 | n | | - | СТ | | ·Δr | ın | TO | ۱rr | ทว | TI | n | 7 |
| | v | | | u | а | L.I | uı | CI | 'In | H.V. | ,, , | па | | u | |
| | | | | | | | | | | | | | | | |

| Brand | Flexible Conduit | |
|---------------------------|------------------|--|
| GTIN | 00077680175632 | |
| Manufacturers Part Number | 6502-30-00 | |
| UPC | 077680175632 | |

Taxonomies, Classifications, and Categories

| Category Description | Liquid Tight |
|----------------------|---|
| Туре | Liquidtight Flexible Non-Metallic Conduit |

Trade Size

Trade Size 1/2

Packaging

| ckaging | | |
|---------|------|--|
| Carton | 1 | |
| Package | 100 | |
| Weight | 0.16 | |
| · | 0.16 | |

Uses, Certifications, and Standards

| Application | Constant flexing and motion applications |
|--------------------|--|
| standard | UL 1660 E123464 |
| Temperature Rating | 176 |