

MATERIAL SAFETY DATA SHEET

MSDS 0169

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME	Metacaulk 1000	HMIS CODES	Health	:
			Flammability	(
			Reactivity)
PRODUCT CODES	66302, 66303, 66305, 66307, 66309, 66312	PPI		1
CHEMICAL FAMILY:	Organic/Inorganic			
USE	Firestopping Sealant			
MANUFACTURER'S NAME	The RectorSeal Corporation	EMERGENCY TELEPHONE NO.	Chemtrec 24 Hours	
	2601 Spenwick Drive		(800) 424-9300	
	Houston, Texas 77055 USA			
DATE OF PREPARATION	August 7, 2002	TECHNICAL SERVICE TELEPHONE NO.	(800) 231-3345	

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

% by WT	CAS No.	INGREDIENT	UNITS
None as defined by OSHA Hazard Communication Standard 29 CFR 1910.1200.			

Section 3 -- HAZARDS IDENTIFICATION

SUMMARY OF ACUTE HAZARDS
 May cause skin irritation.

ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS

INHALATION
 Not a respiratory irritant.

EYE CONTACT
 Contact may cause eye irritation.

SKIN CONTACT
 Contact may cause skin irritation.

INGESTION
 Possible irritation to mucous membranes of the mouth, throat, and stomach

SUMMARY OF CHRONIC HAZARDS
 None known.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
 Persons with pre-existing skin conditions or chemical allergies may be more susceptible to contact effects of the cured elastomer.

Section 4 -- FIRST AID MEASURES

If INHALED: Not a respiratory irritant.

If on SKIN: Wash with soap and water. If irritation occurs, seek medical attention.

If in EYES: Immediately flush with large amounts of water. If irritation occurs seek medical attention

VAPOR DENSITY (AIR = 1): N/A
EVAPORATION RATE (ETHYL ACETATE = 1): >1
APPEARANCE/ODOR: Red Paste/Mild Odor
SOLUBILITY IN WATER: Soluble

=====
Section 10 -- STABILITY AND REACTIVITY
