



METACAULK® FIRESTOP SEALANTS

Metacaulk® 1000

Intumescent, water-based firestop sealant

| Code | Description | Qty. |
|-------|-----------------------|------|
| 66640 | 10.3 oz. cartridge | 12 |
| 66303 | 30 oz. cartridge | 12 |
| 66312 | 20.2 oz. sausage pack | 12 |
| 66305 | 1 gal. | 4 |
| 66307 | 2 gal. | 1 |
| 66309 | 5 gal. | 1 |

Application • Will prevent the spread of fire through joint openings and through-penetrations
 • No dilution or mixing required • Can be used in areas under constant vibration and movement
 • Use in fire-rated gypsum wallboard partitions, concrete walls or floors, wood floors and concrete or corrugated steel deck floor/ceiling assemblies

Recommended for • Metal • Insulated
 • Fiberglass & plastic pipes • Wall construction joints • Power & telephone cables



FEATURES

- UL Classified systems up to 4 hrs.
- Highly intumescent
- Excellent freeze-thaw
- For interior use - paintable
- VOC compliant
- STC rating 62
- Meets ASTM E 814, UL 1479 & UL 2079 standards

See ordering chart for container sizes available.



Metacaulk® MC 150+

General purpose firestop sealant

| Code | Description | Qty. |
|-------|-----------------------|------|
| 66648 | 10.3 oz. cartridge | 12 |
| 66383 | 30 oz. cartridge | 12 |
| 66385 | 20.2 oz. sausage pack | 12 |
| 66389 | 5 gal. | 1 |

Application • One component, general purpose fire-rated sealant and smoke seal for construction joints and through-penetrations on both horizontal and vertical surfaces
 • Non-sag caulking grade sealant that is easy to apply as well as to retrofit • Can be used in areas under constant vibration or movement

Recommended for
 • Metal • Insulated
 • Fiberglass and plastic pipes
 • Wall construction joints
 • Power and telephone cables



FEATURES

- Water-based - VOC compliant
- Excellent freeze-thaw
- For interior use - paintable
- Use for most common applications
- STC rating 51



*FBC™ System Compatible™ indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® pipe and fittings.

**FBC™, FlowGuard Gold®, BlazeMaster® and Corzan® are licensed trademarks of The Lubrizol Corporation.

For Firestopping accessories, visit www.rectorseal.com/qr/mfa.html or scan this code.



METACAULK® FIRESTOP SEALANTS

Metacaulk® 1000

Intumescent, water-based firestop sealant

| Code | Description | Qty. |
|-------|-----------------------|------|
| 66640 | 10.3 oz. cartridge | 12 |
| 66303 | 30 oz. cartridge | 12 |
| 66312 | 20.2 oz. sausage pack | 12 |
| 66305 | 1 gal. | 4 |
| 66307 | 2 gal. | 1 |
| 66309 | 5 gal. | 1 |

Application • Will prevent the spread of fire through joint openings and through-penetrations
 • No dilution or mixing required • Can be used in areas under constant vibration and movement
 • Use in fire-rated gypsum wallboard partitions, concrete walls or floors, wood floors and concrete or corrugated steel deck floor/ceiling assemblies

Recommended for • Metal • Insulated
 • Fiberglass & plastic pipes • Wall construction joints • Power & telephone cables



FEATURES

- UL Classified systems up to 4 hrs.
- Highly intumescent
- Excellent freeze-thaw
- For interior use - paintable
- VOC compliant
- STC rating 62
- Meets ASTM E 814, UL 1479 & UL 2079 standards

See ordering chart for container sizes available.



Metacaulk® MC 150+

General purpose firestop sealant

| Code | Description | Qty. |
|-------|-----------------------|------|
| 66648 | 10.3 oz. cartridge | 12 |
| 66383 | 30 oz. cartridge | 12 |
| 66385 | 20.2 oz. sausage pack | 12 |
| 66389 | 5 gal. | 1 |

Application • One component, general purpose fire-rated sealant and smoke seal for construction joints and through-penetrations on both horizontal and vertical surfaces
 • Non-sag caulking grade sealant that is easy to apply as well as to retrofit • Can be used in areas under constant vibration or movement

Recommended for
 • Metal • Insulated
 • Fiberglass and plastic pipes
 • Wall construction joints
 • Power and telephone cables



FEATURES

- Water-based - VOC compliant
- Excellent freeze-thaw
- For interior use - paintable
- Use for most common applications
- STC rating 51



*FBC™ System Compatible™ indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® pipe and fittings.

**FBC™, FlowGuard Gold®, BlazeMaster® and Corzan® are licensed trademarks of The Lubrizol Corporation.

For Firestopping accessories, visit www.rectorseal.com/qr/mfa.html or scan this code.