

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## 696IG Combo 2SW 1P+3W 15A 120/277V Iv

Pass & Seymour/Legrand

Catalog Number	696IG	
Manufacturer	Pass & Seymour/Legrand	
Description	Single-Pole, 3-Way Double Combination Switch, 15A 120/277V, Ivory.	
Weight per unit	0.2400 (lbs/each)	
Product Category	Combination Devices	

#### **Features**

114103	
action	(1) SP & (1) 3W
actuator	Toggle
amperage rating	15
connection	Side wire
Contact Configuration	N-O
Contact Rating	15amp, 120/277vac
operating cycles	30k.0
Poles	1 & 3-Way
Voltage	120.0 V
Voltage Rating	0.433212996389892
Wattage	Electrical power is expressed in Amps and Volts.
Wire Size	#14 - #10 Awa

### Material, Color, and Finish

Finish	Matte	

## **Dimensions and Weight**

Size 1.32 L x 0.94 W x 4.06 H
-------------------------------

# **Descriptions**

Description	COMBO 2SW 1P+3W 15A 120/277V IV
extra long description	P&S 696IG COMBO 2SW 1P+3W 15A 120/2
Features	Combination
Long Description	Single-Pole, 3-way Double Combination Switch, 15A 120/277V, Ivory.
Product Type	Combo 2SW 1P+3W 15A 120/277V I
Special Features	Easily accessible break-off for separate or common feed. Side wire #12 and #14 AWG. Two devices fit into the space of one.  Grounding combination devices meet NEC Requirements.



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

1 /1 /	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	・ヘヘキロ	IPAPI	ntari	nation

Brand	Pass and Seymour
GTIN	00785007006216
Manufacturers Part Number	696-IG
UPC	785007006216

# **Taxonomies, Classifications, and Categories**

Category Description	Residential Switches
Туре	COMBINATION

#### **Trade Size**

Amperage	15.0
Amperage	10.0

### **Packaging**

okugirig		
Carton	10	
Package	50	
Weight Per each	0.24	

### Uses, Certifications, and Standards

Application	Residential/Commercial
environmental conditions	Flammability: UL94 V2
Mounting	WALL
Operating Temperature	Maximum continuous +60°C, minimum -30°C
standard	CULUS, UL20