

ETP Steel EMT Compression Connectors

7000S Series Connectors

Application

- To ground and secure EMT raceways to boxes and enclosures.

Features

- Male hub threads — NPS.
- Available with insulated throat.
- Concretetight.
- Insulated throat connector rated 90 °C.

Material/Finish

- Body and nut: steel
- Steel/zinc plated

Certifications and Compliances

- UL Standard: 514B
- UL Listed: E14815, E14814
- cUL Listed: E14815
- CSA Standard: C22.2 No. 18.3
- NEMA: FB-1



7050S – 7400S

| Trade Size (Inches) | Catalog Number | Insulated Throat Catalog Number | Dimensions in Inches/Millimeters | | | Weight Lbs./Kgs. Per 100 |
|------------------------|-------------------|------------------------------------|----------------------------------|------------------|---------------|-----------------------------|
| | | | Body Length | Maximum Diameter | Thread Length | |
| 1/2 | 7050S | 7050ST | 1.13/28.7 | 1.06/26.9 | 0.38/9.7 | 15.00/6.80 |
| 3/4 | 7075S | 7075ST | 1.03/26.2 | 1.25/31.8 | 0.44/11.2 | 21.00/9.53 |
| 1 | 7100S | 7100ST | 1.25/31.8 | 1.56/39.6 | 0.44/11.2 | 32.00/14.51 |
| 1-1/4 | 7125S | 7125ST | 1.81/46.0 | 2.00/50.8 | 0.56/14.2 | 72.00/32.66 |
| 1-1/2 | 7150S | 7150ST | 2.00/50.8 | 2.19/55.6 | 0.56/14.2 | 85.00/38.56 |
| 2 | 7200S | 7200ST | 2.25/57.2 | 2.69/68.3 | 0.69/17.5 | 124.00/56.25 |
| 2-1/2 * | 7250S | 7250ST | 2.38/60.5 | 3.34/84.8 | 0.88/22.4 | 160.00/72.57 |
| 3 * | 7300S | 7300ST | 2.88/73.2 | 4.00/101.6 | 0.88/22.4 | 265.00/120.20 |
| 3-1/2 * | 7350S | 7350ST | 3.00/76.2 | 4.50/114.3 | 1.00/25.4 | 425.00/192.78 |
| 4 * | 7400S | 7400ST | 3.19/81.0 | 5.06/128.5 | 1.00/25.4 | 600.00/272.16 |

* Rated for steel EMT, aluminum and steel RMC, and steel IMC.

ETP Steel EMT Compression Connectors

7000US Series Connectors

Application

- To ground and secure EMT raceways to boxes and enclosures.

Features

- Made in the U.S.A.
- Male hub threads — NPS.
- Available with insulated throat.
- Concretetight.
- Insulated throat temperature rated 90 °C.

Material/Finish

- Body and nut: steel
- Steel/zinc plated

Certifications and Compliances

- UL Standard: 514B
- UL Listed: E14895, E14815
- CSA Standard: C22.2 No. 18.3
- cUL Listed: E14815
- CSA Certified: 028507
- NEMA: FB-1



7050US – 7200US



7250US – 7400US

| Trade Size (Inches) | Catalog Number | Insulated Throat Catalog Number | Dimensions in Inches/Millimeters | | |
|------------------------|-------------------|------------------------------------|----------------------------------|------------------|---------------|
| | | | Body Length | Maximum Diameter | Thread Length |
| 1/2 | 7050US | 7050UST | 1.06/26.9 | 0.97/24.6 | 0.38/9.7 |
| 3/4 | 7075US | 7075UST | 1.13/28.7 | 1.22/31.0 | 0.41/10.4 |
| 1 | 7100US | 7100UST | 1.25/31.8 | 1.50/38.1 | 0.44/11.2 |
| 1-1/4 | 7125US | 7125UST | 1.44/36.6 | 1.91/48.5 | 0.50/12.7 |
| 1-1/2 | 7150US | 7150UST | 1.56/39.6 | 2.16/54.9 | 0.53/13.5 |
| 2 | 7200US | 7200UST | 1.69/42.9 | 2.69/68.3 | 0.59/15.0 |
| 2-1/2 | 7250US | 7250UST | 4.06/103.1 | 4.13/104.9 | 1.25/31.8 |
| 3 | 7300US | 7300UST | 4.13/104.9 | 4.69/119.1 | 1.38/35.1 |
| 3-1/2 | 7350US | 7350UST | 4.25/108.0 | 5.34/135.6 | 1.41/35.8 |
| 4 | 7400US | 7400UST | 4.50/114.3 | 5.88/149.4 | 1.50/38.1 |

ETP Steel EMT Compression Connectors

7000S Series Connectors

Application

- To ground and secure EMT raceways to boxes and enclosures.

Features

- Male hub threads — NPS.
- Available with insulated throat.
- Concretetight.
- Insulated throat connector rated 90 °C.

Material/Finish

- Body and nut: steel
- Steel/zinc plated

Certifications and Compliances

- UL Standard: 514B
- UL Listed: E14815, E14814
- cUL Listed: E14815
- CSA Standard: C22.2 No. 18.3
- NEMA: FB-1



7050S – 7400S

| Trade Size (Inches) | Catalog Number | Insulated Throat Catalog Number | Dimensions in Inches/Millimeters | | | Weight Lbs./Kgs. Per 100 |
|------------------------|-------------------|------------------------------------|----------------------------------|------------------|---------------|-----------------------------|
| | | | Body Length | Maximum Diameter | Thread Length | |
| 1/2 | 7050S | 7050ST | 1.13/28.7 | 1.06/26.9 | 0.38/9.7 | 15.00/6.80 |
| 3/4 | 7075S | 7075ST | 1.03/26.2 | 1.25/31.8 | 0.44/11.2 | 21.00/9.53 |
| 1 | 7100S | 7100ST | 1.25/31.8 | 1.56/39.6 | 0.44/11.2 | 32.00/14.51 |
| 1-1/4 | 7125S | 7125ST | 1.81/46.0 | 2.00/50.8 | 0.56/14.2 | 72.00/32.66 |
| 1-1/2 | 7150S | 7150ST | 2.00/50.8 | 2.19/55.6 | 0.56/14.2 | 85.00/38.56 |
| 2 | 7200S | 7200ST | 2.25/57.2 | 2.69/68.3 | 0.69/17.5 | 124.00/56.25 |
| 2-1/2 * | 7250S | 7250ST | 2.38/60.5 | 3.34/84.8 | 0.88/22.4 | 160.00/72.57 |
| 3 * | 7300S | 7300ST | 2.88/73.2 | 4.00/101.6 | 0.88/22.4 | 265.00/120.20 |
| 3-1/2 * | 7350S | 7350ST | 3.00/76.2 | 4.50/114.3 | 1.00/25.4 | 425.00/192.78 |
| 4 * | 7400S | 7400ST | 3.19/81.0 | 5.06/128.5 | 1.00/25.4 | 600.00/272.16 |

* Rated for steel EMT, aluminum and steel RMC, and steel IMC.

ETP Steel EMT Compression Connectors

7000US Series Connectors

Application

- To ground and secure EMT raceways to boxes and enclosures.

Features

- Made in the U.S.A.
- Male hub threads — NPS.
- Available with insulated throat.
- Concretetight.
- Insulated throat temperature rated 90 °C.

Material/Finish

- Body and nut: steel
- Steel/zinc plated

Certifications and Compliances

- UL Standard: 514B
- UL Listed: E14895, E14815
- CSA Standard: C22.2 No. 18.3
- cUL Listed: E14815
- CSA Certified: 028507
- NEMA: FB-1



7050US – 7200US



7250US – 7400US

Commercial Products

COMMERCIAL PRODUCTS: EMT FITTINGS

| Trade Size (Inches) | Catalog Number | Insulated Throat Catalog Number | Dimensions in Inches/Millimeters | | |
|------------------------|-------------------|------------------------------------|----------------------------------|------------------|---------------|
| | | | Body Length | Maximum Diameter | Thread Length |
| 1/2 | 7050US | 7050UST | 1.06/26.9 | 0.97/24.6 | 0.38/9.7 |
| 3/4 | 7075US | 7075UST | 1.13/28.7 | 1.22/31.0 | 0.41/10.4 |
| 1 | 7100US | 7100UST | 1.25/31.8 | 1.50/38.1 | 0.44/11.2 |
| 1-1/4 | 7125US | 7125UST | 1.44/36.6 | 1.91/48.5 | 0.50/12.7 |
| 1-1/2 | 7150US | 7150UST | 1.56/39.6 | 2.16/54.9 | 0.53/13.5 |
| 2 | 7200US | 7200UST | 1.69/42.9 | 2.69/68.3 | 0.59/15.0 |
| 2-1/2 | 7250US | 7250UST | 4.06/103.1 | 4.13/104.9 | 1.25/31.8 |
| 3 | 7300US | 7300UST | 4.13/104.9 | 4.69/119.1 | 1.38/35.1 |
| 3-1/2 | 7350US | 7350UST | 4.25/108.0 | 5.34/135.6 | 1.41/35.8 |
| 4 | 7400US | 7400UST | 4.50/114.3 | 5.88/149.4 | 1.50/38.1 |