

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



774010 Toggle Switch, SPST, On-Off, O-Ring, Screw Ideal

8 8	
Catalog Number	774010
Manufacturer	Ideal
Description Woight por unit	Toggle Switch, 1 Pole, 10 A;20 A, 125/227 V Ac, SPST Contact Configuration, Solid Brass;Nickel-Plated (Bushing) Material, Spade Connection, Hole Mount, Nickel Plated (Bushing), 1.130 Ir (L) X 0.570 In (W) X 0.610 In (H), +32 °F Operating Temperature, +185 °F Operating Temperature, 0.1 LB 0.1000 (lbs/each)
Weight per unit	Gen Purpose Switches
Product Category - •	Gen Pui pose switches
Features	CDCT
action actuator	SPST Togglo
	Toggle 10/20
amperage rating connection	
Contact Rating	Spade, 2 Terminals Factory Tested 100000 Cycles To 21 AMP 14.8 VDC DC Rating
operating cycles	100k
Poles	100k
Dimensions and Weight Size	1.130 IN Length X 0.570 IN Width X 0.610 IN Height
Descriptions	
Description	TOGGLE SWITCH, SPST, ON-OFF, O-RING, SCREW
Features	Great for power tool and motor control switch
	applicationsRugged long-wearing solid brass/nickel-plated bushings1/2 in. diameter mounting holeDielectric Strength: 1500VMechanical Life: 100,000 cyclesOperating Temperature: 32°F to 185°F (0°C to 85°C)DC?Rating: Factory tested 100,000 cycles to 21 Amp 14.8 VDC
Manufacturer Information	
Brand	Ideal
GTIN	00783250573431
UPC	783250573431
Taxonomies, Classifications, and	l Categories
Category Description	TOCOLE CANTOLIEC
Туре	Standard, On-Off
Availability	
Status	Inactive



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Pac	kag	ing

Carton	1
Weight Per each	0.1

Uses, Certifications, and Standards

oo, ooi tiiilaatioilo, aila otaliaa	. 40	
Mounting	1/2 IN Hole Diameter	
Operating Temperature	32 To 185	
standard	CSA, RU Listed, RoHS	