

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



885TRDBCC12 Radiant 15A/125V TR Duplex Recp DB CC12

| Pass & Seymour/Legran | nd |
|------------------------------------|---|
| Catalog Number | 885TRDBCC12 |
| Manufacturer | Pass & Seymour/Legrand |
| Description | Take A Step Up From The Standard. This Tamper-Resistant Duplex Outlet Installs Easily For The Basic Power Every Home Needs, While Elevating Your Space With The Sleek, Clean Lines Of Radiant Registered For A Sophisticated Look. Made Exclusively For Use With Screwless Wall Plates From The Radiant Registered Collection, Sold Separately. |
| Weight per unit | 0.1667 (lbs/each) |
| Product Category | Gen Purpose Recept & Surge Pro |
| Features | |
| indoor/outdoor | Indoor |
| Mounting Type | Вох |
| Outlet Type | |
| Poles | 3 |
| Voltage | |
| Material, Color, and Finish Finish | Metallic |
| Descriptions | |
| Description | RADIANT 15A/125V TR DUPLEX RECP DB CC12 |
| extra long description | P&S 885TRDBCC12 RADIANT 15A/125V TR |
| Long Description | Take a step up from the standard. This tamper-resistant duplex outlet installs easily for the basic power every home needs, while elevating your space with the sleek, clean lines of radiant Registered for a sophisticated look. Made exclusively for use with screwless Wall Plates from the radiant Registered |
| Product Type | Dadient 15 A /125 V TD Dan Door DD CC12 |
| Manufacturer Information | |
| Brand | LEGRAND-PASS & SEYMOUR |
| GTIN | 00785007029413 |
| Manufacturers Part Number | 885-TRDBCC12 |
| UPC | 785007029413 |
| Taxonomies, Classifications, and C | Categories |
| Category Description | B 11 11 10 F01 1 1 |
| | |

Outlet

Type **Trade Size**

| | |
|----------|------|
| Amperage | 15.0 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Packagii | ng |
|----------|----|
|----------|----|

| Carton | 12 | |
|-----------------|--------|--|
| Weight Per each | 0.1667 | |

Uses, Certifications, and Standards

| environmental conditions | 95% (relative humidity, non-condensing) |
|--------------------------|---|
| nema rating | 15A |
| standard | CULUS, UL |