

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



AHCL530C CCL Conn 30A 125V 2P3W-Y&BK Eaton Wiring Devices

| Catalog Number | AHCL530C |
|----------------------------|--|
| Manufacturer | Eaton Wiring Devices |
| Description | Eaton Arrow Hart Color Coded Locking Connector, #14-8 Awg, |
| | 30A, Industrial, 125V, Back, Yellow, Black, Ultra Grip, Nylon, |
| | L5-30, Two-Pole, Three-Wire, Nylon, 0.38 - 1.00" (9.5 - 25.4MM), |
| | -40°C (W/O Impact) to 60°C (-40°F to 140°F) |
| Weight per unit | 10.0 (lbs/each) |
| Product Category | Plugs, Connectors, Inlets, Out |
| Features | |
| media | Yes |
| Descriptions | |
| Description | CCL CONN 30A 125V 2P3W-Y&BK |
| extra long description | EWD AHCL530C CCL Conn 30A 125V 2P3W |
| Features | Eaton's Arrow Hart color coded locking devices are an |
| | industry-first solution that adds six voltage rating color codes |
| | consistent with IEC 60309 standards to locking plugs, connectors, |
| | inlets, outlets and receptacles to provide you a quick, clear and |
| | easy way to identify your circuit voltage. Available in standard NEMA configurations for 20A and 30A applications, the devices |
| | ensure long-lasting, dependable service in the most demanding |
| | environments, are built with a contemporary flare and |
| | ergonomic design |
| Long Description | Eaton Arrow Hart Color Coded Locking Connector, #14-8 AWG, |
| C . | 30A, Industrial, 125V, Back, Yellow, Black, Ultra grip, Nylon, |
| | L5-30, Two-pole, Three-wire, Nylon, 0.38 - 1.00" (9.5 - 25.4mm), |
| | -40°C (w/o impact) to 60°C (-40°F to 140°F) |
| Product Type | CCL Conn 30A 125V 2P3W-Y&BK |
| Manufacturer Information | |
| Brand | Eaton |
| GTIN | 00032664755811 |
| Manufacturers Part Num | |
| UPC | 032664755811 |
| Taxonomies, Classification | ns, and Categories |
| Category Description | Industrial cord connectors |
| Packaging | |
| Carton | |
| Package | 40 |
| Weight Per each | |