



## AHDS60VFD 60A Disconnect Switch Var Freq Drive

*Eaton Wiring Devices*

Catalog Number	AHDS60VFD
Manufacturer	Eaton Wiring Devices
Description	Eaton Motor Control Disconnect Switch, #14-4 Awg, 60A, Industrial, Mounting Feet/Din Rail, Flush or 1/4" Spacing, 600V, Aux. Contacts For VF Drive (Early-Break), Gray, Nema 4X, Enclosure: Valox Thermoplastic, Washdown, Three-Phase, Rotary
Weight per unit	5.0 (lbs/each)
Product Category	Disconnect Motor Switches

### Features

dimensions	11.0000 IN X 7.5000 IN X 5.5000 IN
------------	------------------------------------

### Descriptions

Description	60A DISCONNECT SWITCH VAR FREQ DRIVE
extra long description	EWD AHDS60VFD 60A Disconnect Switch
Features	Additionally, our non-fused motor control disconnect switch and our new stainless-steel X-Switch are NSF listed for use in food processing. Offering flexible and economical designs for both fused and non-fused applications, Eaton's Arrow Hart motor control disconnect switches are built for use in harsh industrial applications to address the needs of safety, reduced downtime and code compliance. Our industrial grade, electrical motor controls feature durable lever handles and switch mechanisms that will wit
Long Description	Eaton motor control disconnect switch, #14-4 AWG, 60A, Industrial, Mounting feet/DIN rail, flush or 1/4" spacing, 600V, Aux. contacts for VF drive (early-break), Gray, NEMA 4X, Enclosure: VALOX thermoplastic, Washdown, Three-phase, Rotary
Product Type	60A Disconnect Switch Var Freq Drive
Special Features	Motor control switches, swt/encl combos

### Manufacturer Information

Brand	Eaton Wiring Devices
GTIN	00032664741371
Manufacturers Part Number	AHDS60VFD
UPC	032664741371

### Taxonomies, Classifications, and Categories

Category Description	Residential Switches
Type	Motor control disconnect switch



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3804 W. Esthner Avenue  
67213-0000, KS Wichita  
Phone: 316-854-0028  
Fax: 316-854-0029

## Packaging

Carton	1
Package	4
Weight Per each	5.01

## Uses, Certifications, and Standards

Application standard	Ind Facilities & Factories - Facility - Other cULus Listed, RoHS Compliant
----------------------	---