

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



AL400N 400 AI/Cu 2 Hole Compression Lug *Nsi Industries*

N TAB	
Catalog Number	AL400N
Manufacturer	Nsi Industries
Description	2HOLESTANDARD Barrelaluminum Compression Lug 400 MCM -1/2 Bolt Standard Barrelaluminum Compression Lugs Is A Type Ofaluminum Compression Connector That Is Produced From High Conductivityaluminum Tubing.Center Stop Assures Proper Cable Installation.They Are Tin-Plated to Provide Corrosion Resistance and Are Marked With Die Index and Color Coded For Easy Reference. Listed For 35KV Maximum When Properly Installed.
Weight per unit	0.4400 (lbs/each)
Product Category	Large Terminals & Connectors
Features	
Cable Size	400 MCM (STR)
Material	Aluminum
Number of Holes	2
Stud Size	1/2
Voltage Rating	600 V
Warranty	1 YEAR
Material, Color, and Finish	
Color	Green
Finish	Tin Plated Bronze
Dimensions and Weight Size	L=6.42 - W=1.60 - OD=1.19 - ID=.759



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

_			•			
. 1	es	~r	ın		$\boldsymbol{\wedge}$	nc
	_	LL		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		117
_	-	v.			•	

Description	400 AL/CU 2 HOLE COMPRESSION LUG
extra long description	NSI AL400N AL/CU CMP Lug 750 MCM 5/
Features	2HoleStandard BarrelAluminum Compression Lug 400 MCM -1/2 Bolt Standard BarrelAluminum Compression Lugs is a type ofaluminum compression connector that is produced from high conductivityaluminum tubing. Center stop assures proper cable installation. They are tin-plated to provide corrosion resistance and are marked with die index and color coded for easy reference. Listed for 35KV maximum when properly installed.
Long Description	2HoleStandard BarrelAluminum Compression Lug 400 MCM -1/2 Bolt Standard BarrelAluminum Compression Lugs is a type ofaluminum compression connector that is produced from high conductivityaluminum tubing. Center stop assures proper cable installation. They are tin-plated to provide corrosion resistance and are marked with die index and color coded for easy reference. Listed for 35KV maximum when properly installed.
Product Type	AI/Cu CMP Lug 750 MCM 5/8 Bolt Size
Special Features	400 MCM (STR) - 1/2 Mounting Holes - 1 3/4 Hole Spacing

Manufacturer Information

Brand	NSi
GTIN	00662381031075
Manufacturers Part Number	AL400N
UPC	662381031075

Taxonomies, Classifications, and Categories

Category Description	Comp & Mech Lugs and Butt Splices
Туре	Standard Barrel - Two Hole

Packaging

Carton	1
Package	6
Weight Per each	0.44

Uses, Certifications, and Standards

Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C
Mounting	1/2 Mounting Holes
standard	UL486A/B