

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



AP20467 3W-4P Plug Crouse-Hinds

Catalog Number	AP20467
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Arktite Ap Plug, 200A, 1.375-1.875", Three-Wire, Four-Pole, 50-400 HZ, Style 2, Copper-Free Aluminum, Crimp/Solder, 600 Vac/250 VDC, 0.56" Max
Weight per unit	•
Product Category	Pin & Sleeve Devices
Features	
amperage rating	200
connection	Crimp/Solder
Cord Type	1.375 To 1.875 In Diameter
dimensions	14.7500 IN X 6.7500 IN X 6.7500 IN
Material	Copper-Free Aluminum
Poles	4
Voltage Rating	
Wire Size	1 To 4/0 AWG (Building), 1 To 3/0 AWG (Extra Flex)
Dimensions and Weight	
Length	14-3/4
Descriptions	
Description	3W-4P PLUG
extra long description	CRS-H AP20467 200A 3W4P ARK PLG 1.3
Features	Crouse-Hinds series Arktite plugs and receptacles are used to
	supply power to portable electrically operated devices, such as motor generator sets, compressors, heating and cooling units, welders, conveyors, lighting systems and similar equipment. Also used where temporary power is needed, such as at trailers, building units, heavy machinery or wherever electrical loads mus be quickly disconnected from power source.
Long Description	Eaton Crouse-Hinds series Arktite AP plug, 200A, 1.375-1.875", Three-wire, four-pole, 50-400 Hz, Style 2, Copper-free aluminum, Crimp/solder, 600 Vac/250 Vdc, 0.56" max
Product Type	200A 3W4P Ark PLG 1.375-1.875 2 .56 Con
Special Features	Watertight, Grounding Style 2, NEMA 4 Enclosure, Special Polarity



ELLIOTT **E**LECTRIC **S**UPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	Eaton
GTIN	00782274039909
Manufacturers Part Number	AP20467
UPC	782274039909
Taxonomies, Classifications, and C	ategories
Category Description	Pin & Sleeve Devices
Туре	PLUG
Packaging	
Carton	1
Weight Per each	12.25
Uses, Certifications, and Standards	5
Application	Ind Facilities & Factories - Facility: Power Distribution and Control
standard	UL 514, UL 1010, UL 1682, CSA C22.2