

# **ELLIOTT ELECTRIC SUPPLY**

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

### BC2SS10C 8.5" 50LB #10SCREW Nylon Barb CBL Tie Panduit Corporation

Catalog Number	BC2SS10C
Catalog Number Manufacturer	Panduit Corporation
Description	The BC2S-S10-C Dome-Top® Barb Ty Clamp Tie, Features A
	Unique Patented Design With Its Round Smooth Edges. Paired
	With The Stainless-Steel Locking Barb, These Cable Ties Provide
	Consistent Performance, Reliability and Infinite Adjustability
	Through The Entire Bundle Range. Standard Cross Section, 8.5"
	(261MM) Length. Appropriate For Indoor Use, Made Of Nylon
	6.6, Are Natural In Color and Come In Packages Of 100.
Weight per unit	0.4400 (lbs/each)
Product Category	Cable Ties & Wraps
Features	
media	Yes
Tensile Strength	
Dimensions and Weight	
Length	8.5
Descriptions	
Description	8.5" 50LB #10SCREW NYLON BARB CBL TIE
extra long description	PAN BC2S-S10-C Dome-Top <sup>®</sup> BC2S-S10-C
Long Description	The BC2S-S10-C Dome-Top® barb ty clamp tie, features a unique
	patented design with its round smooth edges. Paired with the
	stainless-steel locking barb, these cable ties provide consistent
	performance, reliability and infinite adjustability through the
	entire bundle range. Standard cross section, 8.5" (261mm) length. Appropriate for Indoor use, made of Nylon 6.6, are
	natural in color and come in packages of 100.
Product Type	Dome-Top <sup>®</sup> BC2S-S10-C Locking Clamp Barb Tie, PA6.6, M5, 8.5"
Special Features	Indoor
Manufacturer Information	
Brand	Panduit®
GTIN	00074983523146
Manufacturers Part Number	BC2S-S10-C
UPC	074983523146
Taxonomies, Classifications, and (	Categories
	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps
Туре	Locking Clamp Tie



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

### Packaging

Carton	100	
Package	1000	
Weight Per each	0.44	

#### Uses, Certifications, and Standards

Application	Used to secure a cable bundle to another surface such a control
	panel, wall or ceiling.
standard	UL 62275 Compliant (Type 2, 21), UL Listed (File #E56854)