

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Category Description

Type

BG6U58 SPRG 3/8" CNDT to BM FSTNR Cooper B-Line/Cable Tray

| Catalog Number | BG6U58 |
|-----------------------------|--|
| Manufacturer | Cooper B-Line/Cable Tray |
| Description | Eaton B-Line Series Conduit Support Fasteners, Beams, Flange, 1 Height, 1" Length, 1" Width, 0.087LBS, Conduit Size: 0.38", Guide-Rite Conduit to Beam Fasteners, .31" Min Mount Size, .5" Max Mount Size |
| Weight per unit | 0.0870 (lbs/each) |
| Product Category | Anchors & Fasteners |
| Features | |
| dimensions | 1.0000 IN X 1.0000 IN X 1.0000 IN |
| Material | Cold Rolled High Carbon Steel |
| Material, Color, and Finish | |
| Finish | Zinc Phosphate |
| Dimensions and Weight | |
| Size | 3/8 In Conduit |
| Descriptions | |
| Description | SPRG 3/8" CNDT TO BM FSTNR |
| extra long description | B-LINE BG-6-U-5-8 CONDUIT TO BM FS, |
| Features | Designed for ease of installation, long service life and reliable performance, Eaton B-Line series conduit support fasteners provide the ideal choice for a wide range of applications. |
| Long Description | Eaton B-Line series conduit support fasteners, Beams, Flange, 1" Height, 1" Length, 1" Width, 0.087lbs, Conduit size: 0.38", Guide-Rite conduit to beam fasteners, .31" Min mount size, .5" Max mount size |
| Product Type | Conduit to BM FS, 3/8" Conduit, 5/16" to 1/2" Flange |
| Special Features | Flange Thickness 5/16 To 1/2 In, Rotation 360 Deg Pivot, Static Load Capacity 75 Lb |
| Manufacturer Information | |
| Brand | Eaton |
| GTIN | 00781011184551 |
| Manufacturers Part Number | BG-6-U-5-8 |
| UPC | 781011184551 |

BEAM, RA, EDGE, & PARALLEL CLAMPS

Conduit to beam fastener



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Packaging Carton | 1 |
|----------------------------------|--|
| Weight Per each | 0.087 |
| Uses, Certifications, and Standa | rds |
| Application | Commercial / Institutional Buildings / Structures - Commercial / |
| | Institutional Buildings / Structures - OtherCommercial / |
| | Institutional Buildings / Structures - Commercial/Inst Bldg |
| | Strctures - Aftermarket |
| standard | UL/cUL Listed |