

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941

We Deliver...Lower Cost, Quality Products, & Personal Service

Fax: 936-560-4685



BUB6SA 2" Alu Bub MGL Conduit Body Crouse-Hinds

BUB6SA Catalog Number Manufacturer Crouse-Hinds Eaton Crouse-Hinds Series Condulet B Mogul Conduit Body, Description Copper-Free Aluminum, Ub Shape, 2" 2.7 (lbs/each) Weight per unit Product Category Alum

Features

dimensions 13.5000 IN X 3.0000 IN X 4.1300 IN

Material, Color, and Finish

Finish Electrogalvanized With Aluminum Acrylic Painted

Dimensions and Weight

3 Height Hub Size 2 in 13-1/2 Length Width 4-1/8

Descriptions

Description 2" ALU BUB MGL CONDUIT BODY extra long description CRS-H BUB6 SA 2 NPT AL UB MOGUL BOD **Features** Crouse-Hinds series mogul bodies are installed in conduit systems to act as pull outlets for conductors that are stiff due to large size or type of insulation. Mogul bodies provide longer openings needed when pulling large conductors and prevent sharp bends and kinks during installation. Mogul conduit bodies are manufactured in trade sizes 1/2" to 6" and are available in Feraloy iron alloy and copper-free aluminum. Our iron alloy bodies are available with a hot dip galvanized finish for added corrosion Long Description Eaton Crouse-Hinds series Condulet B mogul conduit body, Copper-free aluminum, UB shape, 2" Product Type 2 NPT AI Ub Mogul Body

Manufacturer Information

EATON CROUSE-HINDS SERIES Brand 00782274127958 **GTIN** Manufacturers Part Number BUB6 SA UPC 782274127958

Taxonomies, Classifications, and Categories

Category Description Form 9 condulets, covers & gaskets Mogul conduit body Type



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Package	2
Weight Per each	2.7
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other

UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D