




ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



C.5LG6 1/2X72" LT Gry Duct CVR *Panduit Corporation*

Catalog Number	C.5LG6
Manufacturer	Panduit Corporation
Description	The C.5LG6 PVC Flush Wiring Duct Cover Features A Non-Slip, Liner to Prevent Cover Slide. Designed With The User In Mind, The Cover Is Easy to Install and Remove. The General-Purpose Lead-Free PVC Material Is Suitable For Use In Indoor Applications. UI 94 Flame Class Of V-0 With A UI Recognized Continuous-Use Temperature Up to 122°F (50°C). 0.23" X 0.69" (5.8 MM X 17.5 MM) and 6' (1.83 M) Long. Color Light Gray.
Weight per unit	0.0342 (lbs/each)
Product Category	Ducts, Raceways, Runways, Tray

Features

connection	Snap-on
Material	PVC
media	Yes

Material, Color, and Finish

Color	Light Gray
-------	------------

Dimensions and Weight

Length	72
Width	0.69

Descriptions

Description	1/2X72" LT GRY DUCT CVR
extra long description	PAN C.5LG6 Panduct® C.5LG6 Flush Du
Long Description	The C.5LG6 PVC Flush Wiring Duct Cover features a non-slip, liner to prevent cover slide. Designed with the user in mind, the cover is easy to install and remove. The general-purpose lead-free PVC material is suitable for use in indoor applications. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). 0.23" x 0.69" (5.8 mm x 17.5 mm) and 6' (1.83 m) long. Color Light Gray.
Product Type	Panduct® C.5LG6 Flush Duct Cover

Manufacturer Information

Brand	PANDUIT
GTIN	00074983230006
Manufacturers Part Number	C.5LG6
UPC	074983230006



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	Panduit & Wiremold Metallic & Non-Metallic Raceways
Type	Flushed Duct Cover

Availability

minimum qty	6
-------------	---

Packaging

Carton	120
Weight Per foot	0.0342

Uses, Certifications, and Standards

Application	Cover for Wiring Duct
standard	UL Recognized; Flammability Ratings: UL94 V-0; CSA Certified; CE Compliant; RoHS Compliant