



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1620 Alcock St.  
79065-0000, TX Pampa  
Phone: 806-665-0433  
Fax: 806-665-1002



## C68 2" C FM8 Conduit Body

*Crouse-Hinds*

Catalog Number	C68
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 8 Conduit Outlet Body, Feraloy Iron Alloy, C Shape, 2"
Weight per unit	7.2 (lbs/each)
Product Category	Bodies & Covers

### Features

dimensions	12.2500 IN X 3.7500 IN X 3.5600 IN
Form	Form 8

### Material, Color, and Finish

Finish	Electrogalvanized With Aluminum Acrylic Painted
--------	---

### Dimensions and Weight

Height	3-9/16
Hub Size	2 in
Length	12-1/4
Width	3-3/4

### Descriptions

Description	2" C FM8 CONDUIT BODY
extra long description	CRS-H C68 2 NPT IRON C FORM 8 CNDT
Features	One hundred years after the introduction of the Condulet, Eaton remains the leader in conduit outlet bodies with its Crouse-Hinds series. The line has grown to six families manufactured in a variety of materials, and Form 8 bodies are offered in seven different shapes to provide the most flexible offering on the market. Form 8 Condulet outlet bodies provide more room for heavier conductors. Many shapes and sizes are available for rigid threaded conduit. Two cover screws on all body sizes provide tight
Long Description	Eaton Crouse-Hinds series Condulet Form 8 conduit outlet body, Feraloy iron alloy, C shape, 2"
Product Type	2 NPT Iron C Form 8 CNDT Body

### Manufacturer Information

Brand	Eaton
GTIN	00782274746241
UPC	782274746241

### Taxonomies, Classifications, and Categories

Category Description	FORM 7, 8, CONDULETS, COVERS, & GASKETS
Type	Conduit outlet body



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1620 Alcock St.  
79065-0000, TX Pampa  
Phone: 806-665-0433  
Fax: 806-665-1002

## Packaging

Carton	1
Weight Per each	7.2

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D