

# Specifications

Photo is representative

## Eaton CDR3033

Eaton Crouse-Hinds series PowerMate CDR receptacle, 30A, Three-wire, three-pole, Style 1, Copper-free aluminum, 600 Vac/250 Vdc

### General specifications

|                             |  |
|-----------------------------|--|
| <b>PRODUCT NAME</b>         | Eaton Crouse-Hinds series PowerMate CDR receptacle |
| <b>CATALOG NUMBER</b>       | CDR3033  |
| <b>UPC</b>                  | 662276277038                                       |
| <b>PRODUCT LENGTH/DEPTH</b> | 2.88 in  |
| <b>PRODUCT HEIGHT</b>       | 3.38 in  |
| <b>PRODUCT WIDTH</b>        | 3.38 in  |
| <b>PRODUCT WEIGHT</b>       | 2.2 lb   |

## Certifications and compliances

|                            |                                  |
|----------------------------|----------------------------------|
| <b>AREA CLASSIFICATION</b> | Ordinary/Non-Hazardous Locations |
| <b>STANDARDS TYPE</b>      | NEC/CEC                          |
| <b>NEMA RATING</b>         | 4X                               |

## Resources

|                                      |   |
|--------------------------------------|---|
| <b>3D CAD DRAWING PACKAGE</b>        | <a href="#">Eaton Crouse-Hinds CDR3033 3D drawing</a>   |
| <b>BROCHURES</b>                     | <a href="#">PowerMate Drilling Pin and Sleeve Devices brochure</a>  |
| <b>CATALOGS</b>                      | <a href="#">PowerMate Drilling Pin and Sleeve Devices catalog page</a>  |
| <b>CERTIFICATION REPORTS</b>         | <a href="#">PowerMate Drilling Pin and Sleeve Devices UL certification (Receptacles)</a>  |
| <b>INSTALLATION INSTRUCTIONS</b>     | <a href="#">IF 1834 - PowerMate Pin and Sleeve Devices with Nested Bushing</a><br><a href="#">IF 1632 - 30, 60, 100 and 150A PowerMate Pin and Sleeve Devices</a> |
| <b>SPECIFICATIONS AND DATASHEETS</b> | <a href="#">Eaton Specification Sheet - CDR3033</a><br><a href="#">PowerMate Connectors</a>   |

## Product specifications

|                        |                        |
|------------------------|------------------------|
| <b>AMPERAGE RATING</b> | 30A                    |
| <b>GROUNDING TYPE</b>  | Style 1                |
| <b>CONFIGURATION</b>   | Three-wire, three-pole |
| <b>VOLTAGE RATING</b>  | 600 Vac/250 Vdc        |
| <b>MATERIAL</b>        | Copper-free aluminum   |

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.



# Specifications

Photo is representative

## Eaton CDR3033

Eaton Crouse-Hinds series PowerMate CDR receptacle, 30A, Three-wire, three-pole, Style 1, Copper-free aluminum, 600 Vac/250 Vdc

### General specifications

|                             |  |
|-----------------------------|--|
| <b>PRODUCT NAME</b>         | Eaton Crouse-Hinds series PowerMate CDR receptacle |
| <b>CATALOG NUMBER</b>       | CDR3033  |
| <b>UPC</b>                  | 662276277038                                       |
| <b>PRODUCT LENGTH/DEPTH</b> | 2.88 in  |
| <b>PRODUCT HEIGHT</b>       | 3.38 in  |
| <b>PRODUCT WIDTH</b>        | 3.38 in  |
| <b>PRODUCT WEIGHT</b>       | 2.2 lb   |

## Certifications and compliances

|                            |                                  |
|----------------------------|----------------------------------|
| <b>AREA CLASSIFICATION</b> | Ordinary/Non-Hazardous Locations |
| <b>STANDARDS TYPE</b>      | NEC/CEC                          |
| <b>NEMA RATING</b>         | 4X                               |

## Resources

|                                      |   |
|--------------------------------------|---|
| <b>3D CAD DRAWING PACKAGE</b>        | <a href="#">Eaton Crouse-Hinds CDR3033 3D drawing</a>   |
| <b>BROCHURES</b>                     | <a href="#">PowerMate Drilling Pin and Sleeve Devices brochure</a>  |
| <b>CATALOGS</b>                      | <a href="#">PowerMate Drilling Pin and Sleeve Devices catalog page</a>  |
| <b>CERTIFICATION REPORTS</b>         | <a href="#">PowerMate Drilling Pin and Sleeve Devices UL certification (Receptacles)</a>  |
| <b>INSTALLATION INSTRUCTIONS</b>     | <a href="#">IF 1834 - PowerMate Pin and Sleeve Devices with Nested Bushing</a><br><a href="#">IF 1632 - 30, 60, 100 and 150A PowerMate Pin and Sleeve Devices</a> |
| <b>SPECIFICATIONS AND DATASHEETS</b> | <a href="#">Eaton Specification Sheet - CDR3033</a><br><a href="#">PowerMate Connectors</a>   |

## Product specifications

|                        |                        |
|------------------------|------------------------|
| <b>AMPERAGE RATING</b> | 30A                    |
| <b>GROUNDING TYPE</b>  | Style 1                |
| <b>CONFIGURATION</b>   | Three-wire, three-pole |
| <b>VOLTAGE RATING</b>  | 600 Vac/250 Vdc        |
| <b>MATERIAL</b>        | Copper-free aluminum   |

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
[Eaton.com](http://Eaton.com)

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

