

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



CG50100S 1" STL STR Cord Conn *Appleton/Oz Gedney*

Catalog Number	CG50100S
Manufacturer	Appleton/Oz Gedney
Description	Straight Liquidtight Strain Relief Connector, Size: 1 In, Conductor Range: 1/2 - 5/8 In, Material: Machined Steel, Color: Pink Label, Nema Rating: Nema 3R, Connection: Threaded Hub, Dimensions: 1.38 In Height, Standard: Class I, Divisio
Weight per unit	0.3800 (lbs/each)
Product Category	Cable & Cord Grips
Features	
connection	Threaded Hub
Material, Color, and Finish	
Color	/;Pink
Dimensions and Weight	
Size	1
Descriptions	
Description	1" STL STR CORD CONN
extra long description	APP CG-50100S 1 IN STL L-T CRD&CBL
Long Description	Straight Liquidtight Strain Relief Connector, Size: 1 IN, Conductor Range: 1/2 - 5/8 IN, Material: Machined Steel, Color: Pink Label, Nema Rating: NEMA 3R, Connection: Threaded Hub, Dimensions: 1.38 IN Height, Standard: Class I, Divisio
Product Type	1 In STL L-T CRD&CBL Conn
Special Features	Color coded identification label clearly states the catalog number and minimum-maximum cable diameter range for which the connector is designed; For use in wet or dry locations sealing electrical connections against dust and dirt, oil, water or other atmosphere containing moisture; Machined steel cap; Neoprene sealing grommet; Neoprene sealing grommet firmly but safely grips cable jacket providing strain relief while protecting internal wiring connections against external tension on cable or cord; Steel or Tefl
Manufacturer Information	
Brand	Appleton
GTIN	00781381449434
Manufacturers Part Number	CG-50100S
UPC	781381449434



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cat	egories
Category Description	CORD CONNECTORS & CORD GRIPS
Туре	Straight Liquidtight Strain Relief Connector
Packaging	
Carton	1
Package	10
Weight Per each	0.38
Uses, Certifications, and Standards	
Application	For Flexible Type Neoprene, Hypalon And PVC Jacketed Power Or Control Cord And Cable
nema rating	3R
standard	Class I. Division 2. Class II. Division 1 And 2 Class III. UL 514B.

E14817, CSA C22.2 No. 18.3, 065178