Specifications

Photo is representative







Eaton CH20L125R

Eaton CH main lug loadcenters, Cover included, Main lug only,125A,C,Copper,NEMA 3R, Metallic, Overhead, CH, 20, 20, Three-RATING wire, Single-phase, 120/240 V, #6-2/0 **AWG**

		MAIN
General specifications		CIRCUIT BREAKER
PRODUCT NAME	Eaton CH main lug loadcenter	NUMBER OF CIRCUITS
CATALOG NUMBER	CH20L125R	NUMBER OF SPACES
UPC	782113097602	
PRODUCT LENGTH/DEPTH	21 in	PHASE
PRODUCT HEIGHT	5.19 in	VOLTAGE RATING
PRODUCT WIDTH	14.31 in	
PRODUCT WEIGHT	16 lb	WIRE SIZE
WARRANTY	Limited lifetime	BOX SIZE
CERTIFICATIONS	UL 67 UL 50	ENCLOSURE
CATALOG NOTES	Suitable for use as service equipment when not more than six service disconnecting mains are provided or when not	ENCLOSURE MATERIAL
		NUMBER OF WIRES
CATALUG NUTES	used as a lighting and appliance panelboard.	

Rainproof panels are furnished with hub closure plates. For rainproof hubs.

Product specificati

SPECIAL **FEATURES**

TYPE

AMPERAGE

BUS **MATERIAL**

FEED TYPE

Specifications

Photo is representative







Eaton CH20L125R

Eaton CH main lug loadcenters, Cover included, Main lug only,125A,C,Copper,NEMA 3R, Metallic, Overhead, CH, 20, 20, Three-RATING wire, Single-phase, 120/240 V, #6-2/0 **AWG**

		MAIN
General specifications		CIRCUIT BREAKER
PRODUCT NAME	Eaton CH main lug loadcenter	NUMBER OF CIRCUITS
CATALOG NUMBER	CH20L125R	NUMBER OF SPACES
UPC	782113097602	
PRODUCT LENGTH/DEPTH	21 in	PHASE
PRODUCT HEIGHT	5.19 in	VOLTAGE RATING
PRODUCT WIDTH	14.31 in	
PRODUCT WEIGHT	16 lb	WIRE SIZE
WARRANTY	Limited lifetime	BOX SIZE
CERTIFICATIONS	UL 67 UL 50	ENCLOSURE
CATALOG NOTES	Suitable for use as service equipment when not more than six service disconnecting mains are provided or when not	ENCLOSURE MATERIAL
		NUMBER OF WIRES
CATALUG NUTES	used as a lighting and appliance panelboard.	

Rainproof panels are furnished with hub closure plates. For rainproof hubs.

Product specificati

SPECIAL **FEATURES**

TYPE

AMPERAGE

BUS **MATERIAL**

FEED TYPE