



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

711 Lake Bardwell Dr.
75119-0000, TX Ennis
Phone: 972-875-3413
Fax: 972-875-3174



CH9MB270 70A 2 Circuit Singleph Cu Bus Oem Interior CH Type

Eaton Corp

Catalog Number	CH9MB270
Manufacturer	Eaton Corp
Description	Eaton CH Mounting Base, Single Phase, Copper Bus, Oem Interior, CH Type, Single Row Breaker Mounting, Mounting Base, 70 A, CH, Two-Pole, 0.75 In, 2-Pole CH Circuit Breakers
Weight per unit	0.1000 (lbs/each)
Product Category	Circuit Breaker Accessories

Features

dimensions	4.5000 IN X 1.7500 IN X 1.5000 IN
loadcenter type	CH
media	Yes

Dimensions and Weight

Size	3/4 in
------	--------

Descriptions

Description	70A 2 CIRCUIT SINGLEPH CU BUS OEM INTERIOR CH TYPE
extra long description	ETN CH9MB270 70A, 2 Circuit, 1PH, Cu
Features	Eaton's CH 3/4-inch loadcenters enclose CH circuit breakers for power distribution and circuit protection in residential and light commercial applications. Also called a breaker box, electrical box or even a fuse box, the main function is to take electricity supplied by the utility and distribute it throughout the home to feed lights and receptacles. Covers are typically packaged separately and available as surface or flush mount.
Long Description	Eaton CH Mounting Base, Single phase, copper bus, OEM interior, ch type, single row breaker mounting, Mounting base, 70 A, CH, Two-pole, 0.75 in, 2-pole ch circuit breakers
Product Type	70A, 2 Circuit, 1PH, Cu Bus, Oem Int, CH
Special Features	Single phase, copper bus, OEM interior, ch type, single row breaker mounting

Manufacturer Information

Brand	EATON CUTLER-HAMMER
GTIN	00782113418926
Manufacturers Part Number	CH9MB270
UPC	782113418926



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

711 Lake Bardwell Dr.
75119-0000, TX Ennis
Phone: 972-875-3413
Fax: 972-875-3174

Taxonomies, Classifications, and Categories

Category Description LOADCENTER ACCESSORIES

Type Accessory

Packaging

Carton 1

Weight Per each 0.1

Uses, Certifications, and Standards

Application Other

standard Contact Manufacturer