


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Product Type

Special Features

CHP12L125X0 CH Pon Loadcntr 125A Mlo 12 Space *Eaton Corp*

Eaton Corp	
Catalog Number	CHP12L125X0
Manufacturer	Eaton Corp
Description	Eaton CH Main Lug Loadcenters, Pon, CH, 125 A, X0, Copper, !, Nema 1 Indoor, Steel, 25 Kaic, 24, 12, 3, Single-Phase, 120/240 V, #6-2/0 Awg
Weight per unit	10.1 (lbs/each)
Product Category	Cingle Dhoos Main Lyn Lood Con
Features	
amperage rating	125
interrupt rating	25
media	Yes
number of spaces	
Phase	1
Voltage Rating	120/240 V
Dimensions and Weight	
Depth	16.75
Height	
Size	X0
Width	14.3
Descriptions	
Description	CH PON LOADCNTR 125A MLO 12 SPACE
extra long description	ETN CHP12L125X0 CH PON Loadcenter,
Features	Eaton's CH 3/4-inch loadcenters enclose CH circuit breakers for
	power distribution and circuit protection in residential and light
	commercial applications. Also called a breaker box, electrical box
	or even a fuse box, the main function is to take electricity
	supplied by the utility and distribute it throughout the home to
	feed lights and receptacles. Covers are typically packaged
Laura Danadatian	separately and available as surface or flush mount.
Long Description	Eaton CH main lug loadcenters, PON, CH, 125 A, X0, Copper, !, NEMA 1 indoor, Steel, 25 kAIC, 24, 12, 3, Single-phase, 120/240

V, #6-2/0 AWG

PON

CH Pon Loadcenter, 125A, Mlo, 12 Spaces



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Inform

Brand	Eaton	
GTIN	00786689054267	
Manufacturers Part Number	CHP12L125X0	
UPC	786689054267	

Taxonomies, Classifications, and Categories

Category Description	LOADCENTERS & COVERS
Туре	Main lug loadcenter

Packaging

onaging	
Carton	1
Weight Per each	10.1

Uses, Certifications, and Standards

Application	Elec Assemblies, Panels & EOEM - Electrical Assemblies, Panels
	and EOEMs
standard	UL 67