

Elliott Electric Supply

Y 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

We Deliver...Lower Cost, Quality Products, & Personal Service



CHP22B125R CH Pon Loadcntr 125A Main BRKR 22 Space N3R Eaton Corp

Catalog Number	CHP22B125R
Manufacturer	Eaton Corp
Description	Eaton CH Main Breaker Loadcenters, Cover Included, Main Breaker, 125 A, X2, Copper, Nema 3R, Metallic, CH, 44, 22, Three-Wire, Single-Phase, Overhead, 120/240 V
Weight per unit	
Product Category	
Features	
amperage rating	125
media	
number of spaces	22
Phase	
Voltage Rating	120/240 V
Dimensions and Weight	
Depth	21
Height	
Size	X2
Width	14.31
Descriptions	
Description	CH PON LOADCNTR 125A MAIN BRKR 22 SPACE N3R
extra long description	ETN CHP22B125R CH PON LC, 125A, MB,
Features	Eaton's CH 3/4-inch loadcenters enclose CH circuit breakers for power distribution and circuit protection in residential and light commercial applications. Also called a breaker box, electrical box or even a fuse box, the main function is to take electricity supplied by the utility and distribute it throughout the home to feed lights and receptacles. Covers are typically packaged separately and available as surface or flush mount.
Long Description	Eaton CH main breaker loadcenters,Cover included,Main breaker,125 A,X2,Copper,NEMA 3R,Metallic,CH,44,22,Three-wire,Single-phase,Overhead,120/240 V
Product Type	CH Pon LC, 125A, MB, 22SP, N3R
Special Features	Cover included



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	Eaton
GTIN	00786689058579
Manufacturers Part Number	CHP22B125R
UPC	786689058579
Taxonomies, Classifications, and Cate	egories
Category Description	LOADCENTERS & COVERS
Туре	Main breaker loadcenter
Packaging	
Carton	1
Weight Per each	23
Uses, Certifications, and Standards	
Application	Residential Bldgs & Facilities - Residential Bldgs & Facilities - Other
standard	UL 67,UL 50