

Beam Clamps, Straps, Clamps and Clamp Backs for Rigid Metal Conduit or IMC

| | Catalog Number | Trade Size (Inches) | Dimensions in Inches/Millimeters | | | Hole Diameter | Weight Lbs./Kgs. Per 100 | |
|---|----------------|---------------------|----------------------------------|-----------|------------|---------------|--------------------------|---|
| | | | A | B | C | | | |
| Combination Clamp and Clamp Backs — Steel/Zinc Electroplate | | | | | | | | |
|  | CL-50CB | 1/2 | — | — | — | — | 5.00/2.27 | |
| | CL-75CB | 3/4 | — | — | — | — | 5.00/2.27 | — |
| | CL-100CB | 1 | — | — | — | — | 6.00/2.72 | |
| One-Hole Clamps — Steel/Zinc Electroplate | | | | | | | | |
|  | CL-25 | 1/4 | 0.63/16.0 | 0.47/11.9 | 0.59/15.0 | 0.25/6.3 | 1.70/0.77 | |
| | CL-38 | 3/8 | 0.81/20.6 | 0.63/16.0 | 0.69/17.5 | 0.28/7.1 | 2.60/1.18 | |
| | CL-50 | 1/2 | 1.00/25.4 | 0.75/19.1 | 0.94/23.9 | 0.28/7.1 | 5.00/2.27 | |
| | CL-75 | 3/4 | 1.16/29.5 | 0.75/19.1 | 1.13/28.7 | 0.28/7.1 | 5.90/2.68 | |
| | CL-100 | 1 | 1.34/34.0 | 0.88/22.4 | 1.44/36.6 | 0.34/8.6 | 12.20/5.53 | |
| | CL-125 | 1-1/4 | 1.69/42.9 | 1.00/25.4 | 1.78/45.2 | 0.41/10.4 | 19.00/8.62 | |
| | CL-150 | 1-1/2 | 1.94/49.3 | 1.13/28.7 | 2.00/50.8 | 0.41/10.4 | 25.00/11.34 | |
| | CL-200 | 2 | 2.34/59.4 | 1.19/30.2 | 2.53/64.3 | 0.47/11.9 | 38.00/17.24 | |
| | CL-250 | 2-1/2 | 2.81/71.4 | 1.25/31.8 | 3.03/77.0 | 0.56/14.2 | 76.00/34.47 | |
| | CL-300 | 3 | 3.31/84.1 | 1.25/31.8 | 3.66/93.0 | 0.56/14.2 | 93.00/42.18 | |
| | CL-350 | 3-1/2 | 3.44/87.4 | 1.50/38.1 | 4.16/105.7 | 0.69/17.5 | 123.00/55.79 | |
| | CL-400 | 4 | 3.78/96.0 | 1.50/38.1 | 4.66/118.4 | 0.69/17.5 | 140.00/63.50 | |
| Clamp Backs — Steel — Can be used with EMT | | | | | | | | |
|  | CLB-50 | 1/2 | 2.06/52.3 | 0.88/22.4 | 0.25/6.4 | — | 5.00/2.27 | |
| | CLB-75 | 3/4 | 2.50/63.5 | 1.00/25.4 | 0.25/6.4 | — | 7.00/3.18 | |
| | CLB-100 | 1 | 2.69/68.3 | 1.13/28.7 | 0.25/6.4 | — | 8.60/3.90 | |



COMMERCIAL PRODUCTS: RIGID, IMC AND EMT CLAMPS AND HANGERS

Beam Clamps, Straps, Clamps and Clamp Backs for Rigid Metal Conduit or IMC

| | Catalog Number | Trade Size (Inches) | Dimensions in Inches/Millimeters | | | Hole Diameter | Weight Lbs./Kgs. Per 100 | |
|---|----------------|---------------------|----------------------------------|-----------|------------|---------------|--------------------------|---|
| | | | A | B | C | | | |
| Combination Clamp and Clamp Backs — Steel/Zinc Electroplate | | | | | | | | |
|  | CL-50CB | 1/2 | — | — | — | — | 5.00/2.27 | |
| | CL-75CB | 3/4 | — | — | — | — | 5.00/2.27 | — |
| | CL-100CB | 1 | — | — | — | — | 6.00/2.72 | |
| One-Hole Clamps — Steel/Zinc Electroplate | | | | | | | | |
|  | CL-25 | 1/4 | 0.63/16.0 | 0.47/11.9 | 0.59/15.0 | 0.25/6.3 | 1.70/0.77 | |
| | CL-38 | 3/8 | 0.81/20.6 | 0.63/16.0 | 0.69/17.5 | 0.28/7.1 | 2.60/1.18 | |
| | CL-50 | 1/2 | 1.00/25.4 | 0.75/19.1 | 0.94/23.9 | 0.28/7.1 | 5.00/2.27 | |
| | CL-75 | 3/4 | 1.16/29.5 | 0.75/19.1 | 1.13/28.7 | 0.28/7.1 | 5.90/2.68 | |
| | CL-100 | 1 | 1.34/34.0 | 0.88/22.4 | 1.44/36.6 | 0.34/8.6 | 12.20/5.53 | |
| | CL-125 | 1-1/4 | 1.69/42.9 | 1.00/25.4 | 1.78/45.2 | 0.41/10.4 | 19.00/8.62 | |
| | CL-150 | 1-1/2 | 1.94/49.3 | 1.13/28.7 | 2.00/50.8 | 0.41/10.4 | 25.00/11.34 | |
| | CL-200 | 2 | 2.34/59.4 | 1.19/30.2 | 2.53/64.3 | 0.47/11.9 | 38.00/17.24 | |
| | CL-250 | 2-1/2 | 2.81/71.4 | 1.25/31.8 | 3.03/77.0 | 0.56/14.2 | 76.00/34.47 | |
| | CL-300 | 3 | 3.31/84.1 | 1.25/31.8 | 3.66/93.0 | 0.56/14.2 | 93.00/42.18 | |
| | CL-350 | 3-1/2 | 3.44/87.4 | 1.50/38.1 | 4.16/105.7 | 0.69/17.5 | 123.00/55.79 | |
| | CL-400 | 4 | 3.78/96.0 | 1.50/38.1 | 4.66/118.4 | 0.69/17.5 | 140.00/63.50 | |
| Clamp Backs — Steel — Can be used with EMT | | | | | | | | |
|  | CLB-50 | 1/2 | 2.06/52.3 | 0.88/22.4 | 0.25/6.4 | — | 5.00/2.27 | |
| | CLB-75 | 3/4 | 2.50/63.5 | 1.00/25.4 | 0.25/6.4 | — | 7.00/3.18 | |
| | CLB-100 | 1 | 2.69/68.3 | 1.13/28.7 | 0.25/6.4 | — | 8.60/3.90 | |



COMMERCIAL PRODUCTS: RIGID, IMC AND EMT CLAMPS AND HANGERS