

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



CS6364C LKG Conn, 50A 125/250V, 3P4W Hubbell Wiring Devices

Catalog Number	CS6364C
Manufacturer	Hubbell Wiring Devices
Description	Locking Devices, Twist-Lock®, Industrial, Female Connector Body 50A 125/250V, 3-Pole 4-Wire Grounding, Non-Nema, Screw Terminal, Black and White
Weight per unit	1.2 (lbs/each)
Product Category	Plugs, Connectors, Inlets, Out
eatures	
amperage rating	50
connection	Pressure Screw Terminal
Current Rating	
insulation	Insulated Body
Material	Nylon
Number of Conductors	4
pallet quantity	1190
Poles	3-Pole
Voltage Rating	125/250
aterial, Color, and Finish	
Color	Black;White
mensions and Weight	
Size	6.50 in x 2.56 in x 2.50 in
escriptions	
Description	LKG CONN, 50A 125/250V, 3P4W
extra long description	HWDK CS6364C LKG CONN, 50A 125/250V
Features	Hubbell's 50 Amp Twist-Lock® Devices feature a heavy-duty
	design and super-tough nylon housing built for heavy-duty
	applications and impact resistance, even in the harshest
	environments. Their rigid construction restricts contact
	distortion, minimizing the possibility of mating dissimilar device
	The cord grip's offset gripping jaws securely hold the conductors
Long Description	and the cord jacket for excellent strain relief. Locking Devices, Twist-Lock®, Industrial, Female Connector Body
Long Description	50A 125/250V, 3-Pole 4-Wire Grounding, Non-NEMA, Screw
	- The state of the
	Terminal, Black and White
Product Type	Terminal, Black and White LKG Conn, 50A 125/250V, 3P4W



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

1 /1 /	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	・ヘヘキロ	IPAPI	ntari	nation

Brand	WIRING DEVICE-KELLEMS
GTIN	00783585827971
Manufacturers Part Number	CS6364C
UPC	783585827971

Taxonomies, Classifications, and Categories

Category Description	NEMA RATED TURNLOK PLUGS, CONNECTORS, & RECEPTICLES
Туре	Connector Body

Packaging

Magnig		
Carton	1	
Package	10	
Weight Per each		

Uses, Certifications, and Standards

Application	Heavy Duty Industrial
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Cord
nema rating	Non-NEMA
standard	Certified to CSA C22.2 No.42;Listed to UL 498