



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



CS76 1/0 to 4ALCU Comsplice

Abb Installation Products, Inc

| | |
|------------------|---|
| Catalog Number | CS76 |
| Manufacturer | Abb Installation Products, Inc |
| Description | Aluminum 2 Inch Service Entrance Compression Splice For Wire Range - End A: 1/0 Ascr, 1/0 Stranded, Yellow, End B: 4 6/1, 7/1 Ascr, 3-4 Stranded, 2 Solid, Orange, Die: 5/8. For Al-Al or Al-Cu Conductors. |
| Weight per unit | 0.0530 (lbs/each) |
| Product Category | Large Terminals & Connectors |

Features

| | |
|----------------------|-------------|
| connection | Compression |
| insulation | None |
| Material | Aluminum |
| Number of Conductors | 2 |

Dimensions and Weight

| | |
|------|--------|
| Size | 2 INCH |
|------|--------|

Descriptions

| | |
|------------------------|---|
| Description | 1/0 TO 4ALCU COMPSPLICE |
| extra long description | ABB CS76 AL SERVENTR COMP SPLICE A: |
| Long Description | Aluminum 2 Inch Service Entrance Compression Splice for Wire Range - End A: 1/0 ASCR, 1/0 Stranded, Yellow, End B: 4 6/1, 7/1 ASCR, 3-4 Stranded, 2 Solid, Orange, Die: 5/8. For AL-AL or AL-CU Conductors. |
| Product Type | Al Serventr Comp Splice A:1/0 B:3-4 |
| Special Features | Constructed from Aluminum for High Conductivity. Solid Center Barriers and large Chamfers for easy cable insertion. Prefilled with Oxide Inhibitor to prevent oxidation and keep out moisture. All Splices are color coded and marked with strip lengths, installation die codes and compression locations, providing easy identification for easy installation |

Manufacturer Information

| | |
|---------------------------|----------------------|
| Brand | Blackburn Mechanical |
| GTIN | 00783786100637 |
| Manufacturers Part Number | CS76 |
| UPC | 783786100637 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|-------------------------------------|
| Category Description | Comp & Mech Lugs and Butt Splices |
| Type | Compression Splice Service Entrance |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

| | |
|-----------------|-------|
| Carton | 100 |
| Package | 800 |
| Weight Per each | 0.053 |

Uses, Certifications, and Standards

| | |
|--------------------------|--|
| Application | Basic, uninsulated Splices for Service Entrances. For Combinations of Aluminum-to-Aluminum or Aluminum-to-Copper Conductors |
| environmental conditions | All Seasons / Conditions |
| Mounting standard | None RUS Accepted. Complies with ANSI C119.4 when properly installed on Aluminum-to-Aluminum or Aluminum-to-Copper Conductors |