

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



CVX100480Y 100KA, 480V Wye SPD, CVX100-480y Eaton Power Quality

Catalog Number	CVX100480Y
Manufacturer	Eaton Power Quality
Description	Surge Protection Device, CVX100 Series, 100 Kaic, 220/380V, 230/400V, 240/415V, 277/480V, Includes Ground, 640 L-L, 320 L-N, 320 L-G, 320 N-G Operating Voltage, Three-Phase, Four-Wir
Weight per unit	2.0 (lbs/each)
Product Category	Gen Purpose Recept & Surge Pro
eatures	
Phase	
Voltage Rating	220/380 V, 230/400 V, 240/415 V, 277/480 V
imensions and Weight	
Depth	3.55
Height	5.67
Width	4.75
escriptions	
Description	100KA, 480V WYE SPD, CVX100-480Y
extra long description	ETN CVX100-480Y 100kA, 480V WYE SPD
Features	Eaton's CVX050 and CVX100 Surge Protective Devices (SPDs) ensure that a customer's investment in equipment and processe are protected from the damaging effects of voltage transients. Designed for installation on service entrance, branch panels, or individual equipment disconnects, the CVX series provides enhanced surge protection for mission-critical applications. Available in configurations and current capacities of 50 or 100 k/ per phase.
Long Description	Surge Protection Device, CVX100 series, 100 kAIC, 220/380V, 230/400V, 240/415V, 277/480V, Includes ground, 640 L-L, 320 L-N, 320 L-G, 320 N-G operating voltage, Three-phase, Four-wire
Product Type	
lanufacturer Information	
Brand	Eaton
GTIN	00786685216270
Manufacturers Part Number	CVX100-480Y
UPC	786685216270
axonomies, Classifications, and (Categories
Category Description	
Туре	Surge protection device



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	2
Uses, Certifications, and Standards	
Application	Elec Assemblies, Panels & EOEM - Electrical Assemblies and
	EOEMs - Other
standard	UL 1449