




# Dimmers & Fan Speed Controls Decorator Dimmers – Advanced Functionality

**Tap down** once for full Off. Hold paddle up to raise lights, down to lower.

**Sleek, ergonomic P&S Decorator style** matches other Decorator devices.




**Red LED night light** glows when Off.

**Convenient operation** – combines On/Off preset Decorator switch with separate slider microswitch for separate dimming control.


**Soft start control** brings lights up slowly, extends bulb life.

**Constant memory** returns lights to previous level after power failure.

**D600-ELA**



**D600-ELA**



**D1000-ELA**

**NEW**

Catalog Number	Description	Ratings	Color
<b>600W Incandescent Decorator Dimmers*†</b>			
D600-EW D600-EI D600-ELA	Mechanical Preset, Single Pole and 3-Way	600 Watt	White Ivory Light Almond
<b>1000W Incandescent Decorator Dimmers*†</b>			
D1000-EW D1000-EI D1000-ELA	Mechanical Preset, Single Pole and 3-Way	1000 Watt	White Ivory Light Almond
<b>Decorator On/Off Remotes*†</b>			
DR-EW DR-EI DR-ELA	Multilocation/3-Way		White Ivory Light Almond


**NEW**

**NEW**

\* Available in VisionPak™ packaging, add "V" to Catalog Number. Example: D600-ELAV.  
† All dimmers and fan controls can be operated from more than one location when used with DRE remotes. Uses standard 3-way wiring. See wiring diagram.

### WIRING DIAGRAMS

#### Single Pole and Multilocation




# Dimmers & Fan Speed Controls

**Constant memory** returns lights to previous level after power failure.

**Enables On/Off and full dimming control** from an unlimited number of locations.

**LED indicators keep you informed.** Green LEDs indicate preset level and current light level. Red LED night light glows when load is off.

**Easy operation** — Tap up once for preset, twice for full On. Tap down once for full Off. Hold paddle up to raise lights, down to lower.



**Sleek, ergonomic P&S Decorator style** matches other Decorator devices.

**Unobtrusive preset selection button** helps prevent accidental setting changes.

**Change light level** without affecting preset.

**Elegant fade On and Off** extends bulb life. Easy on the eyes, too.

**Installs easily** using the same wiring as conventional 3-way switches.

**D600M-LAV**

*Today's home and business owners want optimum control of their electrical systems. P&S Dimmers & Fan Speed Controls provide that control — along with aesthetics, durability, trouble-free installation, and technologies aimed at solving real-world problems.*

## Index

Device	Rating	Page Number
Catalog Numbering System		L-2
<b>Dimmers</b>		
Decorator Dimmers		
Scene Director Dimmers	120VAC, 60 Hz	L-3, L-4
Advanced Functionality Decorator Multilocation Dimmers	120VAC, 60 Hz	L-5
Advanced Functionality Decorator Dimmers	120VAC, 60 Hz	L-6
TradeMaster® Decorator Slide Dimmers	120VAC, 60 Hz	L-7
Decorator Slide Dimmers	120 & 277VAC, 60 Hz	L-8, L-9
TradeMaster® Short Slide Dimmers	120VAC, 60 Hz	L-10
Toggle Dimmers		
Advanced Functionality Toggle Dimmers	120VAC, 60 Hz	L-11
TradeMaster® Toggle Dimmers	120VAC, 60 Hz	L-12
Rotary Dimmers		
Incandescent, Low Voltage & Fluorescent Rotary Dimmers	120VAC, 60 Hz	L-13, L-14
<b>Fan Speed Controls</b>		
Decorator Fan Speed Controls		
Scene Director & Advanced Functionality Fan Speed Controls	120VAC, 60 Hz	L-15
TradeMaster® Decorator Slide Fan Speed Controls	120VAC, 60 Hz	L-16
Decorator Slide Fan Speed Controls	120VAC, 60 Hz	L-17
TradeMaster® Short Slide Fan Speed Controls	120VAC, 60 Hz	L-18
TradeMaster® Toggle Fan Speed Controls	120VAC, 60 Hz	L-18
Rotary Fan Speed Controls	120VAC, 60 Hz	L-19, L-20
<b>Wall Box Timers</b>		
Rotary Wall Box Timers	125, 125-T, 250 & 277VAC, 60 Hz	L-21
Toggle Wall Box Timers	500W, 1/3 HP, 120VAC, 60 Hz	L-22



**TradeMaster® & Advanced Functionality Dimmers & Fan Speed Controls use an easy-to-understand catalog numbering system:**

## TLV 600 - \*

### Control Type

- D = Decorator
- DS = Decorator Slide
- SC = Scene Controller
- SS = Short Slide
- T = Toggle

### Load Type

- Blank = Incandescent
- FB = Fluorescent Ballast
- IR = Infrared Remote
- LV = Low-Voltage
- ELV = Electronic Low-Voltage
- MC = Master Controller
- DC = Dual Control Dimmer/  
Speed Control
- DH = De-Hummer  
Fan Speed Control
- SC = Fan Speed Control
- R = Remote

### Load Size

- 300 = 300 Watt
- 600 = 600 Watt/VA
- 603 = 600 Watt/VA,  
3-Way
- 1000 = 1000 Watt/VA
- 1003 = 1000 Watt/VA,  
3-Way
- 3 = 3 Amps
- 5 = 5 Amps
- 15 = 1.5 Amps
- 16 = 1.6 Amps

### Package

- Blank = Box
- V = VisionPak™

### Color

- CL = Clear
- GRY = Gray
- I = Ivory
- LA = Light Almond
- LC = Lighted Clear
- W = White

### Options

- E = Electronic Preset
- L = Lighted
- M = Multilocation
- P = Preset

### Examples:

- D600-MLAV** = Decorator Dimmer, Incandescent, 600W, Multilocation, Light Almond, in a VisionPak
- DS600-LLA** = Decorator Slide Dimmer, Incandescent, 600W, Lighted, Light Almond, in a Box
- SSSC5-WV** = Short Slide, Fan Speed Control, 5 Amp, White, in a VisionPak




Many P&S Dimmers & Fan Speed Controls are available boxed or VisionPak™ clam-shell packaging for high-impact merchandising. Please see the Catalog Numbering System above or specific charts for ordering information.



# Dimmers & Fan Speed Controls Decorator Dimmers – Advanced Functionality

**Tap down** once for full Off. Hold paddle up to raise lights, down to lower.

**Sleek, ergonomic P&S Decorator style** matches other Decorator devices.




**Red LED night light** glows when Off.

**Convenient operation** – combines On/Off preset Decorator switch with separate slider microswitch for separate dimming control.


**Soft start control** brings lights up slowly, extends bulb life.

**Constant memory** returns lights to previous level after power failure.

**D600-ELA**



**D600-ELA**



**D1000-ELA**

**NEW**

Catalog Number	Description	Ratings	Color
<b>600W Incandescent Decorator Dimmers*†</b>			
D600-EW D600-EI D600-ELA	Mechanical Preset, Single Pole and 3-Way	600 Watt	White Ivory Light Almond
<b>1000W Incandescent Decorator Dimmers*†</b>			
D1000-EW D1000-EI D1000-ELA	Mechanical Preset, Single Pole and 3-Way	1000 Watt	White Ivory Light Almond
<b>Decorator On/Off Remotes*†</b>			
DR-EW DR-EI DR-ELA	Multilocation/3-Way		White Ivory Light Almond


**NEW**

**NEW**

\* Available in VisionPak™ packaging, add "V" to Catalog Number. Example: D600-ELAV.  
† All dimmers and fan controls can be operated from more than one location when used with DRE remotes. Uses standard 3-way wiring. See wiring diagram.

### WIRING DIAGRAMS

#### Single Pole and Multilocation




# Dimmers & Fan Speed Controls

**Constant memory** returns lights to previous level after power failure.

**Enables On/Off and full dimming control** from an unlimited number of locations.

**LED indicators keep you informed.** Green LEDs indicate preset level and current light level. Red LED night light glows when load is off.

**Easy operation** — Tap up once for preset, twice for full On. Tap down once for full Off. Hold paddle up to raise lights, down to lower.



**D600M-LAV**

**Sleek, ergonomic P&S Decorator style** matches other Decorator devices.

**Unobtrusive preset selection button** helps prevent accidental setting changes.

**Change light level** without affecting preset.

**Elegant fade On and Off** extends bulb life. Easy on the eyes, too.

**Installs easily** using the same wiring as conventional 3-way switches.

*Today's home and business owners want optimum control of their electrical systems. P&S Dimmers & Fan Speed Controls provide that control — along with aesthetics, durability, trouble-free installation, and technologies aimed at solving real-world problems.*

## Index

Device	Rating	Page Number
Catalog Numbering System		L-2
<b>Dimmers</b>		
Decorator Dimmers		
Scene Director Dimmers	120VAC, 60 Hz	L-3, L-4
Advanced Functionality Decorator Multilocation Dimmers	120VAC, 60 Hz	L-5
Advanced Functionality Decorator Dimmers	120VAC, 60 Hz	L-6
TradeMaster® Decorator Slide Dimmers	120VAC, 60 Hz	L-7
Decorator Slide Dimmers	120 & 277VAC, 60 Hz	L-8, L-9
TradeMaster® Short Slide Dimmers	120VAC, 60 Hz	L-10
Toggle Dimmers		
Advanced Functionality Toggle Dimmers	120VAC, 60 Hz	L-11
TradeMaster® Toggle Dimmers	120VAC, 60 Hz	L-12
Rotary Dimmers		
Incandescent, Low Voltage & Fluorescent Rotary Dimmers	120VAC, 60 Hz	L-13, L-14
<b>Fan Speed Controls</b>		
Decorator Fan Speed Controls		
Scene Director & Advanced Functionality Fan Speed Controls	120VAC, 60 Hz	L-15
TradeMaster® Decorator Slide Fan Speed Controls	120VAC, 60 Hz	L-16
Decorator Slide Fan Speed Controls	120VAC, 60 Hz	L-17
TradeMaster® Short Slide Fan Speed Controls	120VAC, 60 Hz	L-18
TradeMaster® Toggle Fan Speed Controls	120VAC, 60 Hz	L-18
Rotary Fan Speed Controls	120VAC, 60 Hz	L-19, L-20
<b>Wall Box Timers</b>		
Rotary Wall Box Timers	125, 125-T, 250 & 277VAC, 60 Hz	L-21
Toggle Wall Box Timers	500W, 1/3 HP, 120VAC, 60 Hz	L-22





**TradeMaster® & Advanced Functionality Dimmers & Fan Speed Controls use an easy-to-understand catalog numbering system:**

## TLV 600 - \*

### Control Type

- D = Decorator
- DS = Decorator Slide
- SC = Scene Controller
- SS = Short Slide
- T = Toggle

### Load Type

- Blank = Incandescent
- FB = Fluorescent Ballast
- IR = Infrared Remote
- LV = Low-Voltage
- ELV = Electronic Low-Voltage
- MC = Master Controller
- DC = Dual Control Dimmer/  
Speed Control
- DH = De-Hummer  
Fan Speed Control
- SC = Fan Speed Control
- R = Remote

### Load Size

- 300 = 300 Watt
- 600 = 600 Watt/VA
- 603 = 600 Watt/VA,  
3-Way
- 1000 = 1000 Watt/VA
- 1003 = 1000 Watt/VA,  
3-Way
- 3 = 3 Amps
- 5 = 5 Amps
- 15 = 1.5 Amps
- 16 = 1.6 Amps

### Package

- Blank = Box
- V = VisionPak™

### Color

- CL = Clear
- GRY = Gray
- I = Ivory
- LA = Light Almond
- LC = Lighted Clear
- W = White

### Options

- E = Electronic Preset
- L = Lighted
- M = Multilocation
- P = Preset

### Examples:

- D600-MLAV** = Decorator Dimmer, Incandescent, 600W, Multilocation, Light Almond, in a VisionPak
- DS600-LLA** = Decorator Slide Dimmer, Incandescent, 600W, Lighted, Light Almond, in a Box
- SSSC5-WV** = Short Slide, Fan Speed Control, 5 Amp, White, in a VisionPak



Many P&S Dimmers & Fan Speed Controls are available boxed or VisionPak™ clam-shell packaging for high-impact merchandising. Please see the Catalog Numbering System above or specific charts for ordering information.