

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



DG134016FBC21C DG1 480V FR2 N1 10HP 16A CT 15HP 23A VT W/ BC Eaton Corp

	D0404044FD0040
Catalog Number	DG134016FBC21C
Manufacturer Description	Eaton Corp Eaton Powerxl DG1 Variable Frequency Drive, 380-500V Input 7.5 KW 10 HP CT 3PH 50/60 HZ 16A Output IP21/Type 1 Enclosure FR3 LCD Display Internal Emc Filter and DC Choke Ethernet, RS-485
Weight per unit	27.0 (lbs/each)
Product Category	Ac Drives
Features	
display	LCD graphical
Input Voltage	
keypad	Included
Dimensions and Weight	
Depth	21
Height	14.3
Width	10
Descriptions	
Description	DG1 480V FR2 N1 10HP 16A CT 15HP 23A VT W/ BC
extra long description	ETN DG1-34016FB-C21C DG1,480V FR2 ,
Features	Demand more flexibility. Eaton's PowerXL DG1 general purpose, variable frequency drives are engineered for today's demanding commercial and industrial applications. With an industry leading energy efficiency algorithm, high short-circuit current rating and robust design, the DG1 offers customers increased efficiency, safety and reliability.
Long Description	Eaton PowerXL DG1 variable frequency drive, 380-500V input 7.5 kW 10 Hp CT 3PH 50/60 Hz 16A output IP21/type 1 enclosure FR3 LCD display Internal EMC filter and DC choke EtherNet, RS-485
Product Type	DG1, 480V FR2 , N1, 10HP, 16A/15HP, 23A, BC
Manufacturer Information	
Brand	Eaton
GTIN	00786685878911
Manufacturers Part Number	DG1-34016FB-C21C
UPC	786685878911
Taxonomies, Classifications, and C	Categories

DRIVES

Variable Frequency Drive

Category Description

Type



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	27
Uses, Certifications, and Standards	
Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
Enclosure	IP21/type 1 enclosure
standard	cUL Listed,EN 62061,EN 61800-3,UL 508C,EN ISO 13849-1,EN
	61800-5-1,IEC 61508,UL Listed,GoST-R,CE Marked,RoHS
	Compliant, C-Tick Compliant