

# Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



#### DVCL153PHBR Diva 150W Led 3WAY Brown Clam Lutron

| Catalog Number              | DVCL153PHBR  |
|-----------------------------|--|
| Manufacturer                | Lutron   |
| Description                 | Diva Led+ Dimmer - Gloss Finish, Led, Incandescent/Halogen,<br>3-Way/Single-Pole, 150W Led or 600W Inc/Hal Clamshell<br>Packaging In Brown |
| Weight per unit             | 0.2700 (lbs/each)  |
| Product Category            | Lighting Dimmers   |
| Features                    |  |
| actuator                    | Paddle Switch  |
| connection                  | Wire Leads   |
| Connection Type             | Wire Leads   |
| insulation                  | Plastic  |
| Material                    | Plastic/Metal  |
| media                       | Yes  |
| Poles                       |  |
| Switch Type                 | Paddle Switch  |
| Voltage Rating              | 120  |
| Wattage                     | 600  |
| Material, Color, and Finish |  |
| Color                       | Brown  |
| Finish                      | Gloss  |
| Dimensions and Weight       |  |
| Size                        | 4.69 x 2.94;119 x 75   |
|                             |  |



Weight Per each

# Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Descriptions                          |   |
|---------------------------------------|---|
| Description                           | DIVA 150W LED 3WAY BROWN CLAM   |
| extra long description                | LUT DVCL-153PH-BR DIVA CFL/LED CLAM   |
| Features                              | The Diva LED+ dimmer switch provides optimal dimming<br>performance of LED bulbs. This dimmer switch works with up to<br>150-Watt of dimmable LED/CFL or 600-Watt of<br>incandescent/halogen, allowing you to control multiple bulb<br>types on the same circuit. It is designed to control a broad range<br>of dimmable LED and CFL bulbs from a variety of brands including<br>Philips, Cree, GE, EcoSmart and Lighting Science. The Diva<br>dimmer switch features a paddle switch to turn your lights off or<br>on returning the lights to your fav |
| Long Description                      | Diva LED+ Dimmer - Gloss Finish, LED, Incandescent/Halogen,<br>3-way/single-pole, 150W LED or 600W inc/hal clamshell<br>packaging in brown  |
| Product Type                          | Diva CFL/Led Clam Brown   |
| Special Features                      | Controls 150 W dimmable LED/CFL (screw-base), 600 W<br>incandescent, or halogen loads. Paddle turns on/off. Slide up to<br>brighten, down to dim. Provides reliable dimming of dimmable<br>LEDs/CFLs, as well as halogens and incandescents.  |
| Manufacturer Information              |   |
| Brand                                 | Lutron  |
| GTIN                                  | 00027557003285  |
| Manufacturers Part Number<br>UPC      | DVCL-153PH-BR<br>027557003285   |
| Taxonomies, Classifications, and      | Categories  |
| Category Description                  | Residential dimmers, motion sensors, controls, & photo cells  |
| Туре                                  | Dimmer, 3-way/single-pole, clamshell packaging  |
| Packaging                             |   |
| Carton                                | 3   |
| Package                               | 48  |
| , , , , , , , , , , , , , , , , , , , |   |

0.27



### Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

#### Uses, Certifications, and Standards

| Application              | Lighting Control |
|--------------------------|------------------|
| Enclosure                | Plastic          |
| environmental conditions | Indoor use only  |
| Mounting                 | WALLBOX          |
|                          | 32 to 104        |
| standard                 | UL, CSA, NOM     |