



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1207 Energy Drive
75662-0000, TX Kilgore
Phone: 903-984-8485
Fax: 903-984-8193



E22B11 1NO-1NC Contact Block

Eaton Corp

| | |
|------------------|--|
| Catalog Number | E22B11 |
| Manufacturer | Eaton Corp |
| Description | Eaton E22 Pushbutton Contact Block, 22.5 MM, Non-Metallic Heavy-Duty, 1NO, 1NC |
| Weight per unit | 0.0300 (lbs/each) |
| Product Category | Contact Blocks |

Dimensions and Weight

| | |
|--------|-----|
| Depth | 1.5 |
| Height | 0.5 |
| Width | 1.5 |

Descriptions

| | |
|------------------------|---|
| Description | 1NO-1NC CONTACT BLOCK |
| extra long description | ETN E22B11 CONTACT BLOCK 1NO/1NC |
| Features | Eaton's 22.5 mm industrial heavy-duty pushbutton line offers a wide array of functional, smartly styled illuminated and non-illuminated pushbuttons, selector switches, push-pulls, action and twist-to- release operators. The complete line also includes transformer, full voltage, resistor, LED or neon light units. |
| Long Description | Eaton E22 pushbutton contact block, 22.5 mm, Non-metallic Heavy-Duty, 1NO, 1NC |
| Product Type | Contact Block 1NO/1NC |

Manufacturer Information

| | |
|---------------------------|---------------------|
| Brand | EATON CUTLER-HAMMER |
| GTIN | 00782113699486 |
| Manufacturers Part Number | E22B11 |
| UPC | 782113699486 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|-----------------------------|
| Category Description | MINATURE PILOT DEVICES.22MM |
| Type | Pushbutton accessory |

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Weight Per each | 0.03 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1207 Energy Drive
75662-0000, TX Kilgore
Phone: 903-984-8485
Fax: 903-984-8193

Uses, Certifications, and Standards

Application

Stationary Machinery and Equipment Outside Factory -

Stationary Machinery and Equipment Outside Factory - Other

standard

Lloyd's Register Certified, IEC 947-5-1 MTTA, CSA

Certified, UL 508, CE Marked