



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1308 East 4th Street
79720-0000, TX Big Spring
Phone: 432-264-0316
Fax: 432-264-0483



E22JL2N8 PSHPLL Ma JMSHD AI RD CRBZ Estop

Eaton Corp

Catalog Number	E22JL2N8
Manufacturer	Eaton Corp
Description	Eaton E22 Pushbutton, E22 Pushbutton, 22.5 MM, Non-Metallic Heavy-Duty, 50 MM, Nema 3, 3R, 4, 4X, 12, 13, Non-Illuminated, Maintained, Two-Position Push-Pull, Red Actuator, Mushroom , Anodized Aluminum, Emerg. Stop, No Light Unit
Weight per unit	0.0800 (lbs/each)
Product Category	Push Button Components

Features

actuator	Mushroom
----------	----------

Dimensions and Weight

Height	1.5
Length	2
Size	50 mm
Width	1.5

Descriptions

Description	PSHPLL MA JMSHD AL RD CRBZ ESTOP
extra long description	ETN E22JL2N8 PSHPLL MA JMSHD AL RD
Features	Eaton's 22.5 mm industrial heavy-duty pushbutton line offers a wide array of functional, smartly styled illuminated and non-illuminated pushbuttons, selector switches, push-pulls, action and twist-to- release operators. The complete line also includes transformer, full voltage, resistor, LED or neon light units.
Long Description	Eaton E22 pushbutton, E22 Pushbutton, 22.5 mm, Non-Metallic Heavy-Duty, 50 mm, NEMA 3, 3R, 4, 4X, 12, 13, Non-illuminated, Maintained, two-position push-pull, Red actuator, Mushroom , Anodized aluminum, EMERG. STOP, No light unit
Product Type	PSHPLL Ma JMSHD AI RD CRBZ Estop

Manufacturer Information

Brand	Eaton
GTIN	00782113504056
Manufacturers Part Number	E22JL2N8
UPC	782113504056

Taxonomies, Classifications, and Categories

Category Description	MINATURE PILOT DEVICES.22MM
Type	PUSHBUTTON



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1308 East 4th Street
79720-0000, TX Big Spring
Phone: 432-264-0316
Fax: 432-264-0483

Packaging

Carton	1
Weight Per each	0.08

Uses, Certifications, and Standards

Application	Stationary Machinery and Equipment Outside Factory - Stationary Machinery and Equipment Outside Factory - Other
standard	IEC 947-5-1 MTTA, Lloyd's Register Certified, CSA Certified, UL 508, CE Marked