

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Packaging Carton

Weight Per each

E50KL40 E50 Operating Lever

Catalog Number	E50KL40
Manufacturer	Eaton Corp
Description	E50 Nema Limit Switch, Lever, Rotary Lever, 1.38 Inch Len,
	Stainless Steel, Metal Roller 0.75 Inch Diameter 0.32 Inch Width,
	14-250F(-10-121C), Stainless Steel, Steel, UI, Csa, Ce
Weight per unit	0.1000 (lbs/each)
Product Category	Limit Switch Arms, Actuators &
tures	
actuator	Standard roller
dimensions	2.1000 IN X 0.7500 IN X 0.6500 IN
criptions	
Description	E50 OPERATING LEVER
extra long description	ETN E50KL40 E50 LS LEVER,SS,MET ROL
Features	Eaton's E50 modular plug-in limit switches are the industry
	standard with versatility of design and high reliability for low
	maintenance, installation and inventory costs. Standard Viton
	gaskets, seals and boots and a zinc die -cast enclosure provide
	exceptional chemical resistance to the common coolants,
	cleansing agents and hydraulic fluids found in machine tool,
	automotive, wastewater treatment and other heavy-duty
	industrial applications. Mounting dimensions accommodate both
	U.S. and DIN standards for
Long Description	E50 NEMA Limit Switch, Lever, Rotary lever, 1.38 inch len, Stainless
	steel, Metal roller 0.75 inch diameter 0.32 inch
Product Type	width,14-250F(-10-121C),Stainless Steel,Steel, UL,CSA,CE E50 LS Lever, SS, Met Roller, 1.38IN Length
3.	E30 L3 Level , 33, Iviet Rollel , 1.36liv Leligtii
nufacturer Information	
Brand GTIN	EATON CUTLER-HAMMER 00782113317496
Manufacturers Part Number	E50KL40
LIDC	782113317496
onomies, Classifications, and C	
Category Description	
Type	Heavy duty plug-in limit switch accessory

1

0.1

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	CSA Certified,UL Listed,CE,RoHS Compliant,CE Marked