

# EASY-TWIST™

## Wire Connectors

### Combination Pails

#### ET-CP Series



#### SPECIFICATIONS

- UL 486C Listed wire connector E155027.
- **Temperature Rating:** 105 °C (221 °F).
- **Voltage:** 1,000V max. in fixtures and signs.
- **Wire Type:** For Copper wire only.

#### FEATURES

- Compact, easy to carry pail, also convenient for use on maintenance cart.
- 4-pack pail includes the most common Easy-twist™ connectors.



Scan QR code for mobile access to wire combinations.

| CAT. NO. | FIG. NO. | PAIL CONTENTS | COLOR     | WIRE RANGE | QTY. PER PAIL | STD. CTN. QTY. |
|----------|----------|---------------|-----------|------------|---------------|----------------|
| ET-CP-1  | 1        | WWC-T         | Tan       | 22-8 AWG   | 70            | 12             |
|          |          | WWC-Y         | Yellow    | 18-10 AWG  | 80            | 12             |
|          |          | WWC-R         | Red       | 18-8 AWG   | 45            | 12             |
|          |          | WWC-B         | Blue      | 14-6 AWG   | 20            | 12             |
| ET-CP-2  |          | WC-O          | Orange    | 22-14 AWG  | 100           | 12             |
|          |          | WC-Y          | Yellow    | 22-10 AWG  | 75            | 12             |
|          |          | WC-R          | Red       | 22-10 AWG  | 50            | 12             |
|          |          | WWC-T         | Tan       | 22-8 AWG   | 70            | 12             |
| ET-CP-3  |          | WC-O          | Orange    | 22-14 AWG  | 100           | 12             |
|          |          | WWC-T         | Tan       | 22-8 AWG   | 70            | 12             |
|          |          | WWC-Y         | Yellow    | 18-10 AWG  | 80            | 12             |
| ET-CP-11 |          | WWC-R         | Red       | 18-8 AWG   | 45            | 12             |
|          |          | WWC-T         | Tan       | 22-8 AWG   | 40            | 16             |
|          |          | WWC-Y         | Yellow    | 18-10 AWG  | 50            | 16             |
|          |          | WWC-R         | Red       | 18-8 AWG   | 30            | 16             |
| ET-CP-12 |          | WWC-B         | Blue      | 14-6 AWG   | 10            | 16             |
|          | WC-O     | Orange        | 22-14 AWG | 65         | 16            |                |
|          | WC-Y     | Yellow        | 22-10 AWG | 45         | 16            |                |
|          | WC-R     | Red           | 22-10 AWG | 30         | 16            |                |
| ET-CP-13 | WWC-T    | Tan           | 22-8 AWG  | 40         | 16            |                |
|          | WC-O     | Orange        | 22-14 AWG | 60         | 16            |                |
|          | WWC-T    | Tan           | 22-8 AWG  | 45         | 16            |                |
|          | WWC-Y    | Yellow        | 18-10 AWG | 50         | 16            |                |
| ET-CP-14 | WWC-R    | Red           | 18-8 AWG  | 30         | 16            |                |
|          | WC-O     | Orange        | 22-14 AWG | 65         | 16            |                |
|          | WC-Y     | Yellow        | 22-10 AWG | 45         | 16            |                |
|          | WC-R     | Red           | 22-10 AWG | 30         | 16            |                |
| ET-CP-15 | WC-B     | Blue          | 22-14 AWG | 100        | 16            |                |
|          | WC-G     | Gray          | 22-14 AWG | 120        | 16            |                |
|          | WC-B     | Blue          | 22-14 AWG | 100        | 16            |                |
|          | WC-O     | Orange        | 22-14 AWG | 65         | 16            |                |
|          |          | WC-Y          | Yellow    | 22-10 AWG  | 45            | 16             |

# EASY-TWIST™

## Wire Connectors

### Combination Pails

#### ET-CP Series



#### SPECIFICATIONS

- UL 486C Listed wire connector E155027.
- **Temperature Rating:** 105 °C (221 °F).
- **Voltage:** 1,000V max. in fixtures and signs.
- **Wire Type:** For Copper wire only.

#### FEATURES

- Compact, easy to carry pail, also convenient for use on maintenance cart.
- 4-pack pail includes the most common Easy-twist™ connectors.



Scan QR code for mobile access to wire combinations.

| CAT. NO. | FIG. NO. | PAIL CONTENTS | COLOR     | WIRE RANGE | QTY. PER PAIL | STD. CTN. QTY. |
|----------|----------|---------------|-----------|------------|---------------|----------------|
| ET-CP-1  | 1        | WWC-T         | Tan       | 22-8 AWG   | 70            | 12             |
|          |          | WWC-Y         | Yellow    | 18-10 AWG  | 80            | 12             |
|          |          | WWC-R         | Red       | 18-8 AWG   | 45            | 12             |
|          |          | WWC-B         | Blue      | 14-6 AWG   | 20            | 12             |
| ET-CP-2  |          | WC-O          | Orange    | 22-14 AWG  | 100           | 12             |
|          |          | WC-Y          | Yellow    | 22-10 AWG  | 75            | 12             |
|          |          | WC-R          | Red       | 22-10 AWG  | 50            | 12             |
|          |          | WWC-T         | Tan       | 22-8 AWG   | 70            | 12             |
| ET-CP-3  |          | WC-O          | Orange    | 22-14 AWG  | 100           | 12             |
|          |          | WWC-T         | Tan       | 22-8 AWG   | 70            | 12             |
|          |          | WWC-Y         | Yellow    | 18-10 AWG  | 80            | 12             |
| ET-CP-11 |          | WWC-R         | Red       | 18-8 AWG   | 45            | 12             |
|          |          | WWC-T         | Tan       | 22-8 AWG   | 40            | 16             |
|          |          | WWC-Y         | Yellow    | 18-10 AWG  | 50            | 16             |
| ET-CP-12 |          | WWC-R         | Red       | 18-8 AWG   | 30            | 16             |
|          | WWC-B    | Blue          | 14-6 AWG  | 10         | 16            |                |
|          | WC-O     | Orange        | 22-14 AWG | 65         | 16            |                |
|          | WC-Y     | Yellow        | 22-10 AWG | 45         | 16            |                |
| ET-CP-13 | WC-R     | Red           | 22-10 AWG | 30         | 16            |                |
|          | WWC-T    | Tan           | 22-8 AWG  | 40         | 16            |                |
|          | WC-O     | Orange        | 22-14 AWG | 60         | 16            |                |
|          | WWC-T    | Tan           | 22-8 AWG  | 45         | 16            |                |
| ET-CP-14 | WWC-Y    | Yellow        | 18-10 AWG | 50         | 16            |                |
|          | WWC-R    | Red           | 18-8 AWG  | 30         | 16            |                |
|          | WC-O     | Orange        | 22-14 AWG | 65         | 16            |                |
|          | WC-Y     | Yellow        | 22-10 AWG | 45         | 16            |                |
| ET-CP-15 | WC-R     | Red           | 22-10 AWG | 30         | 16            |                |
|          | WC-B     | Blue          | 22-14 AWG | 100        | 16            |                |
|          | WC-G     | Gray          | 22-14 AWG | 120        | 16            |                |
|          | WC-B     | Blue          | 22-14 AWG | 100        | 16            |                |
|          | WC-O     | Orange        | 22-14 AWG | 65         | 16            |                |
|          | WC-Y     | Yellow        | 22-10 AWG | 45         | 16            |                |