


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





EV186FBQ 22-18AWG #6STD Red Fork TRML

Panduit Corporation

Catalog Number	EV186FBQ
Manufacturer	Panduit Corporation
Description	Stronghold EV18-6FB-Q Contractor Grade Insulated Fork Terminals Are A Reliable and Economical Option That Withstand A Wide Range Of General-Purpose Applications. The Fork Design
	Provides For Fast and Easy Installation, Without The Need to Remove Fastener. Accommodates 22-18 Awg, Compatible With #6 Stud (M3.5), Are Red In Color, and Come In Packages Of 25.
Weight per unit	0.0700 (lbs/each)
Product Category	Small Terminals & Connectors
Features	
connection	Funnel
insulation	Vinyl
Material	Copper
media	Yes
Wire Size	18
Material, Color, and Finish	
Color	Red
Finish	Tinned
Dimensions and Weight	
Size	#6
Descriptions	
Description	22-18AWG #6STD RED FORK TRML
extra long description	PAN EV18-6FB-Q StrongHold™ EV18-6FB
Long Description	StrongHold EV18-6FB-Q Contractor Grade Insulated Fork
	Terminals are a reliable and economical option that withstand a
	wide range of general-purpose applications. The fork design
	provides for fast and easy installation, without the need to
	remove fastener. Accommodates 22-18 AWG, compatible with #6 Stud (M3.5), are red in color, and come in packages of 25.
Product Type	Stronghold™ EV18-6FB-Q Loose Piece Forks, Red, Vinyl, 1/8" S
Manufacturer Information	St. St. grid at 2 10 St. D. & 20030 Flood Forms, flood, villy 1, 17 U. S
Brand	Panduit®
GTIN	00613056366442
Manufacturers Part Number	EV18-6FB-Q
UPC	613056366442
S1 0	01000000112



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories		
Category Description	TERMINALS	
Туре	Fork Terminal	
Packaging		
Carton	25	
Package	250	
Weight Per each	0.07	
Uses, Certifications, and Stand	ards	
Mounting	0.31	

CSA Certified LR31212;UL Listed 587H E52164