

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

## **EYD2 3/4" Female/Male Drain Seal** *Crouse-Hinds*

Crouse-minus	
Catalog Number	EYD2
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Eyd Conduit Sealing Fitting With Drain, Female, Feraloy Iron Alloy and/or Ductile Iron, Vertical Only, 3/4"
Weight per unit	1.2 (lbs/each)
Product Category	Sealing Bodies
Features	
connection	Female Threaded, Female Threaded
dimensions	1.5000 IN X 1.5000 IN X 3.6900 IN
Descriptions	
Description	3/4" FEMALE/MALE DRAIN SEAL
extra long description	CRS-H EYD2 3/4 NPT THRU FEMALE CST
Features	In addition to restricting the passage of gases, vapors or flames
	from one portion of the electrical installation to another,
	Crouse-Hinds series EYD and EZD drain sealing fittings prevent
	accumulation of condensate above the seal. They are installed in
	vertical conduit runs and at low points in conduit systems.
Long Description	Eaton Crouse-Hinds series EYD conduit sealing fitting with drain,
D. J. J. T	Female, Feraloy iron alloy and/or ductile iron, Vertical only, 3/4"
Product Type	3/4 NPT Thru Female CST Iron Drain Seal
Special Features	With Drain, Vertical Position
Manufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274375205
Manufacturers Part Number	EYD2
UPC	782274375205
Taxonomies, Classifications, and	Categories
Category Description	HAZARDOUS LOCATION FITTINGS
Туре	Conduit sealing fitting with drain
Packaging	
Carton	1
Package	5
MARIE December	1.00

1.22

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Uses, Certifications, and Standards**

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	CLASS I DIV 1 2 GROUP C D, CLASS II DIV 1 2 GROUP E F G, CLASS
	III
standard	UL 886, CSA C22.2